



GENERAL NOTES:

1. FENCE BOARDS SHALL BE #2 & BTR. CEDAR DOG EAR PICKETS.
2. FENCE RAILS SHALL BE 2x4 DOUGLAS FIR, No. 2 & BTR OR PRESSURE TREATED WHEN RAILS ARE TO BE UNSTAINED.
3. All FENCE HARDWARE SHALL BE GALVANIZED STEEL.
4. RAIL HARDWARE AT CORNER POST SHALL CONTAIN BOTTOM LIP.
5. FENCE HARDWARE SHALL BE ANCHORED WITH #10 X 1 1/2" CONNECTOR SCREWS WITH HEX FLANGE TYPE HEAD. HARDWARE SHALL BE ANCHORED TO RAILS WITH NOT LESS THAN (4) STRUCTURAL CONNECTORS.
6. FENCE RAILS SHALL BE CONNECTED TO LINE POST WITH ADJUSTABLE WOOD ADAPTOR CLAMPS CONTAINING A BOTTOM LIP ALLOWING RAILS TO BE ADJUSTED TO GRADE SLOPES.
7. FENCE BOARDS AND RAILS SHALL RECEIVE 2 COATS OF A PREMIUM GRADE SEMI-TRANSPARENT OR SOLID COLOR WATER PROOFING EXTERIOR GRADE STAIN & SEALER WITH MANUFACTURERS 25 YR WARRANTY.

REVISION	APPROVED	DATE
ORIGINAL	C. SCHMITZ	3/20/2018

CITY OF SANTEE STANDARD DRAWING

WOOD FENCE

APPROVED:

[Signature]
 PRINCIPAL CIVIL ENGINEER
 R.C.E. 60112 DATE: 3/28/2018

DRAWING NUMBER **PW - 11**