

CITY OF SANTEE

PRIORITY DEVELOPMENT PROJECT (PDP)
STORM WATER QUALITY MANAGEMENT PLAN (SWQMP)
FOR
Santee Community Center
[INSERT PERMIT APPLICATION NUMBERS]

10129 Riverwalk Drive
Santee, CA 92071

ASSESSOR'S PARCEL NUMBER(S):
381-051-14-00
ENGINEER OF WORK:



Sarah Curran C69620
[PROVIDE WET SIGNATURE AND STAMP ABOVE LINE]

PREPARED FOR:

City of Santee
10601 Magnolia Ave.
Santee, CA 92071
(619) 258-4100

PDP SWQMP PREPARED BY:

Psomas
401 B St., Suite 1600
San Diego, CA 92101
(619)961-2800

DATE OF SWQMP:
February 2025

PLANS PREPARED BY:

Psomas
401 B St., Suite 1600
San Diego, CA 92101
(619) 961-2800

Page intentionally blank

TABLE OF CONTENTS

Acronym Sheet

PDP SWQMP Preparer's Certification Page

PDP SWQMP Project Owner's Certification Page

Submittal Record

Project Vicinity Map

FORM I-1 Applicability of Permanent, Post-Construction Storm Water BMP Requirements

FORM I-2 Project Type Determination Checklist (Standard Project or PDP)

FORM I-3B Site Information Checklist for PDPs

FORM I-4 Source Control BMP Checklist for All Development Projects

FORM I-5 Site Design BMP Checklist for All Development Projects

FORM I-6 Summary of PDP Structural BMPs

Attachment 1: Backup for PDP Pollutant Control BMPs

Attachment 1a: DMA Exhibit

Attachment 1b: Tabular Summary of DMAs and Design Capture Volume Calculations

Attachment 1c: Harvest and Use Feasibility Screening (when applicable)

Attachment 1d: Categorization of Infiltration Feasibility Condition (when applicable)

Attachment 1e: Pollutant Control BMP Design Worksheets / Calculations

Attachment 2: Backup for PDP Hydromodification Control Measures

Attachment 2a: Hydromodification Management Exhibit

Attachment 2b: Management of Critical Coarse Sediment Yield Areas

Attachment 2c: Geomorphic Assessment of Receiving Channels

Attachment 2d: Flow Control Facility Design

Attachment 3: Structural BMP Maintenance Plan

Attachment 3a: B Structural BMP Maintenance Thresholds and Actions

Attachment 3b: Draft Maintenance Agreement (when applicable)

Attachment 4: Copy of Plan Sheets Showing Permanent Storm Water BMPs

ACRONYMS

APN	Assessor's Parcel Number
BMP	Best Management Practice
HMP	Hydromodification Management Plan
HSG	Hydrologic Soil Group
MS4	Municipal Separate Storm Sewer System
N/A	Not Applicable
NRCS	Natural Resources Conservation Service
PDP	Priority Development Project
PE	Professional Engineer
SC	Source Control
SD	Site Design
SDRWQCB	San Diego Regional Water Quality Control Board
SIC	Standard Industrial Classification
SWQMP	Storm Water Quality Management Plan

SWQMP PREPARER'S CERTIFICATION PAGE

Project Name: Santee Community Center
Permit Application Number: CIP 2018-31

PREPARER'S CERTIFICATION

I hereby declare that I am the Engineer in Responsible Charge of design of storm water best management practices (BMPs) for this project, and that I have exercised responsible charge over the design of the BMPs as defined in Section 6703 of the Business and Professions Code, and that the design is consistent with the PDP requirements of the City of Santee BMP Design Manual, which is a design manual for compliance with local City of San Diego and regional MS4 Permit (California Regional Water Quality Control Board San Diego Region Order No. R9-2015-0100) requirements for storm water management.

I have read and understand that the City of Santee has adopted minimum requirements for managing urban runoff, including storm water, from land development activities, as described in the BMP Design Manual. I certify that this PDP SWQMP has been completed to the best of my ability and accurately reflects the project being proposed and the applicable BMPs proposed to minimize the potentially negative impacts of this project's land development activities on water quality. I understand and acknowledge that the plan check review of this PDP SWQMP by the City Engineer is confined to a review and does not relieve me, as the Engineer in Responsible Charge of design of storm water BMPs for this project, of my responsibilities for project design.



C69620 Exp. 06/30/26

Engineer of Work's Signature, PE Number & Expiration Date

Sarah Curran

Print Name

Psomas

Company

07/07/2025

Date

Engineer's Seal: .



PDP SWQMP Preparation Date: February 2025

Page intentionally blank

SWQMP PROJECT OWNER'S CERTIFICATION PAGE

Project Name: Santee Community Center
Permit Application Number: CIP 2018-31

PROJECT OWNER'S CERTIFICATION

This PDP SWQMP has been prepared for City of Santee by Psomas. The PDP SWQMP is intended to comply with the PDP requirements of the City of Santee BMP Design Manual, which is a design manual for compliance with local City of San Diego and regional MS4 Permit (California Regional Water Quality Control Board San Diego Region Order No. R9-2015-0100) requirements for storm water management.

The undersigned, while it owns the subject property, is responsible for the implementation of the provisions of this plan. Once the undersigned transfers its interests in the property, its successor-in-interest shall bear the aforementioned responsibility to implement the best management practices (BMPs) described within this plan, including ensuring on-going operation and maintenance of structural BMPs. A signed copy of this document shall be available on the subject property into perpetuity.

Project Owner's Signature

Print Name

Company

Date

Page intentionally blank

SUBMITTAL RECORD


Use this Table to keep a record of submittals of this PDP SWQMP. Each time the PDP SWQMP is re-submitted, provide the date and status of the project. In column 4 summarize the changes that have been made or indicate if response to plancheck comments is included. When applicable, insert response to plancheck comments behind this page.

Submittal Number	Date	Project Status	Summary of Changes
1	May 26, 2023	<input checked="" type="checkbox"/> Preliminary Design / Planning/ CEQA <input type="checkbox"/> Final Design	Initial Submittal
2	January 12, 2024	<input type="checkbox"/> Preliminary Design / Planning/ CEQA <input checked="" type="checkbox"/> Final Design	2 nd Submittal
3		<input type="checkbox"/> Preliminary Design / Planning/ CEQA <input type="checkbox"/> Final Design	
4		<input type="checkbox"/> Preliminary Design / Planning/ CEQA <input type="checkbox"/> Final Design	

PROJECT VICINITY MAP

Project Name: Santee Community Center

Permit Application Number: CIP 2018-31



Applicability of Permanent, Post-Construction Storm Water BMP Requirements (Storm Water Intake Form for all Development Permit Applications)		Form I-1 Model BMP Design Manual [August 31, 2015]
Project Identification		
Project Name: Santee Community Center		
Permit Application Number:		Date:
Project Address: 10129 Riverwalk Drive Santee, CA 92071		
Determination of Requirements		
<p>The purpose of this form is to identify permanent, post-construction requirements that apply to the project. This form serves as a short <u>summary</u> of applicable requirements, in some cases referencing separate forms that will serve as the backup for the determination of requirements.</p> <p>Answer each step below, starting with Step 1 and progressing through each step until reaching "Stop". Upon reaching a Stop, do not complete further Steps beyond the Stop.</p> <p>Refer to BMP Design Manual sections and/or separate forms referenced in each step below.</p>		
Step	Answer	Progression
Step 1: Is the project a "development project"? See Section 1.3 of the BMP Design Manual for guidance.	<input checked="" type="checkbox"/> Yes	Go to Step 2.
	<input type="checkbox"/> No	Stop. Permanent BMP requirements do not apply. No SWQMP will be required. Provide discussion below.
Discussion / justification if the project is <u>not</u> a "development project" (e.g., the project includes <i>only</i> interior remodels within an existing building):		
Step 2: Is the project a Standard Project, Priority Development Project (PDP), or exception to PDP definitions? To answer this item, see Section 1.4 of the BMP Design Manual <i>in its entirety</i> for guidance, AND complete Form I-2, Project Type Determination.	<input type="checkbox"/> Standard Project	Stop. <u>Only</u> Standard Project requirements apply, including <u>Standard Project SWQMP</u> .
	<input checked="" type="checkbox"/> PDP	<u>Standard and PDP</u> requirements apply, including <u>PDP SWQMP</u> . Go to Step 3.
	<input type="checkbox"/> Exception to PDP definitions	Stop. <u>Standard Project</u> requirements apply, <u>and any additional requirements specific to the type of project</u> . Provide discussion and list any additional requirements below. Prepare <u>Standard Project SWQMP</u> .

[Step 2 Continued from Page 1] Discussion / justification, and additional requirements for exceptions to PDP definitions, if applicable:

Step 3 (PDPs only). Is the project subject to earlier PDP requirements due to a prior lawful approval? See Section 1.10 of the BMP Design Manual for guidance.	<input type="checkbox"/> Yes	Consult the [City Engineer] to determine requirements. Provide discussion and identify requirements below. Go to Step 4.
	<input checked="" type="checkbox"/> No	BMP Design Manual PDP requirements apply. Go to Step 4.

Discussion / justification of prior lawful approval, and identify requirements (*not required if prior lawful approval does not apply*):

Step 4 (PDPs only). Do hydromodification control requirements apply? See Section 1.6 of the BMP Design Manual for guidance.	<input checked="" type="checkbox"/> Yes	PDP structural BMPs required for pollutant control (Chapter 5) and hydromodification control (Chapter 6). Go to Step 5.
	<input type="checkbox"/> No	Stop. PDP structural BMPs required for pollutant control (Chapter 5) only. Provide brief discussion of exemption to hydromodification control below.

Discussion / justification if hydromodification control requirements do not apply:

Step 5 (PDPs subject to hydromodification control requirements only). Does protection of critical coarse sediment yield areas apply based on review of WMAA Potential Critical Coarse Sediment Yield Area Map? See Section 6.2 of the BMP Design Manual for guidance.	<input type="checkbox"/> Yes	Management measures required for protection of critical coarse sediment yield areas (Chapter 6.2). Stop.
	<input checked="" type="checkbox"/> No	Management measures not required for protection of critical coarse sediment yield areas. Provide brief discussion below. Stop.

Discussion / justification if protection of critical coarse sediment yield areas requirements do not apply:

Critical coarse sediment not located near project site.

Priority Determination Form		Form I-2 Model BMP Design Manual [August 31, 2015]	
Project Information			
Project Name: Santee Community Center			
Permit Application Number:		Date:	
Project Address: 10129 Riverwalk Drive Santee, CA 92071			
Project Type Determination: Standard Project or Priority Development Project (PDP)			
The project is (select one): New Development <input checked="" type="checkbox"/> Redevelopment			
The total proposed newly created or replaced impervious area is: 111,283 ft ² (2.56) acres			
Is the project in any of the following categories, (a) through (f)?			
Yes	No <input checked="" type="checkbox"/>	(a)	New development projects that create 10,000 square feet or more of impervious surfaces (collectively over the entire project site). This includes commercial, industrial, residential, mixed-use, and public development projects on public or private land.
Yes <input checked="" type="checkbox"/>	No	(b)	Redevelopment projects that create and/or replace 5,000 square feet or more of impervious surface (collectively over the entire project site on an existing site of 10,000 square feet or more of impervious surfaces). This includes commercial, industrial, residential, mixed-use, and public development projects on public or private land.
Yes	No <input checked="" type="checkbox"/>	(c)	<p>New and redevelopment projects that create and/or replace 5,000 square feet or more of impervious surface (collectively over the entire project site), and support one or more of the following uses:</p> <ul style="list-style-type: none"> (i) Restaurants. This category is defined as a facility that sells prepared foods and drinks for consumption, including stationary lunch counters and refreshment stands selling prepared foods and drinks for immediate consumption (Standard Industrial Classification (SIC) code 5812). (ii) Hillside development projects. This category includes development on any natural slope that is twenty-five percent or greater. (iii) Parking lots. This category is defined as a land area or facility for the temporary parking or storage of motor vehicles used personally, for business, or for commerce. (iv) Streets, roads, highways, freeways, and driveways. This category is defined as any paved impervious surface used for the transportation of automobiles, trucks, motorcycles, and other vehicles.

Form I-2 Page 2, Form Template Date: August 31, 2015

Yes	No <input checked="" type="checkbox"/>	(d)	<p>New or redevelopment projects that create and/or replace 2,500 square feet or more of impervious surface (collectively over the entire project site), and discharging directly to an Environmentally Sensitive Area (ESA). "Discharging directly to" includes flow that is conveyed overland a distance of 200 feet or less from the project to the ESA, or conveyed in a pipe or open channel any distance as an isolated flow from the project to the ESA (i.e. not commingled with flows from adjacent lands).</p> <p><i>Note: ESAs are areas that include but are not limited to all Clean Water Act Section 303(d) impaired water bodies; areas designated as Areas of Special Biological Significance by the State Water Board and San Diego Water Board; State Water Quality Protected Areas; water bodies designated with the RARE beneficial use by the State Water Board and San Diego Water Board; and any other equivalent environmentally sensitive areas which have been identified by the Copermittees. See BMP Design Manual Section 1.4.2 for additional guidance.</i></p>
Yes	No <input checked="" type="checkbox"/>	(e)	<p>New development projects, or redevelopment projects that create and/or replace 5,000 square feet or more of impervious surface, that support one or more of the following uses:</p> <ul style="list-style-type: none"> (i) Automotive repair shops. This category is defined as a facility that is categorized in any one of the following SIC codes: 5013, 5014, 5541, 7532-7534, or 7536-7539. (ii) Retail gasoline outlets (RGOs). This category includes RGOs that meet the following criteria: (a) 5,000 square feet or more or (b) a projected Average Daily Traffic (ADT) of 100 or more vehicles per day.
Yes	No <input checked="" type="checkbox"/>	(f)	<p>New or redevelopment projects that result in the disturbance of one or more acres of land and are expected to generate pollutants post construction.</p> <p><i>Note: See BMP Design Manual Section 1.4.2 for additional guidance.</i></p>

Does the project meet the definition of one or more of the Priority Development Project categories (a) through (f) listed above?

No – the project is not a Priority Development Project (Standard Project).

☒ Yes – the project is a Priority Development Project (PDP).

The following is for redevelopment PDPs only:

The area of existing (pre-project) impervious area at the project site is: 235,224 acres ft² (A)

The total proposed newly created or replaced impervious area is 111,283 ft² (B)

Percent impervious surface created or replaced (B/A)*100: 47.3%

The percent impervious surface created or replaced is (select one based on the above calculation):

☒ less than or equal to fifty percent (50%) – only new impervious areas are considered PDP

OR

☐ greater than fifty percent (50%) – the entire project site is a PDP

Site Design Checklist For PDPs		Form I-3B (PDPs) Model BMP Design Manual [August 31, 2015]
Project Summary Information		
Project Name	Santee Community Center	
Project Address	10129 Riverwalk Drive Santee, CA 92071	
Assessor's Parcel Number(s) (APN(s))	381-051-14-00	
Permit Application Number	CIP 2018-31	
Project Hydrologic Unit	Select One: <input type="checkbox"/> Santa Margarita 902 <input type="checkbox"/> San Luis Rey 903 <input type="checkbox"/> Carlsbad 904 <input type="checkbox"/> San Dieguito 905 <input type="checkbox"/> Penasquitos 906 <input checked="" type="checkbox"/> San Diego 907 <input type="checkbox"/> Pueblo San Diego 908 <input type="checkbox"/> Sweetwater 909 <input type="checkbox"/> Otay 910 <input type="checkbox"/> Tijuana 911	
Project Watershed (Complete Hydrologic Unit, Area, and Subarea Name with Numeric Identifier)	San Diego River Basin, 434 mi ² 907.1	
Parcel Area (total area of Assessor's Parcel(s) associated with the project)	53.81 Acres (2,343,963 Square Feet)	
Area to be Disturbed by the Project (Project Area)	3.31 Acres (144,344 Square Feet)	
Project Proposed Impervious Area (subset of Project Area)	2.56 Acres (111,283 Square Feet)	
Project Proposed Pervious Area (subset of Project Area)	0.76 Acres (33,061 Square Feet)	
Note: Proposed Impervious Area + Proposed Pervious Area = Area to be Disturbed by the Project. This may be less than the Parcel Area.		

Description of Existing Site Condition

Current Status of the Site (select all that apply):

- ☒ Existing development
- ☐ Previously graded but not built out
- ☐ Demolition completed without new construction
- ☐ Agricultural or other non-impervious use
- ☒ Vacant, undeveloped/natural

Description / Additional Information:

Existing parking lot used by the Cameron Family YMCA.
Existing vacant area North of the Cameron Family YMCA.

Existing Land Cover Includes (select all that apply):

- ☒ Vegetative Cover
- ☒ Non-Vegetated Pervious Areas
- ☒ Impervious Areas

Description / Additional Information:

Existing AC parking lot with landscaped buffer areas.
Proposed parking lot location has existing pervious areas.

Underlying Soil belongs to Hydrologic Soil Group (select all that apply):

- ☐ NRCS Type A
- ☐ NRCS Type B
- ☐ NRCS Type C
- ☒ NRCS Type D

Approximate Depth to Groundwater (GW):

- ☐ GW Depth < 5 feet
- ☐ 5 feet < GW Depth < 10 feet
- ☒ 10 feet < GW Depth < 20 feet
- ☐ GW Depth > 20 feet

Existing Natural Hydrologic Features (select all that apply):

☐ Watercourses

☐ Seeps

☐ Springs

☐ Wetlands

☒ None

Description / Additional Information:

Description of Existing Site Drainage Patterns

How is storm water runoff conveyed from the site? At a minimum, this description should answer:

- (1) whether existing drainage conveyance is natural or urban;
- (2) Is runoff from offsite conveyed through the site? if yes, quantify all offsite drainage areas, design flows, and locations where offsite flows enter the project site, and summarize how such flows are conveyed through the site;
- (3) Provide details regarding existing project site drainage conveyance network, including any existing storm drains, concrete channels, swales, detention facilities, storm water treatment facilities, natural or constructed channels; and
- (4) Identify all discharge locations from the existing project site along with a summary of conveyance system size and capacity for each of the discharge locations. Provide summary of the pre-project drainage areas and design flows to each of the existing runoff discharge locations.

Describe existing site drainage patterns:

The entire existing parking lot south of Riverwalk Drive conveys stormwater to the south of the lot. Runoff surface flow is then conveyed into an existing earthen swale then discharged into Woodglen Vista Creek. The creek eventually discharges into the San Diego River. A summary of the pre-project drainage areas and design flows can be found in the Project's hydrology report.

The vacant area north of the Cameron Family YMCA currently sheet flows south to catch basins located in an earthen swale. From there the drainage is conveyed via pipe to the west where the pipe daylights and outlets into an earthen open channel that flows southerly into Woodglen Vista Creek and eventually into the San Diego River. A summary of the pre-project drainage areas and design flows can be found in the Project's hydrology report.

Description of Proposed Site Development

Project Description / Proposed Land Use and/or Activities:

The community center will be constructed on City-owned property in the Santee Town Center Community Park adjacent to an existing City-owned YMCA facility located at 10129 Riverwalk Drive. The Project will include dedicated facilities for teens and seniors, lobby space, multi-purpose rooms, administrative offices and storage, occupying approximately 12,500 square feet. The Project's site improvements will include complimentary drought tolerant landscape architecture, storm water compliance, environmental documentation, addition of new parking lot area, realignment of adjacent parking facilities (but not replacement of displaced parking) and accessibility compatibility with adjacent features and the new building.

List/describe proposed impervious features of the project (e.g., buildings, roadways, parking lots, courtyards, athletic courts, other impervious features):

The proposed site features one building with support areas and two covered outdoor event spaces and courtyards. The project will also redesign a portion of the existing parking lot. The proposed site will also include the development of a new parking lot to the North of the Cameron Family YMCA.

List/describe proposed pervious features of the project (e.g., landscape areas):

There are four landscaped islands located in the redesigned parking lot as well as planted common areas around the proposed building.

For the proposed new parking lot, there are eight landscaped islands.

Does the project include grading and changes to site topography?

☒ Yes

☐ No

Description / Additional Information:

Grading of the site involves remedial grading per the Project Geotechnical Report requirements and grading to achieve drainage and accessibility compliance requirements around the building and proposed new parking lot area.

Description of Proposed Site Drainage Patterns

Does the project include changes to site drainage (e.g., installation of new storm water conveyance systems)?

☒ Yes

☐ No

If yes, provide details regarding the proposed project site drainage conveyance network, including storm drains, concrete channels, swales, detention facilities, storm water treatment facilities, natural or constructed channels, and the method for conveying offsite flows through or around the proposed project site. Identify all discharge locations from the proposed project site along with a summary of the conveyance system size and capacity for each of the discharge locations. Provide a summary of pre- and post-project drainage areas and design flows to each of the runoff discharge locations. Reference the drainage study for detailed calculations.

Describe proposed site drainage patterns:

Drainage from parking lot areas tributary to our site will be rerouted around our site via a concrete V-gutter that directs the flows to the existing earthen swale and continue to match existing flow conditions. The site has proposed catch basins located in the outdoor event areas to collect surface flows away from the building entryways. There are three biofiltration basins that have a total provided area of 11,000 square feet in order to treat the site and provide hydromodification benefits. Drainage of the site conveys the water to the biofiltration basins and eventually will discharge into Woodglen Vista Creek via surface overflow. A summary of the post-project drainage areas and design flows can be found in the Project's hydrology report.

For the northern new parking lot, water will be conveyed to the west and to the south of the site into three new biofiltration basins then discharged into an earthen open channel to the west which then flows southerly into Woodglen Vista Creek. The creek eventually discharges into the San Diego River. A summary of the post-project drainage areas and design flows can be found in the Project's hydrology report.

Identify whether any of the following features, activities, and/or pollutant source areas will be present (select all that apply):

- ☒ On-site storm drain inlets
- ☐ Interior floor drains and elevator shaft sump pumps
- ☐ Interior parking garages
- ☒ Need for future indoor & structural pest control
- ☒ Landscape/Outdoor Pesticide Use
- ☐ Pools, spas, ponds, decorative fountains, and other water features
- ☒ Food service
- ☒ Refuse areas
- ☐ Industrial processes
- ☐ Outdoor storage of equipment or materials
- ☐ Vehicle and Equipment Cleaning
- ☐ Vehicle/Equipment Repair and Maintenance
- ☐ Fuel Dispensing Areas
- ☐ Loading Docks
- ☒ Fire Sprinkler Test Water
- ☒ Miscellaneous Drain or Wash Water
- ☒ Plazas, sidewalks, and parking lots

Description / Additional Information:

There are three catch basins on the project site. The site will have a kitchen area for food service, trash enclosure, and features an outdoor plaza, seating, sidewalks, and parking lot.

Identification and Narrative of Receiving Water and Pollutants of Concern

Describe flow path of storm water from the project site discharge location(s), through urban storm conveyance systems as applicable, to receiving creeks, rivers, and lagoons as applicable, and ultimate discharge to the Pacific Ocean (or bay, lagoon, lake or reservoir, as applicable):

The site has two proposed catch basins located in the outdoor event areas. There are two biofiltration basins that have a required area of 2,000 square feet in order to treat the site. Drainage of the site conveys the water to the biofiltration basins and eventually will discharge into Woodglen Vista Creek. From the creek, the water will be discharged into the San Diego River.

List any 303(d) impaired water bodies within the path of storm water from the project site to the Pacific Ocean (or bay, lagoon, lake or reservoir, as applicable), identify the pollutant(s)/stressor(s) causing impairment, and identify any TMDLs and/or Highest Priority Pollutants from the WQIP for the impaired water bodies:

303(d) Impaired Water Body	Pollutant(s)/Stressor(s)	TMDLs / WQIP Highest Priority Pollutant
San Diego River	Phosphorus	
	Total Dissolved Solids	
	Nitrogen	
	Indicator Bacteria	Highest Priority Pollutant
	Cadmium	
	Benthic Community Effects	
	Oxygen, Dissolved	
	Toxicity	
	Sulfates	

Identification of Project Site Pollutants*

***Identification of project site pollutants is only required if flow-thru treatment BMPs are implemented onsite in lieu of retention or biofiltration BMPs (note the project must also participate in an alternative compliance program unless prior lawful approval to meet earlier PDP requirements is demonstrated)**

Identify pollutants expected from the project site based on all proposed use(s) of the site (see BMP Design Manual Appendix B.6):

Pollutant	Not Applicable to the Project Site	Expected from the Project Site	Also a Receiving Water Pollutant of Concern
Sediment		X	
Nutrients	X		
Heavy Metals	X		
Organic Compounds		X	
Trash & Debris		X	

Oxygen Demanding Substances	X		
Oil & Grease		X	
Bacteria & Viruses	X		
Pesticides		X	

Hydromodification Management Requirements

Do hydromodification management requirements apply (see Section 1.6 of the BMP Design Manual)?

- ☒ Yes, hydromodification management flow control structural BMPs required.
- ☐ No, the project will discharge runoff directly to existing underground storm drains discharging directly to water storage reservoirs, lakes, enclosed embayments, or the Pacific Ocean.
- ☐ No, the project will discharge runoff directly to conveyance channels whose bed and bank are concrete-lined all the way from the point of discharge to water storage reservoirs, lakes, enclosed embayments, or the Pacific Ocean.
- ☐ No, the project will discharge runoff directly to an area identified as appropriate for an exemption by the WMAA for the watershed in which the project resides.

Description / Additional Information (to be provided if a 'No' answer has been selected above):

Critical Coarse Sediment Yield Areas*

***This Section only required if hydromodification management requirements apply**

Based on the maps provided within the WMAA, do potential critical coarse sediment yield areas exist within the project drainage boundaries?

☐ Yes

☒ No, No critical coarse sediment yield areas to be protected based on WMAA maps

If yes, have any of the optional analyses presented in Section 6.2 of the BMP Design Manual been performed?

☐ 6.2.1 Verification of Geomorphic Landscape Units (GLUs) Onsite

☐ 6.2.2 Downstream Systems Sensitivity to Coarse Sediment

☐ 6.2.3 Optional Additional Analysis of Potential Critical Coarse Sediment Yield Areas Onsite

☐ No optional analyses performed, the project will avoid critical coarse sediment yield areas identified based on WMAA maps

If optional analyses were performed, what is the final result?

☐ No critical coarse sediment yield areas to be protected based on verification of GLUs onsite

☐ Critical coarse sediment yield areas exist but additional analysis has determined that protection is not required. Documentation attached in Attachment 2.b of the SWQMP.

☐ Critical coarse sediment yield areas exist and require protection. The project will implement management measures described in Sections 6.2.4 and 6.2.5 as applicable, and the areas are identified on the SWQMP Exhibit.

Discussion / Additional Information:

The City of San Diego Regional Watershed Management Area analysis provided mapping of Critical Coarse Sediment Yield areas. The location of our project is not near a Coarse Sediment Yield area. Refer to Attachment 2b.

Flow Control for Post-Project Runoff*

***This Section only required if hydromodification management requirements apply**

List and describe point(s) of compliance (POCs) for flow control for hydromodification management (see Section 6.3.1). For each POC, provide a POC identification name or number correlating to the project's HMP Exhibit and a receiving channel identification name or number correlating to the project's HMP Exhibit.

Drainage of the site is conveyed via catch basins and daylighted roof drainage is piped to the biofiltration basins and will then discharge into Woodglen Vista Creek. From the creek, the water will flow to the San Diego River. Biofiltration basins are sized for hydromodification. Please refer to the HMP exhibit for the discharge area.

Has a geomorphic assessment been performed for the receiving channel(s)?

☒ No, the low flow threshold is 0.1Q2 (default low flow threshold)

☐ Yes, the result is the low flow threshold is 0.1Q2

☐ Yes, the result is the low flow threshold is 0.3Q2

☐ Yes, the result is the low flow threshold is 0.5Q2

If a geomorphic assessment has been performed, provide title, date, and preparer:

Discussion / Additional Information: (optional)

Other Site Requirements and Constraints

When applicable, list other site requirements or constraints that will influence storm water management design, such as zoning requirements including setbacks and open space, or local codes governing minimum street width, sidewalk construction, allowable pavement types, and drainage requirements.

None.

Optional Additional Information or Continuation of Previous Sections As Needed

This space provided for additional information or continuation of information from previous sections as needed.

Source Control BMP Checklist for All Development Projects (Standard Projects and Priority Development Projects)		Form I-4 Model BMP Design Manual [August 31, 2015]	
Project Identification			
Project Name: Santee Community Center			
Permit Application Number: CIP 2018-31			
Source Control BMPs			
All development projects must implement source control BMPs SC-1 through SC-6 where applicable and feasible. See Chapter 4 and Appendix E of the Model BMP Design Manual for information to implement source control BMPs shown in this checklist.			
Answer each category below pursuant to the following.			
<ul style="list-style-type: none"> • "Yes" means the project will implement the source control BMP as described in Chapter 4 and/or Appendix E of the Model BMP Design Manual. Discussion / justification is not required. • "No" means the BMP is applicable to the project but it is not feasible to implement. Discussion / justification must be provided. • "N/A" means the BMP is not applicable at the project site because the project does not include the feature that is addressed by the BMP (e.g., the project has no outdoor materials storage areas). Discussion / justification may be provided. 			
Source Control Requirement		Applied?	
SC-1 Prevention of Illicit Discharges into the MS4		<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No <input type="checkbox"/> N/A
Discussion / justification if SC-1 not implemented:			
SC-2 Storm Drain Stenciling or Signage		<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No <input type="checkbox"/> N/A
Discussion / justification if SC-2 not implemented:			
SC-3 Protect Outdoor Materials Storage Areas from Rainfall, Run-On, Runoff, and Wind Dispersal		<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No <input type="checkbox"/> N/A
Discussion / justification if SC-3 not implemented:			
SC-4 Protect Materials Stored in Outdoor Work Areas from Rainfall, Run-On, Runoff, and Wind Dispersal		<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No <input type="checkbox"/> N/A
Discussion / justification if SC-4 not implemented:			

Source Control Requirement	Applied?		
SC-5 Protect Trash Storage Areas from Rainfall, Run-On, Runoff, and Wind Dispersal	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	<input type="checkbox"/> N/A
Discussion / justification if SC-5 not implemented:			
SC-6 Additional BMPs Based on Potential Sources of Runoff Pollutants (must answer for each source listed below)			
<input type="checkbox"/> On-site storm drain inlets	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	<input type="checkbox"/> N/A
<input type="checkbox"/> Interior floor drains and elevator shaft sump pumps	<input type="checkbox"/> Yes	<input type="checkbox"/> No	<input checked="" type="checkbox"/> N/A
<input type="checkbox"/> Interior parking garages	<input type="checkbox"/> Yes	<input type="checkbox"/> No	<input checked="" type="checkbox"/> N/A
<input type="checkbox"/> Need for future indoor & structural pest control	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	<input type="checkbox"/> N/A
<input type="checkbox"/> Landscape/Outdoor Pesticide Use	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	<input type="checkbox"/> N/A
<input type="checkbox"/> Pools, spas, ponds, decorative fountains, and other water features	<input type="checkbox"/> Yes	<input type="checkbox"/> No	<input checked="" type="checkbox"/> N/A
<input type="checkbox"/> Food service	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	<input type="checkbox"/> N/A
<input type="checkbox"/> Refuse areas	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	<input type="checkbox"/> N/A
<input type="checkbox"/> Industrial processes	<input type="checkbox"/> Yes	<input type="checkbox"/> No	<input checked="" type="checkbox"/> N/A
<input type="checkbox"/> Outdoor storage of equipment or materials	<input type="checkbox"/> Yes	<input type="checkbox"/> No	<input checked="" type="checkbox"/> N/A
<input type="checkbox"/> Vehicle and Equipment Cleaning	<input type="checkbox"/> Yes	<input type="checkbox"/> No	<input checked="" type="checkbox"/> N/A
<input type="checkbox"/> Vehicle/Equipment Repair and Maintenance	<input type="checkbox"/> Yes	<input type="checkbox"/> No	<input checked="" type="checkbox"/> N/A
<input type="checkbox"/> Fuel Dispensing Areas	<input type="checkbox"/> Yes	<input type="checkbox"/> No	<input checked="" type="checkbox"/> N/A
<input type="checkbox"/> Loading Docks	<input type="checkbox"/> Yes	<input type="checkbox"/> No	<input checked="" type="checkbox"/> N/A
<input type="checkbox"/> Fire Sprinkler Test Water	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	<input type="checkbox"/> N/A
<input type="checkbox"/> Miscellaneous Drain or Wash Water	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	<input type="checkbox"/> N/A
<input type="checkbox"/> Plazas, sidewalks, and parking lots	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	<input type="checkbox"/> N/A

Discussion / justification if SC-6 not implemented. Clearly identify which sources of runoff pollutants are discussed. Justification must be provided for all "No" answers shown above.

Additional BMPs Based on Potential Sources of Runoff Pollutants not applicable to our site.

Site Design BMP Checklist for All Development Projects (Standard Projects and Priority Development Projects)		Form I-5 Model BMP Design Manual [August 31, 2015]	
Project Identification			
Project Name: Santee Community Center			
Permit Application Number: CIP 2018-31			
Site Design BMPs			
<p>All development projects must implement site design BMPs SD-1 through SD-8 where applicable and feasible. See Chapter 4 and Appendix E of the Model BMP Design Manual for information to implement site design BMPs shown in this checklist.</p> <p>Answer each category below pursuant to the following.</p> <ul style="list-style-type: none"> • "Yes" means the project will implement the site design BMP as described in Chapter 4 and/or Appendix E of the Model BMP Design Manual. Discussion / justification is not required. • "No" means the BMP is applicable to the project but it is not feasible to implement. Discussion / justification must be provided. • "N/A" means the BMP is not applicable at the project site because the project does not include the feature that is addressed by the BMP (e.g., the project site has no existing natural areas to conserve). Discussion / justification may be provided. 			
Site Design Requirement		Applied?	
SD-1 Maintain Natural Drainage Pathways and Hydrologic Features		<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No <input type="checkbox"/> N/A
Discussion / justification if SD-1 not implemented:			
SD-2 Conserve Natural Areas, Soils, and Vegetation		<input type="checkbox"/> Yes	<input checked="" type="checkbox"/> No <input type="checkbox"/> N/A
Discussion / justification if SD-2 not implemented: Existing landscaped planters in the parking lot are being removed. Existing pervious area to the south of the project site is being modified to incorporate the Biofiltration BMPs			
SD-3 Minimize Impervious Area		<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No <input type="checkbox"/> N/A
Discussion / justification if SD-3 not implemented:			
SD-4 Minimize Soil Compaction		<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No <input type="checkbox"/> N/A
Discussion / justification if SD-4 not implemented:			
SD-5 Impervious Area Dispersion		<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No <input type="checkbox"/> N/A
Discussion / justification if SD-5 not implemented:			

Site Design Requirement	Applied?		
SD-6 Runoff Collection	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	<input type="checkbox"/> N/A
Discussion / justification if SD-6 not implemented:			
SD-7 Landscaping with Native or Drought Tolerant Species	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	<input type="checkbox"/> N/A
Discussion / justification if SD-7 not implemented:			
SD-8 Harvesting and Using Precipitation	<input type="checkbox"/> Yes	<input type="checkbox"/> No	<input checked="" type="checkbox"/> N/A
Discussion / justification if SD-8 not implemented: Harvest and Use BMP is not feasible for the project site.			

<p align="center">Summary of PDP Structural BMPs</p>	<p align="center">Form I-6 (PDPs) Model BMP Design Manual [August 31, 2015]</p>
<p align="center">Project Identification</p>	
<p>Project Name: Santee Community Center</p>	
<p>Permit Application Number: CIP 2018-31</p>	
<p align="center">PDP Structural BMPs</p>	
<p>All PDPs must implement structural BMPs for storm water pollutant control (see Chapter 5 of the BMP Design Manual). Selection of PDP structural BMPs for storm water pollutant control must be based on the selection process described in Chapter 5. PDPs subject to hydromodification management requirements must also implement structural BMPs for flow control for hydromodification management (see Chapter 6 of the BMP Design Manual). Both storm water pollutant control and flow control for hydromodification management can be achieved within the same structural BMP(s).</p> <p>PDP structural BMPs must be verified by the local jurisdiction at the completion of construction. This may include requiring the project owner or project owner's representative and engineer of record to certify construction of the structural BMPs (see Section 1.12 of the BMP Design Manual). PDP structural BMPs must be maintained into perpetuity, and the local jurisdiction must confirm the maintenance (see Section 7 of the BMP Design Manual).</p> <p>Use this form to provide narrative description of the general strategy for structural BMP implementation at the project site in the box below. Then complete the PDP structural BMP summary information sheet (page 3 of this form) for each structural BMP within the project (copy the BMP summary information page as many times as needed to provide summary information for each individual structural BMP).</p>	
<p>Bio-1 Biofiltration BMPs were selected for this site due to the ample site area to accommodate these basins. Drainage flows are directed to the basins via surface flow and pipes from catch basins throughout the site. These basins are being utilized for flow and pollutant control.</p> <p>(Continue on page 2 as necessary.)</p>	

Structural BMP Summary Information (Copy this page as needed to provide information for each individual proposed structural BMP)	
Structural BMP ID No. BF-1B	
Construction Plan Sheet No. C1.9	
<p>Type of structural BMP:</p> <p><input type="checkbox"/> Retention by harvest and use (HU-1)</p> <p><input type="checkbox"/> Retention by infiltration basin (INF-1)</p> <p><input type="checkbox"/> Retention by bioretention (INF-2)</p> <p><input type="checkbox"/> Retention by permeable pavement (INF-3)</p> <p><input type="checkbox"/> Partial retention by biofiltration with partial retention (PR-1)</p> <p><input checked="" type="checkbox"/> Biofiltration (BF-1)</p> <p><input type="checkbox"/> Biofiltration with Nutrient Sensitive Media Design (BF-2)</p> <p><input type="checkbox"/> Proprietary Biofiltration (BF-3) meeting all requirements of Appendix F</p> <p><input type="checkbox"/> Flow-thru treatment control with prior lawful approval to meet earlier PDP requirements (provide BMP type/description in discussion section below)</p> <p><input type="checkbox"/> Flow-thru treatment control included as pre-treatment/forebay for an onsite retention or biofiltration BMP (provide BMP type/description and indicate which onsite retention or biofiltration BMP it serves in discussion section below)</p> <p><input type="checkbox"/> Flow-thru treatment control with alternative compliance (provide BMP type/description in discussion section below)</p> <p><input type="checkbox"/> Detention pond or vault for hydromodification management</p> <p><input type="checkbox"/> Other (describe in discussion section below)</p>	
<p>Purpose:</p> <p><input type="checkbox"/> Pollutant control only</p> <p><input type="checkbox"/> Hydromodification control only</p> <p><input checked="" type="checkbox"/> Combined pollutant control and hydromodification control</p> <p><input type="checkbox"/> Pre-treatment/forebay for another structural BMP</p> <p><input type="checkbox"/> Other (describe in discussion section below)</p>	
Who will certify construction of this BMP? Provide name and contact information for the party responsible to sign BMP verification forms if required by the [City Engineer] (See Section 1.12 of the BMP Design Manual)	City of Santee
Who will be the final owner of this BMP?	City of Santee
Who will maintain this BMP into perpetuity?	City of Santee
What is the funding mechanism for maintenance?	City of Santee

Structural BMP Summary Information
(Copy this page as needed to provide information for each individual proposed structural BMP)

Structural BMP ID No. BF-1C

Construction Plan Sheet No. C1.9

Type of structural BMP:

- ☐ Retention by harvest and use (HU-1)
☐ Retention by infiltration basin (INF-1)
☐ Retention by bioretention (INF-2)
☐ Retention by permeable pavement (INF-3)
☐ Partial retention by biofiltration with partial retention (PR-1)
☒ Biofiltration (BF-1)
☐ Biofiltration with Nutrient Sensitive Media Design (BF-2)
☐ Proprietary Biofiltration (BF-3) meeting all requirements of Appendix F
☐ Flow-thru treatment control with prior lawful approval to meet earlier PDP requirements (provide BMP type/description in discussion section below)
☐ Flow-thru treatment control included as pre-treatment/forebay for an onsite retention or biofiltration BMP (provide BMP type/description and indicate which onsite retention or biofiltration BMP it serves in discussion section below)
☐ Flow-thru treatment control with alternative compliance (provide BMP type/description in discussion section below)
☐ Detention pond or vault for hydromodification management
☐ Other (describe in discussion section below)

Purpose:

- ☐ Pollutant control only
☐ Hydromodification control only
☒ Combined pollutant control and hydromodification control
☐ Pre-treatment/forebay for another structural BMP
☐ Other (describe in discussion section below)

Who will certify construction of this BMP?
 Provide name and contact information for the party responsible to sign BMP verification forms if required by the [City Engineer] (See Section 1.12 of the BMP Design Manual)

City of Santee

Who will be the final owner of this BMP?

City of Santee

Who will maintain this BMP into perpetuity?

City of Santee

What is the funding mechanism for maintenance?

City of Santee

Structural BMP Summary Information
(Copy this page as needed to provide information for each individual proposed structural BMP)

Structural BMP ID No. BF-1D

Construction Plan Sheet No. C1.9

Type of structural BMP:

- ☐ Retention by harvest and use (HU-1)
- ☐ Retention by infiltration basin (INF-1)
- ☐ Retention by bioretention (INF-2)
- ☐ Retention by permeable pavement (INF-3)
- ☐ Partial retention by biofiltration with partial retention (PR-1)
- ☒ Biofiltration (BF-1)
- ☐ Biofiltration with Nutrient Sensitive Media Design (BF-2)
- ☐ Proprietary Biofiltration (BF-3) meeting all requirements of Appendix F
- ☐ Flow-thru treatment control with prior lawful approval to meet earlier PDP requirements (provide BMP type/description in discussion section below)
- ☐ Flow-thru treatment control included as pre-treatment/forebay for an onsite retention or biofiltration BMP (provide BMP type/description and indicate which onsite retention or biofiltration BMP it serves in discussion section below)
- ☐ Flow-thru treatment control with alternative compliance (provide BMP type/description in discussion section below)
- ☐ Detention pond or vault for hydromodification management
- ☐ Other (describe in discussion section below)

Purpose:

- ☐ Pollutant control only
- ☐ Hydromodification control only
- ☒ Combined pollutant control and hydromodification control
- ☐ Pre-treatment/forebay for another structural BMP
- ☐ Other (describe in discussion section below)

Who will certify construction of this BMP?
 Provide name and contact information for the party responsible to sign BMP verification forms if required by the [City Engineer] (See Section 1.12 of the BMP Design Manual)

City of Santee

Who will be the final owner of this BMP?

City of Santee

Who will maintain this BMP into perpetuity?

City of Santee

What is the funding mechanism for maintenance?

City of Santee

Structural BMP Summary Information (Copy this page as needed to provide information for each individual proposed structural BMP)	
Structural BMP ID No. BF-1E	
Construction Plan Sheet No. C1.9	
<p>Type of structural BMP:</p> <p><input type="checkbox"/> Retention by harvest and use (HU-1)</p> <p><input type="checkbox"/> Retention by infiltration basin (INF-1)</p> <p><input type="checkbox"/> Retention by bioretention (INF-2)</p> <p><input type="checkbox"/> Retention by permeable pavement (INF-3)</p> <p><input type="checkbox"/> Partial retention by biofiltration with partial retention (PR-1)</p> <p><input checked="" type="checkbox"/> Biofiltration (BF-1)</p> <p><input type="checkbox"/> Biofiltration with Nutrient Sensitive Media Design (BF-2)</p> <p><input type="checkbox"/> Proprietary Biofiltration (BF-3) meeting all requirements of Appendix F</p> <p><input type="checkbox"/> Flow-thru treatment control with prior lawful approval to meet earlier PDP requirements (provide BMP type/description in discussion section below)</p> <p><input type="checkbox"/> Flow-thru treatment control included as pre-treatment/forebay for an onsite retention or biofiltration BMP (provide BMP type/description and indicate which onsite retention or biofiltration BMP it serves in discussion section below)</p> <p><input type="checkbox"/> Flow-thru treatment control with alternative compliance (provide BMP type/description in discussion section below)</p> <p><input type="checkbox"/> Detention pond or vault for hydromodification management</p> <p><input type="checkbox"/> Other (describe in discussion section below)</p>	
<p>Purpose:</p> <p><input type="checkbox"/> Pollutant control only</p> <p><input type="checkbox"/> Hydromodification control only</p> <p><input checked="" type="checkbox"/> Combined pollutant control and hydromodification control</p> <p><input type="checkbox"/> Pre-treatment/forebay for another structural BMP</p> <p><input type="checkbox"/> Other (describe in discussion section below)</p>	
Who will certify construction of this BMP? Provide name and contact information for the party responsible to sign BMP verification forms if required by the [City Engineer] (See Section 1.12 of the BMP Design Manual)	City of Santee
Who will be the final owner of this BMP?	City of Santee
Who will maintain this BMP into perpetuity?	City of Santee
What is the funding mechanism for maintenance?	City of Santee

Structural BMP Summary Information (Copy this page as needed to provide information for each individual proposed structural BMP)	
Structural BMP ID No. BF-1F	
Construction Plan Sheet No. C1.9	
<p>Type of structural BMP:</p> <p><input type="checkbox"/> Retention by harvest and use (HU-1)</p> <p><input type="checkbox"/> Retention by infiltration basin (INF-1)</p> <p><input type="checkbox"/> Retention by bioretention (INF-2)</p> <p><input type="checkbox"/> Retention by permeable pavement (INF-3)</p> <p><input type="checkbox"/> Partial retention by biofiltration with partial retention (PR-1)</p> <p><input checked="" type="checkbox"/> Biofiltration (BF-1)</p> <p><input type="checkbox"/> Biofiltration with Nutrient Sensitive Media Design (BF-2)</p> <p><input type="checkbox"/> Proprietary Biofiltration (BF-3) meeting all requirements of Appendix F</p> <p><input type="checkbox"/> Flow-thru treatment control with prior lawful approval to meet earlier PDP requirements (provide BMP type/description in discussion section below)</p> <p><input type="checkbox"/> Flow-thru treatment control included as pre-treatment/forebay for an onsite retention or biofiltration BMP (provide BMP type/description and indicate which onsite retention or biofiltration BMP it serves in discussion section below)</p> <p><input type="checkbox"/> Flow-thru treatment control with alternative compliance (provide BMP type/description in discussion section below)</p> <p><input type="checkbox"/> Detention pond or vault for hydromodification management</p> <p><input type="checkbox"/> Other (describe in discussion section below)</p>	
<p>Purpose:</p> <p><input type="checkbox"/> Pollutant control only</p> <p><input type="checkbox"/> Hydromodification control only</p> <p><input checked="" type="checkbox"/> Combined pollutant control and hydromodification control</p> <p><input type="checkbox"/> Pre-treatment/forebay for another structural BMP</p> <p><input type="checkbox"/> Other (describe in discussion section below)</p>	
Who will certify construction of this BMP? Provide name and contact information for the party responsible to sign BMP verification forms if required by the [City Engineer] (See Section 1.12 of the BMP Design Manual)	City of Santee
Who will be the final owner of this BMP?	City of Santee
Who will maintain this BMP into perpetuity?	City of Santee
What is the funding mechanism for maintenance?	City of Santee

Structural BMP Summary Information (Copy this page as needed to provide information for each individual proposed structural BMP)	
Structural BMP ID No. BF-2A	
Construction Plan Sheet No. C1.9	
<p>Type of structural BMP:</p> <p><input type="checkbox"/> Retention by harvest and use (HU-1)</p> <p><input type="checkbox"/> Retention by infiltration basin (INF-1)</p> <p><input type="checkbox"/> Retention by bioretention (INF-2)</p> <p><input type="checkbox"/> Retention by permeable pavement (INF-3)</p> <p><input type="checkbox"/> Partial retention by biofiltration with partial retention (PR-1)</p> <p><input checked="" type="checkbox"/> Biofiltration (BF-1)</p> <p><input type="checkbox"/> Biofiltration with Nutrient Sensitive Media Design (BF-2)</p> <p><input type="checkbox"/> Proprietary Biofiltration (BF-3) meeting all requirements of Appendix F</p> <p><input type="checkbox"/> Flow-thru treatment control with prior lawful approval to meet earlier PDP requirements (provide BMP type/description in discussion section below)</p> <p><input type="checkbox"/> Flow-thru treatment control included as pre-treatment/forebay for an onsite retention or biofiltration BMP (provide BMP type/description and indicate which onsite retention or biofiltration BMP it serves in discussion section below)</p> <p><input type="checkbox"/> Flow-thru treatment control with alternative compliance (provide BMP type/description in discussion section below)</p> <p><input type="checkbox"/> Detention pond or vault for hydromodification management</p> <p><input type="checkbox"/> Other (describe in discussion section below)</p>	
<p>Purpose:</p> <p><input type="checkbox"/> Pollutant control only</p> <p><input type="checkbox"/> Hydromodification control only</p> <p><input checked="" type="checkbox"/> Combined pollutant control and hydromodification control</p> <p><input type="checkbox"/> Pre-treatment/forebay for another structural BMP</p> <p><input type="checkbox"/> Other (describe in discussion section below)</p>	
Who will certify construction of this BMP? Provide name and contact information for the party responsible to sign BMP verification forms if required by the [City Engineer] (See Section 1.12 of the BMP Design Manual)	City of Santee
Who will be the final owner of this BMP?	City of Santee
Who will maintain this BMP into perpetuity?	City of Santee
What is the funding mechanism for maintenance?	City of Santee

Structural BMP Summary Information (Copy this page as needed to provide information for each individual proposed structural BMP)	
Structural BMP ID No. BF-2B	
Construction Plan Sheet No. C1.9	
<p>Type of structural BMP:</p> <p><input type="checkbox"/> Retention by harvest and use (HU-1)</p> <p><input type="checkbox"/> Retention by infiltration basin (INF-1)</p> <p><input type="checkbox"/> Retention by bioretention (INF-2)</p> <p><input type="checkbox"/> Retention by permeable pavement (INF-3)</p> <p><input type="checkbox"/> Partial retention by biofiltration with partial retention (PR-1)</p> <p><input checked="" type="checkbox"/> Biofiltration (BF-1)</p> <p><input type="checkbox"/> Biofiltration with Nutrient Sensitive Media Design (BF-2)</p> <p><input type="checkbox"/> Proprietary Biofiltration (BF-3) meeting all requirements of Appendix F</p> <p><input type="checkbox"/> Flow-thru treatment control with prior lawful approval to meet earlier PDP requirements (provide BMP type/description in discussion section below)</p> <p><input type="checkbox"/> Flow-thru treatment control included as pre-treatment/forebay for an onsite retention or biofiltration BMP (provide BMP type/description and indicate which onsite retention or biofiltration BMP it serves in discussion section below)</p> <p><input type="checkbox"/> Flow-thru treatment control with alternative compliance (provide BMP type/description in discussion section below)</p> <p><input type="checkbox"/> Detention pond or vault for hydromodification management</p> <p><input type="checkbox"/> Other (describe in discussion section below)</p>	
<p>Purpose:</p> <p><input type="checkbox"/> Pollutant control only</p> <p><input type="checkbox"/> Hydromodification control only</p> <p><input checked="" type="checkbox"/> Combined pollutant control and hydromodification control</p> <p><input type="checkbox"/> Pre-treatment/forebay for another structural BMP</p> <p><input type="checkbox"/> Other (describe in discussion section below)</p>	
Who will certify construction of this BMP? Provide name and contact information for the party responsible to sign BMP verification forms if required by the [City Engineer] (See Section 1.12 of the BMP Design Manual)	City of Santee
Who will be the final owner of this BMP?	City of Santee
Who will maintain this BMP into perpetuity?	City of Santee
What is the funding mechanism for maintenance?	City of Santee

Structural BMP Summary Information (Copy this page as needed to provide information for each individual proposed structural BMP)	
Structural BMP ID No. BF-2C	
Construction Plan Sheet No. C1.9	
<p>Type of structural BMP:</p> <p><input type="checkbox"/> Retention by harvest and use (HU-1)</p> <p><input type="checkbox"/> Retention by infiltration basin (INF-1)</p> <p><input type="checkbox"/> Retention by bioretention (INF-2)</p> <p><input type="checkbox"/> Retention by permeable pavement (INF-3)</p> <p><input type="checkbox"/> Partial retention by biofiltration with partial retention (PR-1)</p> <p><input checked="" type="checkbox"/> Biofiltration (BF-1)</p> <p><input type="checkbox"/> Biofiltration with Nutrient Sensitive Media Design (BF-2)</p> <p><input type="checkbox"/> Proprietary Biofiltration (BF-3) meeting all requirements of Appendix F</p> <p><input type="checkbox"/> Flow-thru treatment control with prior lawful approval to meet earlier PDP requirements (provide BMP type/description in discussion section below)</p> <p><input type="checkbox"/> Flow-thru treatment control included as pre-treatment/forebay for an onsite retention or biofiltration BMP (provide BMP type/description and indicate which onsite retention or biofiltration BMP it serves in discussion section below)</p> <p><input type="checkbox"/> Flow-thru treatment control with alternative compliance (provide BMP type/description in discussion section below)</p> <p><input type="checkbox"/> Detention pond or vault for hydromodification management</p> <p><input type="checkbox"/> Other (describe in discussion section below)</p>	
<p>Purpose:</p> <p><input type="checkbox"/> Pollutant control only</p> <p><input type="checkbox"/> Hydromodification control only</p> <p><input checked="" type="checkbox"/> Combined pollutant control and hydromodification control</p> <p><input type="checkbox"/> Pre-treatment/forebay for another structural BMP</p> <p><input type="checkbox"/> Other (describe in discussion section below)</p>	
Who will certify construction of this BMP? Provide name and contact information for the party responsible to sign BMP verification forms if required by the [City Engineer] (See Section 1.12 of the BMP Design Manual)	City of Santee
Who will be the final owner of this BMP?	City of Santee
Who will maintain this BMP into perpetuity?	City of Santee
What is the funding mechanism for maintenance?	City of Santee


ATTACHMENT 1

BACKUP FOR PDP POLLUTANT CONTROL BMPS


This is the cover sheet for Attachment 1.

Indicate which Items are Included behind this cover sheet:

Attachment Sequence	Contents	Checklist
Attachment 1a	DMA Exhibit (Required) See DMA Exhibit Checklist on the back of this Attachment cover sheet.	<input checked="" type="checkbox"/> Included
Attachment 1b	Tabular Summary of DMAs Showing DMA ID matching DMA Exhibit, DMA Area, and DMA Type (Required)* *Provide table in this Attachment OR on DMA Exhibit in Attachment 1a	<input checked="" type="checkbox"/> Included on DMA Exhibit in Attachment 1a <input type="checkbox"/> Included as Attachment 1b, separate from DMA Exhibit
Attachment 1c	Form I-7, Harvest and Use Feasibility Screening Checklist (Required unless the entire project will use infiltration BMPs) Refer to Appendix B.3-1 of the BMP Design Manual to complete Form I-7.	<input checked="" type="checkbox"/> Included <input type="checkbox"/> Not included because the entire project will use infiltration BMPs
Attachment 1d	Form I-8, Categorization of Infiltration Feasibility Condition (Required unless the project will use harvest and use BMPs) Refer to Appendices C and D of the BMP Design Manual to complete Form I-8.	<input checked="" type="checkbox"/> Included <input type="checkbox"/> Not included because the entire project will use harvest and use BMPs
Attachment 1e	Pollutant Control BMP Design Worksheets / Calculations (Required) Refer to Appendices B and E of the BMP Design Manual for structural pollutant control BMP design guidelines	<input checked="" type="checkbox"/> Included




- LEGEND**
- CURB RAMP
 - CONCRETE CROSS GUTTER/RIBBON GUTTER
 - SIDEWALK UNDERDRAIN
 - CATCH BASIN
 - CLEANOUT
 - SLOPE ARROW
 - NEW CONTOUR
 - EXISTING CONTOUR (PER AERIAL SURVEY, ACCURACY OF ± 0.5')
 - EXISTING ELEVATION (PER FIELD SURVEY, ACCURACY OF ± 0.1')
 - EXISTING SPOT ELEVATION (PER AERIAL SURVEY, ACCURACY OF ± 0.5')
 - NEW CONTOUR LINE
 - DAYLIGHT LINE
 - SAWCUT LINE
 - RIDGE LINE
 - CONCRETE CURB
 - CONCRETE CURB AND GUTTER
 - PUBLIC UTILITIES EASEMENT LINE
 - DRAINAGE FLOW ARROW
 - DRAINAGE AREA BOUNDARY
 - SUBCATCHMENT IDENTIFICATION
- A=AREA (ACRES)
Q=6-HOUR, 100-YEAR STORM EVENT (CFS)
TC=TIME OF CONCENTRATION (MIN)



SANTEE COMMUNITY CENTER



PRE-DEVELOPMENT DRAINAGE
CONDITION

FIGURE A1




- LEGEND**
- CURB RAMP
 - CONCRETE CROSS GUTTER/RIBBON GUTTER
 - SIDEWALK UNDERDRAIN
 - CATCH BASIN
 - CLEANOUT
 - SLOPE ARROW
 - 500- NEW CONTOUR
 - x 505.50 NEW SPOT ELEVATION
 - 500- EXISTING CONTOUR (PER AERIAL SURVEY, ACCURACY OF ± 0.5')
 - 000.00 EXISTING ELEVATION (PER FIELD SURVEY, ACCURACY OF ± 0.1')
 - x 500.0 EXISTING SPOT ELEVATION (PER AERIAL SURVEY, ACCURACY OF ± 0.5')
 - 740- NEW CONTOUR LINE
 - DAYLIGHT LINE
 - SAWCUT LINE
 - RIDGE LINE
 - CONCRETE CURB
 - CONCRETE CURB AND GUTTER
 - PUBLIC UTILITIES EASEMENT LINE
 - DRAINAGE AREA BOUNDARY
 - SUBCATCHMENT IDENTIFICATION
- 1B
- A=AREA (ACRES)
Q=6-HOUR, 100-YEAR STORM EVENT (CFS)
TC=TIME OF CONCENTRATION (MIN)

- GENERAL NOTES:**
- HYDRAULIC SOIL GROUP = C
 - APPROXIMATE DEPTH TO GROUND WATER = 14.5 - 16.1 FT BELOW EXISTING SURFACE
 - NO EXISTING NATURAL HYDROLOGIC FEATURES EXIST WITHIN THE PROJECT LIMITS.
 - THERE ARE NO POTENTIAL CRITICAL COURSE SEDIMENT YIELD AREAS LOCATED WITHIN OR DIRECTLY ADJACENT TO THE PROJECT LIMITS.
 - THE CITY OF SANTEE, AS THE PROJECT OWNER, IS RESPONSIBLE FOR THE MAINTENANCE OF PROPOSED BMPs, INCLUDING BIOFILTRATION BASINS AND TRASH CAPTURE DEVICES.



- BIOFILTRATION PROTECTION DURING CONSTRUCTION:**
- PREVENT OVER-COMPACTING OF NATIVE SOILS IN AREAS OF THE BASIN WHERE INFILTRATION WILL OCCUR. DELINEATE THE BIOFILTRATION AREA AND KEEP CONSTRUCTION TRAFFIC OFF. PROTECT SOILS WITH FENCING, PLYWOOD, ETC.
 - PROVIDE EROSION CONTROL IN THE CONTRIBUTING DRAINAGE AREAS OF THE DESIGNATED BIOFILTRATION AREA. STABILIZE UPSLOPE AREAS.
 - DRAINAGE SHOULD BE DIRECTED AWAY FROM BIORETENTION FACILITIES UNTIL UPSLOPE AREAS ARE STABILIZED. THE CONCENTRATION OF FINES COULD PREVENT POST-CONSTRUCTION INFILTRATION AND CAUSE DESIGN FAILURE.
 - IF DRAINAGE IS TO BE ALLOWED THROUGH THE FACILITY DURING CONSTRUCTION LEAVE OR BACKFILL AT LEAST 6 INCHES ABOVE THE FINAL GRADE. TEMPORARILY COVER THE UNDERDRAIN WITH PLASTIC OR FABRIC. LINE OR MULCH THE BIOFILTRATION AREA.
 - BIORETENTION FACILITIES SHOULD REMAIN OUTSIDE THE LIMIT OF DISTURBANCE TO PREVENT SOIL COMPACTION BY HEAVY EQUIPMENT. PROTECT BIORETENTION AREAS WITH SILT FENCE AND CONSTRUCTION FENCING.
 - VERIFY INSTALLATION OF UNDERDRAIN IS CORRECT PRIOR TO PLACING SOIL.

FOR REFERENCE ONLY
BIOFILTRATION BASIN DETAIL
N.T.S.




SPECIFIER CHART

MODEL NO.	STANDARD DEPTH (12" MIN)	SHALLOW DEPTH (12" MIN)	STANDARD DEPTH (12" MIN)	SHALLOW DEPTH (12" MIN)
STANDARD DEPTH (12" MIN)	SHALLOW DEPTH (12" MIN)	STANDARD DEPTH (12" MIN)	SHALLOW DEPTH (12" MIN)	STANDARD DEPTH (12" MIN)
FGP-10F	10" X 10"	10" X 10"	10" X 10"	10" X 10"
FGP-15F	15" X 15"	15" X 15"	15" X 15"	15" X 15"
FGP-20F	20" X 20"	20" X 20"	20" X 20"	20" X 20"
FGP-25F	25" X 25"	25" X 25"	25" X 25"	25" X 25"
FGP-30F	30" X 30"	30" X 30"	30" X 30"	30" X 30"
FGP-36F	36" X 36"	36" X 36"	36" X 36"	36" X 36"
FGP-42F	42" X 42"	42" X 42"	42" X 42"	42" X 42"
FGP-48F	48" X 48"	48" X 48"	48" X 48"	48" X 48"
FGP-54F	54" X 54"	54" X 54"	54" X 54"	54" X 54"
FGP-60F	60" X 60"	60" X 60"	60" X 60"	60" X 60"

DMA DATA TABLE

DMA TITLE	TRIBUTARY SIZE (AC)	DRAINS TO
1A	2.00	EXISTING POINT OF DISCHARGE (NO IMPROVEMENTS PROPOSED)
1B	0.61	BF-1B
1C	0.17	BF-1C
1D	0.38	BF-1D
1E	0.46	BF-1E
1F	0.16	BF-1F
2A	0.40	BF-2A
2B	0.28	BF-2B
2C	0.71	BF-2C



SANTEE COMMUNITY CENTER






POST-DEVELOPMENT DRAINAGE
CONDITION

FIGURE A2

PSOMAS
401 B Street, Suite 1600
San Diego, CA 92101
(619) 961-2800 (619) 961-2392 fax
www.psomas.com

Attachment 1c

Worksheet 0-2. Harvest and Use Feasibility Screening

Harvest and Use Feasibility Screening		Worksheet B.3-1
<p>1. Is there a demand for harvested water (check all that apply) at the project site that is reliably present during the wet season? Waiting on flush volume from plumbing.</p> <p><input checked="" type="checkbox"/> Toilet and urinal flushing</p> <p><input type="checkbox"/> Landscape irrigation Due to the use of reclaimed water for the entirety of landscape irrigation, there is no irrigation demand for Harvest and Use (per City of Santee BMP Manual, Section B.3.2.2, bullet 1)</p> <p><input type="checkbox"/> Other: _____</p>		
<p>2. If there is a demand; estimate the anticipated average wet season demand over a period of 36 hours. Guidance for planning level demand calculations for toilet/urinal flushing and landscape irrigation is provided in Section B.3.2.</p> <p>Daily Occupancy - 190 Total daily toilet/urinal use (based on office/retail space (7 per occupant)) - 1330 uses per day - 1995 uses in 36 hours Average 0.7 gal/flush = 1397 gallons used in 36 hours</p>		
<p>3. Calculate the DCV using worksheet B-2.1.</p> <p>DCV = 4514 cu-ft = 33,767 gallons</p>		
<p>3a. Is the 36-hour demand greater than or equal to the DCV?</p> <p>Yes / No </p> <p></p>	<p>3b. Is the 36-hour demand greater than 0.25DCV but less than the full DCV?</p> <p>Yes / No </p> <p></p>	<p>3c. Is the 36-hour demand less than 0.25DCV?</p> <p></p>
<p>Harvest and use appears to be feasible. Conduct more detailed evaluation and sizing calculations to confirm that DCV can be used at an adequate rate to meet drawdown criteria.</p>	<p>Harvest and use may be feasible. Conduct more detailed evaluation and sizing calculations to determine feasibility. Harvest and use may only be able to be used for a portion of the site, or (optionally) the storage may need to be upsized to meet long term capture targets while draining in longer than 36 hours.</p>	<p>Harvest and use is considered to be infeasible.</p>

Worksheet 0-1: Categorization of Infiltration Feasibility Condition

Categorization of Infiltration Feasibility Condition		Worksheet C.4-1	
Part 1 - Full Infiltration Feasibility Screening Criteria Would infiltration of the full design volume be feasible from a physical perspective without any undesirable consequences that cannot be reasonably mitigated?			
Criteria	Screening Question	Yes	No
1	Is the estimated reliable infiltration rate below proposed facility locations greater than 0.5 inches per hour? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.2 and Appendix D.		<input checked="" type="checkbox"/>
Provide basis: Per the project specific Geotechnical Report, the infiltration rate is less than 0.001 inches per hour.			
Summarize findings of studies; provide reference to studies, calculations, maps, data sources, etc. Provide narrative discussion of study/data source applicability.			
2	Can infiltration greater than 0.5 inches per hour be allowed without increasing risk of geotechnical hazards (slope stability, groundwater mounding, utilities, or other factors) that cannot be mitigated to an acceptable level? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.2.		<input checked="" type="checkbox"/>
Provide basis: Per the project specific Geotechnical Report, the infiltration rate is less than 0.001 inches per hour.			
Summarize findings of studies; provide reference to studies, calculations, maps, data sources, etc. Provide narrative discussion of study/data source applicability.			

Worksheet C.4-1 Page 2 of 4			
Criteria	Screening Question	Yes	No
3	Can infiltration greater than 0.5 inches per hour be allowed without increasing risk of groundwater contamination (shallow water table, storm water pollutants or other factors) that cannot be mitigated to an acceptable level? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.3.		<input checked="" type="checkbox"/>
<p>Provide basis: Per the project specific Geotechnical Report, the infiltration rate is less than 0.001 inches per hour.</p> <p>Summarize findings of studies; provide reference to studies, calculations, maps, data sources, etc. Provide narrative discussion of study/data source applicability.</p>			
4	Can infiltration greater than 0.5 inches per hour be allowed without causing potential water balance issues such as change of seasonality of ephemeral streams or increased discharge of contaminated groundwater to surface waters? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.3.		<input checked="" type="checkbox"/>
<p>Provide basis: Per the project specific Geotechnical Report, the infiltration rate is less than 0.001 inches per hour.</p> <p>Summarize findings of studies; provide reference to studies, calculations, maps, data sources, etc. Provide narrative discussion of study/data source applicability.</p>			
Part 1 Result*	<p>If all answers to rows 1 - 4 are “Yes” a full infiltration design is potentially feasible. The feasibility screening category is Full Infiltration</p> <p>If any answer from row 1-4 is “No”, infiltration may be possible to some extent but would not generally be feasible or desirable to achieve a “full infiltration” design. Proceed to Part 2</p>		

*To be completed using gathered site information and best professional judgment considering the definition of MEP in the MS4 Permit. Additional testing and/or studies may be required by City Engineer to substantiate findings.

Worksheet C.4-1 Page 3 of 4

Part 2 – Partial Infiltration vs. No Infiltration Feasibility Screening Criteria

Would infiltration of water in any appreciable amount be physically feasible without any negative consequences that cannot be reasonably mitigated?

Criteria	Screening Question	Yes	No
5	Do soil and geologic conditions allow for infiltration in any appreciable rate or volume? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.2 and Appendix D.		<input checked="" type="checkbox"/>

Provide basis:

Per the project specific Geotechnical Report, the infiltration rate is less than 0.001 inches per hour.

Summarize findings of studies; provide reference to studies, calculations, maps, data sources, etc. Provide narrative discussion of study/data source applicability and why it was not feasible to mitigate low infiltration rates.

6	Can Infiltration in any appreciable quantity be allowed without increasing risk of geotechnical hazards (slope stability, groundwater mounding, utilities, or other factors) that cannot be mitigated to an acceptable level? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.2.		<input checked="" type="checkbox"/>
---	---	--	-------------------------------------

Provide basis:

Per the project specific Geotechnical Report, the infiltration rate is less than 0.001 inches per hour.

Summarize findings of studies; provide reference to studies, calculations, maps, data sources, etc. Provide narrative discussion of study/data source applicability and why it was not feasible to mitigate low infiltration rates.

Worksheet C.4-1 Page 4 of 4			
Criteria	Screening Question	Yes	No
7	<p>Can Infiltration in any appreciable quantity be allowed without posing significant risk for groundwater related concerns (shallow water table, storm water pollutants or other factors)?</p> <p>The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.3.</p>		<input checked="" type="checkbox"/>
<p>Provide basis:</p> <p>Per the project specific Geotechnical Report, the infiltration rate is less than 0.001 inches per hour.</p> <p>Summarize findings of studies; provide reference to studies, calculations, maps, data sources, etc. Provide narrative discussion of study/data source applicability and why it was not feasible to mitigate low infiltration rates.</p>			
8	<p>Can infiltration be allowed without violating downstream water rights? The response to this Screening Question shall be based on a comprehensive evaluation of the factors presented in Appendix C.3.</p>		<input checked="" type="checkbox"/>
<p>Provide basis:</p> <p>Per the project specific Geotechnical Report, the infiltration rate is less than 0.001 inches per hour.</p> <p>Summarize findings of studies; provide reference to studies, calculations, maps, data sources, etc. Provide narrative discussion of study/data source applicability and why it was not feasible to mitigate low infiltration rates.</p>			
Part 2 Result*	<p>If all answers from row 1-4 are yes then partial infiltration design is potentially feasible. The feasibility screening category is Partial Infiltration.</p> <p>If any answer from row 5-8 is no, then infiltration of any volume is considered to be infeasible within the drainage area. The feasibility screening category is No Infiltration.</p>		No Infiltration

*To be completed using gathered site information and best professional judgment considering the definition of MEP in the Permit. Additional testing and/or studies may be required by Agency/Jurisdictions to substantiate findings

Attachment 1e

Automated Worksheet B.1: Calculation of Design Capture Volume (V2.0)

Category	#	Description	<i>i</i>	<i>ii</i>	<i>iii</i>	<i>iv</i>	<i>v</i>	<i>vi</i>	<i>vii</i>	<i>viii</i>	<i>ix</i>	<i>x</i>	Units
Standard Drainage Basin Inputs	1	Drainage Basin ID or Name	DMA 1B	DMA 1C	DMA 1D	DMA 2A	DMA 2B	DMA 2C					unitless
	2	85th Percentile 24-hr Storm Depth	0.50	0.50	0.50	0.50	0.50	0.50					inches
	3	Impervious Surfaces <u>Not Directed to Dispersion Area</u> (C=0.90)	33,565	4,810	22,685	13,250	9,276	24,188					sq-ft
	4	Semi-Pervious Surfaces <u>Not Serving as Dispersion Area</u> (C=0.30)											sq-ft
	5	Engineered Pervious Surfaces <u>Not Serving as Dispersion Area</u> (C=0.10)											sq-ft
	6	Natural Type A Soil <u>Not Serving as Dispersion Area</u> (C=0.10)											sq-ft
	7	Natural Type B Soil <u>Not Serving as Dispersion Area</u> (C=0.14)											sq-ft
	8	Natural Type C Soil <u>Not Serving as Dispersion Area</u> (C=0.23)											sq-ft
	9	Natural Type D Soil <u>Not Serving as Dispersion Area</u> (C=0.30)	8,385	2,640	10,790	4,185	2,930	7,639					sq-ft
Dispersion Area, Tree Well & Rain Barrel Inputs (Optional)	10	Does Tributary Incorporate Dispersion, Tree Wells, and/or Rain Barrels?	No	No	No	No	No	No	No	No	No	No	yes/no
	11	Impervious Surfaces Directed to Dispersion Area per SD-B (Ci=0.90)											sq-ft
	12	Semi-Pervious Surfaces Serving as Dispersion Area per SD-B (Ci=0.30)											sq-ft
	13	Engineered Pervious Surfaces Serving as Dispersion Area per SD-B (Ci=0.10)											sq-ft
	14	Natural Type A Soil Serving as Dispersion Area per SD-B (Ci=0.10)											sq-ft
	15	Natural Type B Soil Serving as Dispersion Area per SD-B (Ci=0.14)											sq-ft
	16	Natural Type C Soil Serving as Dispersion Area per SD-B (Ci=0.23)											sq-ft
	17	Natural Type D Soil Serving as Dispersion Area per SD-B (Ci=0.30)											sq-ft
	18	Number of Tree Wells Proposed per SD-A											#
	19	Average Mature Tree Canopy Diameter											ft
	20	Number of Rain Barrels Proposed per SD-E											#
21	Average Rain Barrel Size											gal	
Initial Runoff Factor Calculation	22	Total Tributary Area	41,950	7,450	33,475	17,435	12,206	31,827	0	0	0	0	sq-ft
	23	Initial Runoff Factor for Standard Drainage Areas	0.78	0.69	0.71	0.76	0.76	0.76	0.00	0.00	0.00	0.00	unitless
	24	Initial Runoff Factor for Dispersed & Dispersion Areas	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	unitless
	25	Initial Weighted Runoff Factor	0.78	0.69	0.71	0.76	0.76	0.76	0.00	0.00	0.00	0.00	unitless
	26	Initial Design Capture Volume	1,363	214	990	552	387	1,008	0	0	0	0	cubic-feet
Dispersion Area Adjustments	27	Total Impervious Area Dispersed to Pervious Surface	0	0	0	0	0	0	0	0	0	0	sq-ft
	28	Total Pervious Dispersion Area	0	0	0	0	0	0	0	0	0	0	sq-ft
	29	Ratio of Dispersed Impervious Area to Pervious Dispersion Area	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	ratio
	30	Adjustment Factor for Dispersed & Dispersion Areas	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	1.00	ratio
	31	Runoff Factor After Dispersion Techniques	0.78	0.69	0.71	0.76	0.76	0.76	n/a	n/a	n/a	n/a	unitless
	32	Design Capture Volume After Dispersion Techniques	1,363	214	990	552	387	1,008	0	0	0	0	cubic-feet
Tree & Barrel Adjustments	33	Total Tree Well Volume Reduction	0	0	0	0	0	0	0	0	0	0	cubic-feet
	34	Total Rain Barrel Volume Reduction	0	0	0	0	0	0	0	0	0	0	cubic-feet
Results	35	Final Adjusted Runoff Factor	0.78	0.69	0.71	0.76	0.76	0.76	0.00	0.00	0.00	0.00	unitless
	36	Final Effective Tributary Area	32,721	5,141	23,767	13,251	9,277	24,189	0	0	0	0	sq-ft
	37	Initial Design Capture Volume Retained by Site Design Elements	0	0	0	0	0	0	0	0	0	0	cubic-feet
	38	Final Design Capture Volume Tributary to BMP	1,363	214	990	552	387	1,008	0	0	0	0	cubic-feet
No Warning Messages													

Automated Worksheet B.2: Retention Requirements (V2.0)

Category	#	Description	<i>i</i>	<i>ii</i>	<i>iii</i>	<i>iv</i>	<i>v</i>	<i>vi</i>	<i>vii</i>	<i>viii</i>	<i>ix</i>	<i>x</i>	Units
Basic Analysis	1	Drainage Basin ID or Name	DMA 1B	DMA 1C	DMA 1D	DMA 2A	DMA 2B	DMA 2C	-	-	-	-	unitless
	2	85th Percentile Rainfall Depth	0.50	0.50	0.50	0.50	0.50	0.50	-	-	-	-	inches
	3	Predominant NRCS Soil Type Within BMP Location	D	D	D	D	D	D					unitless
	4	Is proposed BMP location Restricted or Unrestricted for Infiltration Activities?	Restricted	Restricted	Restricted	Restricted	Restricted	Restricted					unitless
	5	Nature of Restriction	Groundwater	Groundwater	Groundwater	Groundwater	Groundwater	Groundwater					unitless
	6	Do Minimum Retention Requirements Apply to this Project?	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	yes/no
	7	Are Habitable Structures Greater than 9 Stories Proposed?	No	No	No	No	No	No					yes/no
Advanced Analysis	8	Has Geotechnical Engineer Performed an Infiltration Analysis?	Yes	Yes	Yes	Yes	Yes	Yes					yes/no
	9	Design Infiltration Rate Recommended by Geotechnical Engineer	0.001	0.001	0.001	0.001	0.001	0.001					in/hr
Result	10	Design Infiltration Rate Used To Determine Retention Requirements	0.000	0.000	0.000	0.000	0.000	0.000	-	-	-	-	in/hr
	11	Percent of Average Annual Runoff that Must be Retained within DMA	4.5%	4.5%	4.5%	4.5%	4.5%	4.5%	-	-	-	-	percentage
	12	Fraction of DCV Requiring Retention	0.02	0.02	0.02	0.02	0.02	0.02	-	-	-	-	ratio
	13	Required Retention Volume	27	4	20	11	8	20	-	-	-	-	cubic-feet

No Warning Messages

Automated Worksheet B.3: BMP Performance (V2.0)

Category	#	Description	<i>i</i>	<i>ii</i>	<i>iii</i>	<i>iv</i>	<i>v</i>	<i>vi</i>	<i>vii</i>	<i>viii</i>	<i>ix</i>	<i>x</i>	Units
BMP Inputs	1	Drainage Basin ID or Name	DMA 1B	DMA 1C	DMA 1D	DMA 2A	DMA 2B	DMA 2C	-	-	-	-	sq-ft
	2	Design Infiltration Rate Recommended	0.000	0.000	0.000	0.000	0.000	0.000	-	-	-	-	in/hr
	3	Design Capture Volume Tributary to BMP	1,363	214	990	552	387	1,008	-	-	-	-	cubic-feet
	4	Is BMP Vegetated or Unvegetated?	Vegetated	Vegetated	Vegetated	Vegetated	Vegetated	Vegetated					unitless
	5	Is BMP Impermeably Lined or Unlined?	Lined	Lined	Lined	Lined	Lined	Lined					unitless
	6	Does BMP Have an Underdrain?	Underdrain	Underdrain	Underdrain	Underdrain	Underdrain	Underdrain					unitless
	7	Does BMP Utilize Standard or Specialized Media?	Standard	Standard	Standard	Standard	Standard	Standard					unitless
	8	Provided Surface Area	860	930	2,795	685	460	3,150					sq-ft
	9	Provided Surface Ponding Depth	12	12	12	6	6	6					inches
	10	Provided Soil Media Thickness	27	27	27	27	27	27					inches
	11	Provided Gravel Thickness (Total Thickness)	27	27	27	27	27	27					inches
	12	Underdrain Offset	3	3	3	3	3	3					inches
	13	Diameter of Underdrain or Hydromod Orifice (Select Smallest)	0.90	0.90	0.90	0.90	0.90	0.90					inches
	14	Specialized Soil Media Filtration Rate											in/hr
	15	Specialized Soil Media Pore Space for Retention											unitless
	16	Specialized Soil Media Pore Space for Biofiltration											unitless
	17	Specialized Gravel Media Pore Space											unitless
Retention Calculations	18	Volume Infiltrated Over 6 Hour Storm	0	0	0	0	0	0	0	0	0	0	cubic-feet
	19	Ponding Pore Space Available for Retention	0.00	0.00	0.00	0.00	0.00	0.00	1.00	1.00	1.00	1.00	unitless
	20	Soil Media Pore Space Available for Retention	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05	unitless
	21	Gravel Pore Space Available for Retention (Above Underdrain)	0.00	0.00	0.00	0.00	0.00	0.00	0.40	0.40	0.40	0.40	unitless
	22	Gravel Pore Space Available for Retention (Below Underdrain)	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	unitless
	23	Effective Retention Depth	2.55	2.55	2.55	2.55	2.55	2.55	0.00	0.00	0.00	0.00	inches
	24	Fraction of DCV Retained (Independent of Drawdown Time)	0.13	0.92	0.60	0.26	0.25	0.66	0.00	0.00	0.00	0.00	ratio
	25	Calculated Retention Storage Drawdown Time	120	120	120	120	120	120	0	0	0	0	hours
	26	Efficacy of Retention Processes	0.15	0.71	0.53	0.27	0.26	0.57	0.00	0.00	0.00	0.00	ratio
	27	Volume Retained by BMP (Considering Drawdown Time)	206	152	529	150	102	574	0	0	0	0	cubic-feet
	28	Design Capture Volume Remaining for Biofiltration	1,157	62	461	402	285	434	0	0	0	0	cubic-feet
Biofiltration Calculations	29	Max Hydromod Flow Rate through Underdrain	0.0486	0.0486	0.0486	0.0462	0.0462	0.0462	0.0000	0.0000	0.0000	0.0000	cfs
	30	Max Soil Filtration Rate Allowed by Underdrain Orifice	2.44	2.26	0.75	2.91	4.34	0.63	0.00	0.00	0.00	0.00	in/hr
	31	Soil Media Filtration Rate per Specifications	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	5.00	in/hr
	32	Soil Media Filtration Rate to be used for Sizing	2.44	2.26	0.75	2.91	4.34	0.63	0.00	0.00	0.00	0.00	in/hr
	33	Depth Biofiltered Over 6 Hour Storm	14.64	13.54	4.50	17.47	26.02	3.80	0.00	0.00	0.00	0.00	inches
	34	Ponding Pore Space Available for Biofiltration	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.00	0.00	unitless
	35	Soil Media Pore Space Available for Biofiltration	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	unitless
	36	Gravel Pore Space Available for Biofiltration (Above Underdrain)	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	0.40	unitless
	37	Effective Depth of Biofiltration Storage	27.00	27.00	27.00	21.00	21.00	21.00	0.00	0.00	0.00	0.00	inches
	38	Drawdown Time for Surface Ponding	5	5	16	2	1	9	0	0	0	0	hours
	39	Drawdown Time for Effective Biofiltration Depth	11	12	36	7	5	33	0	0	0	0	hours
	40	Total Depth Biofiltered	41.64	40.54	31.50	38.47	47.02	24.80	0.00	0.00	0.00	0.00	inches
	41	Option 1 - Biofilter 1.50 DCV: Target Volume	1,736	93	692	602	427	651	0	0	0	0	cubic-feet
	42	Option 1 - Provided Biofiltration Volume	1,736	93	692	602	427	651	0	0	0	0	cubic-feet
	43	Option 2 - Store 0.75 DCV: Target Volume	868	46	346	301	214	325	0	0	0	0	cubic-feet
	44	Option 2 - Provided Storage Volume	868	46	346	301	214	325	0	0	0	0	cubic-feet
	45	Portion of Biofiltration Performance Standard Satisfied	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.00	0.00	ratio
Result	46	Do Site Design Elements and BMPs Satisfy Annual Retention Requirements?	Yes	Yes	Yes	Yes	Yes	Yes	-	-	-	-	yes/no
	47	Overall Portion of Performance Standard Satisfied (BMP Efficacy Factor)	1.00	1.00	1.00	1.00	1.00	1.00	0.00	0.00	0.00	0.00	ratio
	48	Deficit of Effectively Treated Stormwater	0	0	0	0	0	0	n/a	n/a	n/a	n/a	cubic-feet

Attention!
- BMPs sized at <3% of the effective tributary areas must be accompanied by Reduced Size BMP Maintenance calculations (see last tab)

ATTACHMENT 2


BACKUP FOR PDP HYDROMODIFICATION CONTROL MEASURES

This is the cover sheet for Attachment 2.

- ☐ Mark this box if this attachment is empty because the project is exempt from PDP hydromodification management requirements.



Indicate which Items are Included behind this cover sheet:

Attachment Sequence	Contents	Checklist
Attachment 2a	Hydromodification Management Exhibit (Required)	<input checked="" type="checkbox"/> Included See Hydromodification Management Exhibit Checklist on the back of this Attachment cover sheet.
Attachment 2b	Management of Critical Coarse Sediment Yield Areas (WMAA Exhibit is required, additional analyses are optional) See Section 6.2 of the BMP Design Manual.	<input checked="" type="checkbox"/> Exhibit showing project drainage boundaries marked on WMAA Critical Coarse Sediment Yield Area Map (Required) Optional analyses for Critical Coarse Sediment Yield Area Determination <input type="checkbox"/> 6.2.1 Verification of Geomorphic Landscape Units Onsite <input type="checkbox"/> 6.2.2 Downstream Systems Sensitivity to Coarse Sediment <input type="checkbox"/> 6.2.3 Optional Additional Analysis of Potential Critical Coarse Sediment Yield Areas Onsite
Attachment 2c	Geomorphic Assessment of Receiving Channels (Optional) See Section 6.3.4 of the BMP Design Manual.	<input checked="" type="checkbox"/> Not performed <input type="checkbox"/> Included <input type="checkbox"/> Submitted as separate stand-alone document
Attachment 2d	Flow Control Facility Design, including Structural BMP Drawdown Calculations and Overflow Design Summary (Required) See Chapter 6 and Appendix G of the BMP Design Manual	<input checked="" type="checkbox"/> Included <input type="checkbox"/> Submitted as separate stand-alone document
Attachment 2e	Vector Control Plan (Required when structural BMPs will not drain in 96 hours)	<input type="checkbox"/> Included <input checked="" type="checkbox"/> Not required because BMPs will drain in less than 96 hours





- LEGEND**
- CURB RAMP
 - CONCRETE CROSS GUTTER/RIBBON GUTTER
 - SIDEWALK UNDERDRAIN
 - CATCH BASIN
 - CLEANOUT
 - SLOPE ARROW
 - NEW CONTOUR
 - NEW SPOT ELEVATION
 - EXISTING CONTOUR (PER AERIAL SURVEY, ACCURACY OF ± 0.5')
 - EXISTING ELEVATION (PER FIELD SURVEY, ACCURACY OF ± 0.1')
 - EXISTING SPOT ELEVATION (PER AERIAL SURVEY, ACCURACY OF ± 0.5')
 - NEW CONTOUR LINE
 - DAYLIGHT LINE
 - SAWCUT LINE
 - RIDGE LINE
 - CONCRETE CURB
 - CONCRETE CURB AND GUTTER
 - PUBLIC UTILITIES EASEMENT LINE
 - DRAINAGE AREA BOUNDARY
 - SUBCATCHMENT IDENTIFICATION
- 1B
- A=AREA (ACRES)
Q=6-HOUR, 100-YEAR STORM EVENT (CFS)
TC=TIME OF CONCENTRATION (MIN)

- GENERAL NOTES:**
- HYDRAULIC SOIL GROUP = C
 - APPROXIMATE DEPTH TO GROUND WATER = 14.5 - 16.1 FT BELOW EXISTING SURFACE
 - NO EXISTING NATURAL HYDROLOGIC FEATURES EXIST WITHIN THE PROJECT LIMITS.
 - THERE ARE NO POTENTIAL CRITICAL COURSE SEDIMENT YIELD AREAS LOCATED WITHIN OR DIRECTLY ADJACENT TO THE PROJECT LIMITS.
 - THE CITY OF SANTEE, AS THE PROJECT OWNER, IS RESPONSIBLE FOR THE MAINTENANCE OF PROPOSED BMPS, INCLUDING BIOFILTRATION BASINS AND TRASH CAPTURE DEVICES.




- BIOFILTRATION PROTECTION DURING CONSTRUCTION:**
- PREVENT OVER-COMPACTING OF NATIVE SOILS IN AREAS OF THE BASIN WHERE INFILTRATION WILL OCCUR. DELINEATE THE BIOFILTRATION AREA AND KEEP CONSTRUCTION TRAFFIC OFF. PROTECT SOILS WITH FENCING, PLYWOOD, ETC.
 - PROVIDE EROSION CONTROL IN THE CONTRIBUTING DRAINAGE AREAS OF THE DESIGNATED BIOFILTRATION AREA. STABILIZE UPSLOPE AREAS.
 - DRAINAGE SHOULD BE DIRECTED AWAY FROM BIORETENTION FACILITIES UNTIL UPSLOPE AREAS ARE STABILIZED. THE CONCENTRATION OF FINES COULD PREVENT POST-CONSTRUCTION INFILTRATION AND CAUSE DESIGN FAILURE.
 - IF DRAINAGE IS TO BE ALLOWED THROUGH THE FACILITY DURING CONSTRUCTION LEAVE OR BACKFILL AT LEAST 6 INCHES ABOVE THE FINAL GRADE. TEMPORARILY COVER THE UNDERDRAIN WITH PLASTIC OR FABRIC. LINE OR MULCH THE BIOFILTRATION AREA.
 - BIORETENTION FACILITIES SHOULD REMAIN OUTSIDE THE LIMIT OF DISTURBANCE TO PREVENT SOIL COMPACTION BY HEAVY EQUIPMENT. PROTECT BIORETENTION AREAS WITH SILT FENCE AND CONSTRUCTION FENCING.
 - VERIFY INSTALLATION OF UNDERDRAIN IS CORRECT PRIOR TO PLACING SOIL.

FOR REFERENCE ONLY
BIOFILTRATION BASIN DETAIL
N.T.S.



DMA DATA TABLE		
DMA TITLE	TRIBUTARY SIZE (AC)	DRAINS TO
1A	2.00	EXISTING POINT OF DISCHARGE (NO IMPROVEMENTS PROPOSED)
1B	0.61	BF-1B
1C	0.17	BF-1C
1D	0.38	BF-1D
1E	0.46	BF-1E
1F	0.16	BF-1F
2A	0.40	BF-2A
2B	0.28	BF-2B
2C	0.71	BF-2C



SANTEE COMMUNITY CENTER


POST-DEVELOPMENT DRAINAGE
CONDITION

FIGURE A2

PSOMAS
401 B Street, Suite 1600
San Diego, CA 92101
(619) 961-2800 (619) 961-2392 fax
www.psomas.com

Attachment 2a

FOR REFERENCE ONLY
FLOGARD CATCH BASIN INSERT FILTER
N.T.S.



REACH ID	NAME
1	Santa Margarita River
2	San Luis Rey River
3	Buena Vista Creek
4	Agua Hedionda Creek
5	San Marcos Creek
6	Encinitas Creek
7	Cottonwood Creek (Carlsbad WMA)
8	Escondido Creek
9	San Dieguito Creek - Reach 1
10	San Dieguito Creek - Reach 2
11	Lusardi Creek
12	Los Penasquitos / Poway Creek
13	Rattlesnake Creek
14	Carroll Canyon Creek
15	Rose Creek
16	San Diego River
17	Sycamore Creek
18	Woodglen Vista Creek
19	San Vicente Creek
20	Forester Creek
21	Chollas Creek
22	Sweetwater River - Reach 1
23	Sweetwater River - Reach 2
24	Otay River
25	Jamul / Dulzura Creek
26	Tijuana River
27	Cottonwood Creek (Tijuana WMA)

Potential Critical Coarse Sediment Yield Areas

Regional San Diego County Watersheds

Exhibit Date: Sept. 8, 2014

Attachment 2d

SDHM 3.1
PROJECT REPORT

General Model Information

Project Name: 2025_SCC
Site Name: SCC
Site Address:
City:
Report Date: 2/24/2025
Gage: SANTEE
Data Start: 10/01/1973
Data End: 09/30/2004
Timestep: Hourly
Precip Scale: 1.000
Version Date: 2021/06/28

POC Thresholds

Low Flow Threshold for POC1:	10 Percent of the 2 Year
High Flow Threshold for POC1:	10 Year

Low Flow Threshold for POC2:	10 Percent of the 2 Year
High Flow Threshold for POC2:	10 Year

Landuse Basin Data

Predeveloped Land Use

Pre Basin 1

Bypass: No

GroundWater: No

Pervious Land Use acre
C,NatVeg,Flat 1.79

Pervious Total 1.79

Impervious Land Use acre

Impervious Total 0

Basin Total 1.79

Element Flows To:
Surface Interflow Groundwater

DRAFT

Pre Basin 2

Bypass:	No
GroundWater:	No
Pervious Land Use C,NatVeg,Flat	acre 1.39
Pervious Total	1.39
Impervious Land Use	acre
Impervious Total	0
Basin Total	1.39

Element Flows To:	Interflow	Groundwater
Surface		

DRAFT

Mitigated Land Use

Prop Basin 2

Bypass:	No
GroundWater:	No
Pervious Land Use C,NatVeg,Flat	acre 0.34
Pervious Total	0.34
Impervious Land Use IMPERVIOUS-FLAT	acre 1.05
Impervious Total	1.05
Basin Total	1.39

Element Flows To:		
Surface	Interflow	Groundwater
Surface rtial Ret 2	Surface rtial Ret 2	

DRAFT

Prop Basin 1

Bypass:	No
GroundWater:	No
Pervious Land Use C,NatVeg,Flat	acre 0.33
Pervious Total	0.33
Impervious Land Use IMPERVIOUS-FLAT	acre 1.46
Impervious Total	1.46
Basin Total	1.79

Element Flows To:

Surface	Interflow	Groundwater
Surface rtial Ret 1	Surface rtial Ret 1	

DRAFT

DRAFT

Mitigated Routing

Bio Partial Ret 2

Bottom Length: 161.93 ft.
 Bottom Width: 161.93 ft.
 Material thickness of first layer: 0.25
 Material type for first layer: Mulch
 Material thickness of second layer: 1.5
 Material type for second layer: ESM
 Material thickness of third layer: 1.5
 Material type for third layer: GRAVEL
 Underdrain used
 Underdrain Diameter (feet): 0.5
 Orifice Diameter (in.): 0.749612500000001
 Offset (in.): 3
 Flow Through Underdrain (ac-ft.): 21.954
 Total Outflow (ac-ft.): 24.896
 Percent Through Underdrain: 88.18
 Discharge Structure
 Riser Height: 0.5 ft.
 Riser Diameter: 12 in.
 Element Flows To:
 Outlet 1 Outlet 2

Biofilter Hydraulic Table

Stage(feet)	Area(ac.)	Volume(ac-ft.)	Discharge(cfs)	Infilt(cfs)
0.0000	0.6019	0.0000	0.0000	0.0000
0.0467	0.6019	0.0084	0.0000	0.0000
0.0934	0.6019	0.0169	0.0000	0.0000
0.1401	0.6019	0.0253	0.0000	0.0000
0.1868	0.6019	0.0337	0.0000	0.0000
0.2335	0.6019	0.0422	0.0000	0.0000
0.2802	0.6019	0.0506	0.0000	0.0000
0.3269	0.6019	0.0590	0.0000	0.0000
0.3736	0.6019	0.0675	0.0000	0.0000
0.4203	0.6019	0.0759	0.0000	0.0000
0.4670	0.6019	0.0843	0.0000	0.0000
0.5137	0.6019	0.0928	0.0000	0.0000
0.5604	0.6019	0.1012	0.0000	0.0000
0.6071	0.6019	0.1096	0.0000	0.0000
0.6538	0.6019	0.1181	0.0000	0.0000
0.7005	0.6019	0.1265	0.0000	0.0000
0.7473	0.6019	0.1349	0.0000	0.0000
0.7940	0.6019	0.1434	0.0000	0.0000
0.8407	0.6019	0.1518	0.0000	0.0000
0.8874	0.6019	0.1602	0.0000	0.0000
0.9341	0.6019	0.1687	0.0000	0.0000
0.9808	0.6019	0.1771	0.0000	0.0000
1.0275	0.6019	0.1855	0.0000	0.0000
1.0742	0.6019	0.1940	0.0000	0.0000
1.1209	0.6019	0.2024	0.0000	0.0000
1.1676	0.6019	0.2108	0.0000	0.0000
1.2143	0.6019	0.2193	0.0000	0.0000
1.2610	0.6019	0.2277	0.0000	0.0000
1.3077	0.6019	0.2361	0.0000	0.0000

1.3544	0.6019	0.2446	0.0000	0.0000
1.4011	0.6019	0.2530	0.0000	0.0000
1.4478	0.6019	0.2614	0.0000	0.0000
1.4945	0.6019	0.2699	0.0000	0.0000
1.5412	0.6019	0.2783	0.0000	0.0000
1.5879	0.6019	0.2868	0.0000	0.0000
1.6346	0.6019	0.2952	0.0000	0.0000
1.6813	0.6019	0.3036	0.0000	0.0000
1.7280	0.6019	0.3121	0.0000	0.0000
1.7747	0.6019	0.3237	0.0000	0.0000
1.8214	0.6019	0.3354	0.0000	0.0000
1.8681	0.6019	0.3471	0.0000	0.0000
1.9148	0.6019	0.3587	0.0000	0.0000
1.9615	0.6019	0.3704	0.0000	0.0000
2.0082	0.6019	0.3821	0.0000	0.0000
2.0549	0.6019	0.3937	0.0000	0.0000
2.1016	0.6019	0.4054	0.0000	0.0000
2.1484	0.6019	0.4171	0.0000	0.0000
2.1951	0.6019	0.4287	0.0000	0.0000
2.2418	0.6019	0.4404	0.0000	0.0000
2.2885	0.6019	0.4521	0.0000	0.0000
2.3352	0.6019	0.4637	0.0000	0.0000
2.3819	0.6019	0.4754	0.0000	0.0000
2.4286	0.6019	0.4871	0.0000	0.0000
2.4753	0.6019	0.4987	0.0000	0.0000
2.5220	0.6019	0.5104	0.0000	0.0000
2.5687	0.6019	0.5221	0.0000	0.0000
2.6154	0.6019	0.5337	0.0000	0.0000
2.6621	0.6019	0.5454	0.0000	0.0000
2.7088	0.6019	0.5571	0.0000	0.0000
2.7555	0.6019	0.5687	0.0000	0.0000
2.8022	0.6019	0.5804	0.0000	0.0000
2.8489	0.6019	0.5921	0.0000	0.0000
2.8956	0.6019	0.6037	0.0000	0.0000
2.9423	0.6019	0.6154	0.0000	0.0000
2.9890	0.6019	0.6271	0.0000	0.0000
3.0357	0.6019	0.6387	0.0000	0.0000
3.0824	0.6019	0.6504	0.0000	0.0000
3.1291	0.6019	0.6621	0.0000	0.0000
3.1758	0.6019	0.6737	0.0000	0.0000
3.2225	0.6019	0.6854	0.0000	0.0000
3.2500	0.6019	0.6923	0.0000	0.0000

Biofilter Hydraulic Table

Stage(feet)	Area(ac.)	Volume(ac-ft.)	Discharge(cfs)	To Amended(cfs)	Infilt(cfs)
3.2500	0.6019	0.6923	0.0000	0.0264	0.0000
3.2967	0.6019	0.7204	0.0000	0.0264	0.0000
3.3434	0.6019	0.7485	0.0000	0.0264	0.0000
3.3901	0.6019	0.7766	0.0000	0.0264	0.0000
3.4368	0.6019	0.8047	0.0000	0.0264	0.0000
3.4835	0.6019	0.8328	0.0000	0.0264	0.0000
3.5302	0.6019	0.8609	0.0000	0.0264	0.0000
3.5769	0.6019	0.8890	0.0000	0.0264	0.0000
3.6236	0.6019	0.9172	0.0000	0.0264	0.0000
3.6703	0.6019	0.9453	0.0000	0.0264	0.0000
3.7170	0.6019	0.9734	0.0000	0.0264	0.0000
3.7637	0.6019	1.0015	0.0000	0.0264	0.0000
3.8104	0.6019	1.0296	0.0000	0.0264	0.0000

3.8571	0.6019	1.0577	0.0000	0.0264	0.0000
3.9038	0.6019	1.0858	0.0000	0.0264	0.0000
3.9505	0.6019	1.1139	0.0000	0.0264	0.0000
3.9973	0.6019	1.1421	0.0000	0.0264	0.0000
4.0440	0.6019	1.1702	0.0000	0.0264	0.0000
4.0907	0.6019	1.1983	0.0000	0.0264	0.0000
4.1374	0.6019	1.2264	0.0000	0.0264	0.0000
4.1841	0.6019	1.2545	0.0000	0.0264	0.0000
4.2308	0.6019	1.2826	0.0000	0.0264	0.0000
4.2500	0.6019	1.2942	0.0000	0.0264	0.0000

DRAFT

Surface rtial Ret 2

Element Flows To:

Outlet 1

Outlet 2

Bio Partial Ret 2

DRAFT

Bio Partial Ret 1

Bottom Length: 197.29 ft.
 Bottom Width: 197.29 ft.
 Material thickness of first layer: 0.25
 Material type for first layer: Mulch
 Material thickness of second layer: 1.5
 Material type for second layer: ESM
 Material thickness of third layer: 1.5
 Material type for third layer: GRAVEL
 Underdrain used
 Underdrain Diameter (feet): 0.5
 Orifice Diameter (in.): 0.830401500000001
 Offset (in.): 3
 Flow Through Underdrain (ac-ft.): 27.587
 Total Outflow (ac-ft.): 31.943
 Percent Through Underdrain: 86.36
 Discharge Structure
 Riser Height: 0.5 ft.
 Riser Diameter: 12 in.
 Element Flows To:
 Outlet 1 Outlet 2

Biofilter Hydraulic Table

Stage(feet)	Area(ac.)	Volume(ac-ft.)	Discharge(cfs)	Infilt(cfs)
0.0000	0.8936	0.0000	0.0000	0.0000
0.0522	0.8936	0.0140	0.0000	0.0000
0.1044	0.8936	0.0280	0.0000	0.0000
0.1566	0.8936	0.0420	0.0000	0.0000
0.2088	0.8936	0.0560	0.0000	0.0000
0.2610	0.8936	0.0700	0.0000	0.0000
0.3132	0.8936	0.0840	0.0000	0.0000
0.3654	0.8936	0.0979	0.0000	0.0000
0.4176	0.8936	0.1119	0.0000	0.0000
0.4698	0.8936	0.1259	0.0000	0.0000
0.5220	0.8936	0.1399	0.0000	0.0000
0.5742	0.8936	0.1539	0.0000	0.0000
0.6264	0.8936	0.1679	0.0000	0.0000
0.6786	0.8936	0.1819	0.0000	0.0000
0.7308	0.8936	0.1959	0.0000	0.0000
0.7830	0.8936	0.2099	0.0000	0.0000
0.8352	0.8936	0.2239	0.0000	0.0000
0.8874	0.8936	0.2379	0.0000	0.0000
0.9396	0.8936	0.2519	0.0000	0.0000
0.9918	0.8936	0.2659	0.0000	0.0000
1.0440	0.8936	0.2799	0.0000	0.0000
1.0962	0.8936	0.2938	0.0000	0.0000
1.1484	0.8936	0.3078	0.0000	0.0000
1.2005	0.8936	0.3218	0.0000	0.0000
1.2527	0.8936	0.3358	0.0000	0.0000
1.3049	0.8936	0.3498	0.0000	0.0000
1.3571	0.8936	0.3638	0.0000	0.0000
1.4093	0.8936	0.3778	0.0000	0.0000
1.4615	0.8936	0.3918	0.0000	0.0000
1.5137	0.8936	0.4058	0.0000	0.0000
1.5659	0.8936	0.4198	0.0000	0.0000

1.6181	0.8936	0.4338	0.0000	0.0000
1.6703	0.8936	0.4478	0.0000	0.0000
1.7225	0.8936	0.4618	0.0000	0.0000
1.7747	0.8936	0.4811	0.0000	0.0000
1.8269	0.8936	0.5005	0.0000	0.0000
1.8791	0.8936	0.5198	0.0000	0.0000
1.9313	0.8936	0.5392	0.0000	0.0000
1.9835	0.8936	0.5585	0.0000	0.0000
2.0357	0.8936	0.5779	0.0000	0.0000
2.0879	0.8936	0.5973	0.0000	0.0000
2.1401	0.8936	0.6166	0.0000	0.0000
2.1923	0.8936	0.6360	0.0000	0.0000
2.2445	0.8936	0.6553	0.0000	0.0000
2.2967	0.8936	0.6747	0.0000	0.0000
2.3489	0.8936	0.6940	0.0000	0.0000
2.4011	0.8936	0.7134	0.0000	0.0000
2.4533	0.8936	0.7327	0.0000	0.0000
2.5055	0.8936	0.7521	0.0000	0.0000
2.5577	0.8936	0.7715	0.0000	0.0000
2.6099	0.8936	0.7908	0.0000	0.0000
2.6621	0.8936	0.8102	0.0000	0.0000
2.7143	0.8936	0.8295	0.0000	0.0000
2.7665	0.8936	0.8489	0.0000	0.0000
2.8187	0.8936	0.8682	0.0000	0.0000
2.8709	0.8936	0.8876	0.0000	0.0000
2.9231	0.8936	0.9070	0.0000	0.0000
2.9753	0.8936	0.9263	0.0000	0.0000
3.0275	0.8936	0.9457	0.0000	0.0000
3.0797	0.8936	0.9650	0.0000	0.0000
3.1319	0.8936	0.9844	0.0000	0.0000
3.1841	0.8936	1.0037	0.0000	0.0000
3.2363	0.8936	1.0231	0.0000	0.0000
3.2500	0.8936	1.0282	0.0000	0.0000

Biofilter Hydraulic Table

Stage(feet)	Area(ac.)	Volume(ac-ft.)	Discharge(cfs)	To Amended(cfs)	Infilt(cfs)
3.2500	0.8936	1.0282	0.0000	0.0324	0.0000
3.3022	0.8936	1.0748	0.0000	0.0324	0.0000
3.3544	0.8936	1.1215	0.0000	0.0324	0.0000
3.4066	0.8936	1.1681	0.0000	0.0324	0.0000
3.4588	0.8936	1.2148	0.0000	0.0324	0.0000
3.5110	0.8936	1.2614	0.0000	0.0324	0.0000
3.5632	0.8936	1.3080	0.0000	0.0324	0.0000
3.6154	0.8936	1.3547	0.0000	0.0324	0.0000
3.6676	0.8936	1.4013	0.0000	0.0324	0.0000
3.7198	0.8936	1.4480	0.0000	0.0324	0.0000
3.7720	0.8936	1.4946	0.0000	0.0324	0.0000
3.8242	0.8936	1.5413	0.0000	0.0324	0.0000
3.8764	0.8936	1.5879	0.0000	0.0324	0.0000
3.9286	0.8936	1.6345	0.0000	0.0324	0.0000
3.9808	0.8936	1.6812	0.0000	0.0324	0.0000
4.0330	0.8936	1.7278	0.0000	0.0324	0.0000
4.0852	0.8936	1.7745	0.0000	0.0324	0.0000
4.1374	0.8936	1.8211	0.0000	0.0324	0.0000
4.1896	0.8936	1.8677	0.0000	0.0324	0.0000
4.2418	0.8936	1.9144	0.0000	0.0324	0.0000
4.2940	0.8936	1.9610	0.0000	0.0324	0.0000
4.3462	0.8936	2.0077	0.0000	0.0324	0.0000

4.3984	0.8936	2.0543	0.0000	0.0324	0.0000
4.4505	0.8936	2.1010	0.0000	0.0324	0.0000
4.5027	0.8936	2.1476	0.0000	0.0324	0.0000
4.5549	0.8936	2.1942	0.0000	0.0324	0.0000
4.6071	0.8936	2.2409	0.0000	0.0324	0.0000
4.6593	0.8936	2.2875	0.0015	0.0324	0.0000
4.7115	0.8936	2.3342	0.0022	0.0324	0.0000
4.7500	0.8936	2.3685	0.0032	0.0324	0.0000

DRAFT

Surface rtial Ret 1

Element Flows To:

Outlet 1


Outlet 2

Bio Partial Ret 1


DRAFT

Analysis Results

POC 1



+ Predeveloped x Mitigated



Predeveloped Landuse Totals for POC #1

Total Pervious Area: 1.79
Total Impervious Area: 0

Mitigated Landuse Totals for POC #1

Total Pervious Area: 0.33
Total Impervious Area: 1.46

Flow Frequency Method: Cunnane

Flow Frequency Return Periods for Predeveloped. POC #1

Return Period	Flow(cfs)
2 year	0.338562
5 year	0.491893
10 year	0.769406
25 year	1.17907

Flow Frequency Return Periods for Mitigated. POC #1

Return Period	Flow(cfs)
2 year	0.014617
5 year	0.350192
10 year	0.548751
25 year	0.771831

Duration Flows


The Facility PASSED

Flow(cfs)	Predev	Mit	Percentage	Pass/Fail
0.0339	510	469	91	Pass
0.0413	451	380	84	Pass
0.0487	411	321	78	Pass
0.0561	361	285	78	Pass
0.0636	330	271	82	Pass
0.0710	303	260	85	Pass
0.0784	259	235	90	Pass
0.0859	235	222	94	Pass
0.0933	209	212	101	Pass
0.1007	184	194	105	Pass
0.1082	160	176	110	Pass
0.1156	153	164	107	Pass
0.1230	145	154	106	Pass
0.1304	140	143	102	Pass
0.1379	136	133	97	Pass
0.1453	129	121	93	Pass
0.1527	127	116	91	Pass
0.1602	123	108	87	Pass
0.1676	120	100	83	Pass
0.1750	116	90	77	Pass
0.1825	110	85	77	Pass
0.1899	103	75	72	Pass
0.1973	99	70	70	Pass
0.2047	94	67	71	Pass
0.2122	90	66	73	Pass
0.2196	83	64	77	Pass
0.2270	78	59	75	Pass
0.2345	72	49	68	Pass
0.2419	65	45	69	Pass
0.2493	59	43	72	Pass
0.2568	56	41	73	Pass
0.2642	53	37	69	Pass
0.2716	45	34	75	Pass
0.2790	44	34	77	Pass
0.2865	40	32	80	Pass
0.2939	39	31	79	Pass
0.3013	38	29	76	Pass
0.3088	38	29	76	Pass
0.3162	38	26	68	Pass
0.3236	36	25	69	Pass
0.3310	35	25	71	Pass
0.3385	34	23	67	Pass
0.3459	30	21	70	Pass
0.3533	28	21	75	Pass
0.3608	27	17	62	Pass
0.3682	27	17	62	Pass
0.3756	26	17	65	Pass
0.3831	24	16	66	Pass
0.3905	23	12	52	Pass
0.3979	22	12	54	Pass
0.4053	21	12	57	Pass
0.4128	17	12	70	Pass
0.4202	16	11	68	Pass


0.4276	14	10	71	Pass
0.4351	14	9	64	Pass
0.4425	13	9	69	Pass
0.4499	13	9	69	Pass
0.4574	12	9	75	Pass
0.4648	12	8	66	Pass
0.4722	11	7	63	Pass
0.4796	11	6	54	Pass
0.4871	10	6	60	Pass
0.4945	10	5	50	Pass
0.5019	10	5	50	Pass
0.5094	10	5	50	Pass
0.5168	10	5	50	Pass
0.5242	9	5	55	Pass
0.5317	9	5	55	Pass
0.5391	9	5	55	Pass
0.5465	8	5	62	Pass
0.5539	7	5	71	Pass
0.5614	6	5	83	Pass
0.5688	6	5	83	Pass
0.5762	6	4	66	Pass
0.5837	5	4	80	Pass
0.5911	5	3	60	Pass
0.5985	5	3	60	Pass
0.6060	4	2	50	Pass
0.6134	4	2	50	Pass
0.6208	4	2	50	Pass
0.6282	4	2	50	Pass
0.6357	4	2	50	Pass
0.6431	4	2	50	Pass
0.6505	4	2	50	Pass
0.6580	4	2	50	Pass
0.6654	4	2	50	Pass
0.6728	4	2	50	Pass
0.6802	4	2	50	Pass
0.6877	4	2	50	Pass
0.6951	4	2	50	Pass
0.7025	4	2	50	Pass
0.7100	4	2	50	Pass
0.7174	4	2	50	Pass
0.7248	4	2	50	Pass
0.7323	4	2	50	Pass
0.7397	3	2	66	Pass
0.7471	3	2	66	Pass
0.7545	3	2	66	Pass
0.7620	3	2	66	Pass
0.7694	3	2	66	Pass

DRAFT

POC 2



+ Predeveloped x Mitigated



Predeveloped Landuse Totals for POC #2

Total Pervious Area: 1.39
Total Impervious Area: 0

Mitigated Landuse Totals for POC #2

Total Pervious Area: 0.34
Total Impervious Area: 1.05

Flow Frequency Method: Cunnane

Flow Frequency Return Periods for Predeveloped. POC #2

Return Period	Flow(cfs)
2 year	0.262905
5 year	0.381973
10 year	0.597472
25 year	0.915591

Flow Frequency Return Periods for Mitigated. POC #2

Return Period	Flow(cfs)
2 year	0.007763
5 year	0.266186
10 year	0.474116
25 year	0.646797

Duration Flows

The Facility PASSED

Flow(cfs)	Predev	Mit	Percentage	Pass/Fail
0.0263	508	553	108	Pass
0.0321	449	292	65	Pass
0.0378	413	277	67	Pass
0.0436	367	264	71	Pass
0.0494	330	250	75	Pass
0.0551	303	235	77	Pass
0.0609	267	224	83	Pass
0.0667	235	205	87	Pass
0.0724	210	190	90	Pass
0.0782	182	172	94	Pass
0.0840	161	168	104	Pass
0.0898	154	154	100	Pass
0.0955	145	144	99	Pass
0.1013	140	131	93	Pass
0.1071	135	123	91	Pass
0.1128	131	111	84	Pass
0.1186	127	105	82	Pass
0.1244	123	98	79	Pass
0.1301	119	87	73	Pass
0.1359	118	82	69	Pass
0.1417	110	73	66	Pass
0.1475	103	70	67	Pass
0.1532	99	65	65	Pass
0.1590	94	58	61	Pass
0.1648	90	53	58	Pass
0.1705	83	49	59	Pass
0.1763	78	48	61	Pass
0.1821	71	45	63	Pass
0.1878	65	41	63	Pass
0.1936	60	39	65	Pass
0.1994	56	37	66	Pass
0.2051	53	34	64	Pass
0.2109	46	34	73	Pass
0.2167	44	32	72	Pass
0.2225	40	31	77	Pass
0.2282	39	31	79	Pass
0.2340	38	28	73	Pass
0.2398	38	26	68	Pass
0.2455	38	26	68	Pass
0.2513	36	23	63	Pass
0.2571	35	20	57	Pass
0.2628	34	20	58	Pass
0.2686	30	18	60	Pass
0.2744	28	18	64	Pass
0.2801	27	16	59	Pass
0.2859	27	16	59	Pass
0.2917	26	16	61	Pass
0.2975	24	16	66	Pass
0.3032	23	14	60	Pass
0.3090	22	13	59	Pass
0.3148	21	12	57	Pass
0.3205	17	12	70	Pass
0.3263	16	12	75	Pass

0.3321	14	11	78	Pass
0.3378	14	11	78	Pass
0.3436	13	10	76	Pass
0.3494	13	10	76	Pass
0.3552	12	10	83	Pass
0.3609	12	10	83	Pass
0.3667	11	10	90	Pass
0.3725	11	8	72	Pass
0.3782	10	8	80	Pass
0.3840	10	6	60	Pass
0.3898	10	6	60	Pass
0.3955	10	6	60	Pass
0.4013	10	6	60	Pass
0.4071	9	6	66	Pass
0.4128	9	6	66	Pass
0.4186	9	6	66	Pass
0.4244	8	6	75	Pass
0.4302	7	5	71	Pass
0.4359	6	5	83	Pass
0.4417	6	5	83	Pass
0.4475	6	5	83	Pass
0.4532	5	5	100	Pass
0.4590	5	5	100	Pass
0.4648	5	4	80	Pass
0.4705	4	4	100	Pass
0.4763	4	4	100	Pass
0.4821	4	4	100	Pass
0.4879	4	4	100	Pass
0.4936	4	4	100	Pass
0.4994	4	4	100	Pass
0.5052	4	4	100	Pass
0.5109	4	2	50	Pass
0.5167	4	2	50	Pass
0.5225	4	2	50	Pass
0.5282	4	2	50	Pass
0.5340	4	2	50	Pass
0.5398	4	2	50	Pass
0.5455	4	2	50	Pass
0.5513	4	2	50	Pass
0.5571	4	2	50	Pass
0.5629	4	2	50	Pass
0.5686	4	2	50	Pass
0.5744	3	2	66	Pass
0.5802	3	2	66	Pass
0.5859	3	2	66	Pass
0.5917	3	2	66	Pass
0.5975	3	2	66	Pass

DRAFT

Model Default Modifications

Total of 0 changes have been made.

PERLND Changes

No PERLND changes have been made.

IMPLND Changes

No IMPLND changes have been made.

DRAFT

Appendix
Predeveloped Schematic



Mitigated Schematic



Predeveloped UCI File

RUN

GLOBAL

WWM4 model simulation
START 1973 10 01 END 2004 09 30
RUN INTERP OUTPUT LEVEL 3 0
RESUME 0 RUN 1 UNIT SYSTEM 1
END GLOBAL

FILES

<File>	<Un#>	<-----File Name----->	***
<-ID->			***
WDM	26	2025_SCC.wdm	
MESSU	25	Pre2025_SCC.MES	
	27	Pre2025_SCC.L61	
	28	Pre2025_SCC.L62	
	30	POC2025_SCC1.dat	
	31	POC2025_SCC2.dat	

END FILES

OPN SEQUENCE

INGRP INDELT 00:60

PERLND 19

COPY 501

COPY 502

DISPLY 1

DISPLY 2

END INGRP

END OPN SEQUENCE

DISPLY

DISPLY-INFO1

#	-	#	<-----Title----->	***TRAN	PIVL	DIG1	FIL1	PYR	DIG2	FIL2	YRND
1			Pre Basin 1	MAX				1	2	30	9
2			Pre Basin 2	MAX				1	2	31	9

END DISPLY-INFO1

END DISPLY

COPY

TIMESERIES

#	-	#	NPT	NMN	***
---	---	---	-----	-----	-----

1			1	1	
---	--	--	---	---	--

501			1	1	
-----	--	--	---	---	--

502			1	1	
-----	--	--	---	---	--

END TIMESERIES

END COPY

GENER

OPCODE

#	#	OPCD	***
---	---	------	-----

END OPCODE

PARM

#	#	K	***
---	---	---	-----

END PARM

END GENER

PERLND

GEN-INFO

<PLS >	<-----Name----->	NBLKS	Unit-systems	Printer	***	
#	-	#	User	t-series	Engl Metr	***
			in	out		***

19			C,NatVeg,Flat	1	1	1	1	27	0	
----	--	--	---------------	---	---	---	---	----	---	--

END GEN-INFO

*** Section PWATER***

ACTIVITY

<PLS >	***** Active Sections *****														
#	-	#	ATMP	SNOW	PWAT	SED	PST	PWG	PQAL	MSTL	PEST	NITR	PHOS	TRAC	***
19			0	0	1	0	0	0	0	0	0	0	0	0	

END ACTIVITY

PRINT-INFO


```

<PLS > ***** Print-flags ***** PIVL  PYR
# - # ATMP SNOW PWAT  SED  PST  PWG  PQAL MSTL PEST NITR PHOS TRAC  *****
19      0      0      4      0      0      0      0      0      0      0      0      0      1      9
END PRINT-INFO

```

```

PWAT-PARM1
<PLS > PWATER variable monthly parameter value flags ***
# - # CSNO RTOP UZFG  VCS  VUZ  VNN VIFW VIRC  VLE INFC  HWT ***
19      0      1      1      1      0      0      0      0      1      1      0
END PWAT-PARM1

```

```

PWAT-PARM2
<PLS > PWATER input info: Part 2          ***
# - # ***FOREST  LZSN  INFILT  LSUR  SLSUR  KVARY  AGWRC
19      0      3.8      0.035      100      0.05      2.5      0.915
END PWAT-PARM2

```

```

PWAT-PARM3
<PLS > PWATER input info: Part 3          ***
# - # ***PETMAX  PETMIN  INFEXP  INFILD  DEEPFR  BASETP  AGWETP
19      0      0      2      2      0      0.05      0.05
END PWAT-PARM3

```

```

PWAT-PARM4
<PLS > PWATER input info: Part 4          ***
# - # CEPSC  UZSN  NSUR  INTFW  IRC  LZETP ***
19      0      0.6      0.04      1      0.3      0
END PWAT-PARM4

```

```

MON-LZETPARM
<PLS > PWATER input info: Part 3          ***
# - # JAN FEB MAR APR MAY JUN JUL AUG SEP OCT NOV DEC ***
19      0.4 0.4 0.4 0.4 0.6 0.6 0.6 0.6 0.4 0.4 0.4
END MON-LZETPARM

```

```

MON-INTERCEP
<PLS > PWATER input info: Part 3          ***
# - # JAN FEB MAR APR MAY JUN JUL AUG SEP OCT NOV DEC ***
19      0.1 0.1 0.1 0.1 0.06 0.06 0.06 0.06 0.06 0.1 0.1 0.1
END MON-INTERCEP

```

```

PWAT-STATE1
<PLS > *** Initial conditions at start of simulation
      ran from 1990 to end of 1992 (pat 1-11-95) RUN 21 ***
# - # *** CEPS  SURS  UZS  IFWS  LZS  AGWS  GWVS
19      0      0      0.01      0      0.4      0.01      0
END PWAT-STATE1

```

END PERLND

```

IMPLND
GEN-INFO
<PLS ><-----Name----->  Unit-systems  Printer ***
# - #                        User  t-series Engl Metr ***
                        in  out      ***
END GEN-INFO
*** Section IWATER***

```

```

ACTIVITY
<PLS > ***** Active Sections *****
# - # ATMP SNOW IWAT  SLD  IWG IQAL  ***
END ACTIVITY

```

```

PRINT-INFO
<ILS > ***** Print-flags ***** PIVL  PYR
# - # ATMP SNOW IWAT  SLD  IWG IQAL  *****
END PRINT-INFO

```

```

IWAT-PARM1
<PLS > IWATER variable monthly parameter value flags ***
# - # CSNO RTOP VRS  VNN RTLI  ***
END IWAT-PARM1

```

```

IWAT-PARM2
  <PLS >          IWATER input info: Part 2          ***
  # - # *** LSUR      SLSUR      NSUR      RETSC
END IWAT-PARM2

IWAT-PARM3
  <PLS >          IWATER input info: Part 3          ***
  # - # ***PETMAX      PETMIN
END IWAT-PARM3

IWAT-STATE1
  <PLS > *** Initial conditions at start of simulation
  # - # *** RETS      SURS
END IWAT-STATE1

END IMPLND

SCHEMATIC
<-Source->          <--Area-->          <-Target->          MBLK          ***
<Name> #          <-factor->          <Name> #          Tbl#          ***
Pre Basin 1***
PERLND 19          1.79          COPY 501          12
PERLND 19          1.79          COPY 501          13
Pre Basin 2***
PERLND 19          1.39          COPY 502          12
PERLND 19          1.39          COPY 502          13

*****Routing*****
END SCHEMATIC

NETWORK
<-Volume-> <-Grp> <-Member-><--Mult-->Tran <-Target vols> <-Grp> <-Member-> ***
<Name> #          <Name> # #<-factor->strg <Name> # #          <Name> # #          ***
COPY 501 OUTPUT MEAN 1 1 12.1          DISPLY 1          INPUT TIMSER 1
COPY 502 OUTPUT MEAN 1 1 12.1          DISPLY 2          INPUT TIMSER 1

<-Volume-> <-Grp> <-Member-><--Mult-->Tran <-Target vols> <-Grp> <-Member-> ***
<Name> #          <Name> # #<-factor->strg <Name> # #          <Name> # #          ***
END NETWORK

RCHRES
GEN-INFO
  RCHRES          Name          Nexits          Unit Systems          Printer          ***
  # - #<-----><----> User T-series Engl Metr LKFG          ***
                                in out          ***
END GEN-INFO
*** Section RCHRES***

ACTIVITY
  <PLS > ***** Active Sections *****
  # - # HYFG ADFG CNFG HTFG SDFG GQFG OXFG NUFG PKFG PHFG ***
END ACTIVITY

PRINT-INFO
  <PLS > ***** Print-flags ***** PIVL PYR
  # - # HYDR ADCA CONS HEAT SED GQL OXRX NUTR PLNK PHCB PIVL PYR *****
END PRINT-INFO

HYDR-PARM1
  RCHRES Flags for each HYDR Section          ***
  # - # VC A1 A2 A3 ODFVFG for each *** ODGTFG for each FUNCT for each
        FG FG FG FG possible exit *** possible exit possible exit
        * * * * * * * * * * * * * * * *
END HYDR-PARM1

HYDR-PARM2
  # - # FTABNO          LEN          DELTH          STCOR          KS          DB50          ***
  <-----><-----><-----><-----><-----><-----><----->          ***

```

```

END HYDR-PARM2
HYDR-INIT
  RCHRES Initial conditions for each HYDR section ***
  # - # *** VOL Initial value of COLIND Initial value of OUTDGT
  *** ac-ft for each possible exit for each possible exit
<-----><-----> <----><----><----><----><----> *** <----><----><----><----><---->
END HYDR-INIT
END RCHRES

SPEC-ACTIONS
END SPEC-ACTIONS
FTABLES
END FTABLES

EXT SOURCES
<-Volume-> <Member> SsysSgap<--Mult-->Tran <-Target vols> <-Grp> <-Member-> ***
<Name> # <Name> # tem strg<-factor->strg <Name> # # <Name> # # ***
WDM 2 PREC ENGL 1 PERLND 1 999 EXTNL PREC
WDM 2 PREC ENGL 1 IMPLND 1 999 EXTNL PREC
WDM 1 EVAP ENGL 1 PERLND 1 999 EXTNL PETINP
WDM 1 EVAP ENGL 1 IMPLND 1 999 EXTNL PETINP

END EXT SOURCES

EXT TARGETS
<-Volume-> <-Grp> <-Member-><--Mult-->Tran <-Volume-> <Member> Tsys Tgap Amd ***
<Name> # <Name> # #<-factor->strg <Name> # <Name> tem strg strg***
COPY 501 OUTPUT MEAN 1 1 12.1 WDM 501 FLOW ENGL REPL
COPY 502 OUTPUT MEAN 1 1 12.1 WDM 502 FLOW ENGL REPL
END EXT TARGETS

MASS-LINK
<Volume> <-Grp> <-Member-><--Mult--> <Target> <-Grp> <-Member->***
<Name> <Name> # #<-factor-> <Name> <Name> # #***
MASS-LINK 12
PERLND PWATER SURO 0.083333 COPY INPUT MEAN
END MASS-LINK 12

MASS-LINK 13
PERLND PWATER IFWO 0.083333 COPY INPUT MEAN
END MASS-LINK 13

END MASS-LINK

END RUN

```

Mitigated UCI File

RUN

GLOBAL

WWM4 model simulation
START 1973 10 01 END 2004 09 30
RUN INTERP OUTPUT LEVEL 3 0
RESUME 0 RUN 1 UNIT SYSTEM 1
END GLOBAL

FILES

<File>	<Un#>	<-----File Name----->	***
<-ID->			***
WDM	26	2025_SCC.wdm	
MESSU	25	Mit2025_SCC.MES	
	27	Mit2025_SCC.L61	
	28	Mit2025_SCC.L62	
	31	POC2025_SCC2.dat	
	30	POC2025_SCC1.dat	

END FILES

OPN SEQUENCE

INGRP INDELT 00:60

PERLND 19
IMPLND 1
RCHRES 1
RCHRES 2
RCHRES 3
RCHRES 4
COPY 2
COPY 502
COPY 1
COPY 501
DISPLY 2
DISPLY 1

END INGRP

END OPN SEQUENCE

DISPLY

DISPLY-INFO1

#	-	#	<-----Title----->	***	TRAN	PIVL	DIG1	FIL1	PYR	DIG2	FIL2	YRND
2			Surface rtial Ret	2	MAX				1	2	31	9
1			Surface rtial Ret	1	MAX				1	2	30	9

END DISPLY-INFO1

END DISPLY

COPY

TIMESERIES

#	-	#	NPT	NMN	***
1			1	1	
2			1	1	
502			1	1	
501			1	1	

END TIMESERIES

END COPY

GENER

OPCODE

OPCD ***

END OPCODE

PARM

K ***

END PARM

END GENER

PERLND

GEN-INFO

<PLS >	<-----Name----->	NBLKS	Unit-systems	Printer	***
#	-	#	User	t-series	Engl Metr
			in	out	***
19	C,NatVeg,Flat	1	1	1	1
					27
					0

END GEN-INFO

*** Section PWATER***

```

ACTIVITY
<PLS > ***** Active Sections *****
# - # ATMP SNOW PWAT SED PST PWG PQAL MSTL PEST NITR PHOS TRAC ***
19      0      0      1      0      0      0      0      0      0      0      0      0
END ACTIVITY

PRINT-INFO
<PLS > ***** Print-flags ***** PIVL PYR
# - # ATMP SNOW PWAT SED PST PWG PQAL MSTL PEST NITR PHOS TRAC *****
19      0      0      4      0      0      0      0      0      0      0      0      0      1      9
END PRINT-INFO

PWAT-PARM1
<PLS > PWATER variable monthly parameter value flags ***
# - # CSNO RTOP UZFG VCS VUZ VNN VIFW VIRC VLE INFC HWT ***
19      0      1      1      1      0      0      0      0      1      1      0
END PWAT-PARM1

PWAT-PARM2
<PLS > PWATER input info: Part 2 ***
# - # ***FOREST LZSN INFILT LSUR SLSUR KVARY AGWRC
19      0      3.8      0.035      100      0.05      2.5      0.915
END PWAT-PARM2

PWAT-PARM3
<PLS > PWATER input info: Part 3 ***
# - # ***PETMAX PETMIN INFEXP INFILD DEEPFR BASETP AGWETP
19      0      0      2      2      0      0.05      0.05
END PWAT-PARM3

PWAT-PARM4
<PLS > PWATER input info: Part 4 ***
# - # CEPSC UZSN NSUR INTFW IRC LZETP ***
19      0      0.6      0.04      1      0.3      0
END PWAT-PARM4

MON-LZETPARM
<PLS > PWATER input info: Part 3 ***
# - # JAN FEB MAR APR MAY JUN JUL AUG SEP OCT NOV DEC ***
19      0.4      0.4      0.4      0.4      0.6      0.6      0.6      0.6      0.6      0.4      0.4      0.4
END MON-LZETPARM

MON-INTERCEP
<PLS > PWATER input info: Part 3 ***
# - # JAN FEB MAR APR MAY JUN JUL AUG SEP OCT NOV DEC ***
19      0.1      0.1      0.1      0.1      0.06      0.06      0.06      0.06      0.06      0.1      0.1      0.1
END MON-INTERCEP

PWAT-STATE1
<PLS > *** Initial conditions at start of simulation
ran from 1990 to end of 1992 (pat 1-11-95) RUN 21 ***
# - # *** CEPS SURS UZS IFWS LZS AGWS GWVS
19      0      0      0.01      0      0.4      0.01      0
END PWAT-STATE1

END PERLND

IMPLND
GEN-INFO
<PLS ><-----Name-----> Unit-systems Printer ***
# - # User t-series Engr Metr ***
in out ***
1 IMPERVIOUS-FLAT 1 1 1 27 0
END GEN-INFO
*** Section IWATER***

ACTIVITY
<PLS > ***** Active Sections *****
# - # ATMP SNOW IWAT SLD IWG IQAL ***
1      0      0      1      0      0      0
END ACTIVITY

```

```

PRINT-INFO
<ILS > ***** Print-flags ***** PIVL  PYR
# - # ATMP SNOW IWAT  SLD  IWG IQAL  *****
1      0      0      4      0      0      0      1      9
END PRINT-INFO

IWAT-PARM1
<PLS >  IWATER variable monthly parameter value flags  ***
# - # CSNO RTOP  VRS  VNN RTLI  ***
1      0      0      0      0      1
END IWAT-PARM1

IWAT-PARM2
<PLS >      IWATER input info: Part 2      ***
# - # ***  LSUR      SLSUR      NSUR      RETSC
1      100      0.05      0.011      0.1
END IWAT-PARM2

IWAT-PARM3
<PLS >      IWATER input info: Part 3      ***
# - # ***PETMAX      PETMIN
1      0      0
END IWAT-PARM3

IWAT-STATE1
<PLS > *** Initial conditions at start of simulation
# - # ***  RETS      SURS
1      0      0
END IWAT-STATE1

END IMPLND

SCHEMATIC
<-Source->      <--Area-->      <-Target->      MBLK      ***
<Name>  #      <-factor->      <Name>  #      Tbl#      ***
Prop Basin  2***
PERLND  19      0.34      RCHRES  1      2
PERLND  19      0.34      RCHRES  1      3
IMPLND   1      1.05      RCHRES  1      5
Prop Basin  1***
PERLND  19      0.33      RCHRES  3      2
PERLND  19      0.33      RCHRES  3      3
IMPLND   1      1.46      RCHRES  3      5

*****Routing*****
PERLND  19      0.34      COPY  2      12
IMPLND   1      1.05      COPY  2      15
PERLND  19      0.34      COPY  2      13
RCHRES   1      1      RCHRES  2      8
PERLND  19      0.33      COPY  1      12
IMPLND   1      1.46      COPY  1      15
PERLND  19      0.33      COPY  1      13
RCHRES   3      1      RCHRES  4      8
RCHRES   2      1      COPY  502      16
RCHRES   1      1      COPY  502      17
RCHRES   4      1      COPY  501      16
RCHRES   3      1      COPY  501      17
END SCHEMATIC

NETWORK
<-Volume-> <-Grp> <-Member-><--Mult-->Tran <-Target vols> <-Grp> <-Member-> ***
<Name>  #      <Name>  # #<-factor->strg <Name>  #  #      <Name>  #  #      ***
COPY  502 OUTPUT MEAN  1 1  12.1      DISPLY  2      INPUT  TIMSER 1
COPY  501 OUTPUT MEAN  1 1  12.1      DISPLY  1      INPUT  TIMSER 1

<-Volume-> <-Grp> <-Member-><--Mult-->Tran <-Target vols> <-Grp> <-Member-> ***
<Name>  #      <Name>  # #<-factor->strg <Name>  #  #      <Name>  #  #      ***
END NETWORK

```

RCHRES

GEN-INFO

RCHRES	Name	Nexits	Unit	Systems	Printer			
# - #	<----->	<---->	User	T-series	Engl Metr	LKFG		
				in out				
1	Surface rtial Re-029	2	1	1 1	28 0	1		
2	Bio Partial Ret -028	1	1	1 1	28 0	1		
3	Surface rtial Re-040	2	1	1 1	28 0	1		
4	Bio Partial Ret -039	1	1	1 1	28 0	1		

END GEN-INFO

*** Section RCHRES***

ACTIVITY

<PLS > ***** Active Sections *****												
# - #	HYFG	ADFG	CNFG	HTFG	SDFG	GQFG	OXFG	NUFG	PKFG	PHFG		***
1	1	0	0	0	0	0	0	0	0	0		
2	1	0	0	0	0	0	0	0	0	0		
3	1	0	0	0	0	0	0	0	0	0		
4	1	0	0	0	0	0	0	0	0	0		

END ACTIVITY

PRINT-INFO

<PLS > ***** Print-flags *****													PIVL	PYR	
# - #	HYDR	ADCA	CONS	HEAT	SED	GOL	OXRX	NUTR	PLNK	PHCB	PIVL	PYR		*****	
1	4	0	0	0	0	0	0	0	0	0	1	9			
2	4	0	0	0	0	0	0	0	0	0	1	9			
3	4	0	0	0	0	0	0	0	0	0	1	9			
4	4	0	0	0	0	0	0	0	0	0	1	9			

END PRINT-INFO

HYDR-PARM1

RCHRES Flags for each HYDR Section													*****			
# - #	VC	A1	A2	A3	ODFVFG	for each	***	ODGTFG	for each	FUNCT	for each					
	FG	FG	FG	FG	possible	exit	***	possible	exit	possible	exit					
	*	*	*	*	*	*	*	*	*	*	*	*	*	*		
1	0	1	0	0	4	5	0	0	0	2	2	2	2	2		
2	0	1	0	0	4	0	0	0	0	2	2	2	2	2		
3	0	1	0	0	4	5	0	0	0	2	2	2	2	2		
4	0	1	0	0	4	0	0	0	0	2	2	2	2	2		

END HYDR-PARM1

HYDR-PARM2

# - #	FTABNO	LEN	DELTH	STCOR	KS	DB50		
<----->	<----->	<----->	<----->	<----->	<----->	<----->		
1	1	0.01	0.0	0.0	0.0	0.0		
2	2	0.03	0.0	0.0	0.0	0.0		
3	3	0.01	0.0	0.0	0.0	0.0		
4	4	0.04	0.0	0.0	0.0	0.0		

END HYDR-PARM2

HYDR-INIT

RCHRES Initial conditions for each HYDR section													*****			
# - #	***	VOL	Initial value of COLIND					Initial value of OUTDGT								
	***	ac-ft	for each possible exit					for each possible exit								
<----->	<----->		<----->	<----->	<----->	<----->	***	<----->	<----->	<----->	<----->	<----->				
1	0	4.0	5.0	0.0	0.0	0.0		0.0	0.0	0.0	0.0	0.0				
2	0	4.0	0.0	0.0	0.0	0.0		0.0	0.0	0.0	0.0	0.0				
3	0	4.0	5.0	0.0	0.0	0.0		0.0	0.0	0.0	0.0	0.0				
4	0	4.0	0.0	0.0	0.0	0.0		0.0	0.0	0.0	0.0	0.0				

END HYDR-INIT

END RCHRES

SPEC-ACTIONS

END SPEC-ACTIONS

FTABLES

FTABLE	2					
71	4					
Depth	Area	Volume	Outflow1	Velocity	Travel Time	***
(ft)	(acres)	(acre-ft)	(cfs)	(ft/sec)	(Minutes)	***
0.000000	0.601944	0.000000	0.000000			

0.046703	0.601944	0.008434	0.000000
0.093407	0.601944	0.016868	0.000000
0.140110	0.601944	0.025301	0.000000
0.186813	0.601944	0.033735	0.000000
0.233516	0.601944	0.042169	0.000000
0.280220	0.601944	0.050603	0.000000
0.326923	0.601944	0.059037	0.000000
0.373626	0.601944	0.067471	0.000000
0.420330	0.601944	0.075904	0.000000
0.467033	0.601944	0.084338	0.000000
0.513736	0.601944	0.092772	0.000000
0.560440	0.601944	0.101206	0.000000
0.607143	0.601944	0.109640	0.000000
0.653846	0.601944	0.118074	0.000000
0.700549	0.601944	0.126507	0.000000
0.747253	0.601944	0.134941	0.000000
0.793956	0.601944	0.143375	0.000000
0.840659	0.601944	0.151809	0.000000
0.887363	0.601944	0.160243	0.000000
0.934066	0.601944	0.168677	0.000000
0.980769	0.601944	0.177110	0.000000
1.027473	0.601944	0.185544	0.000000
1.074176	0.601944	0.193978	0.000000
1.120879	0.601944	0.202412	0.000000
1.167582	0.601944	0.210846	0.000000
1.214286	0.601944	0.219280	0.000937
1.260989	0.601944	0.227713	0.001406
1.307692	0.601944	0.236147	0.002206
1.354396	0.601944	0.244581	0.002606
1.401099	0.601944	0.253015	0.003210
1.447802	0.601944	0.261449	0.003512
1.494505	0.601944	0.269883	0.003995
1.541209	0.601944	0.278316	0.004237
1.587912	0.601944	0.286750	0.004646
1.634615	0.601944	0.295184	0.004851
1.681319	0.601944	0.303618	0.005212
1.728022	0.601944	0.312052	0.005393
1.774725	0.601944	0.320486	0.005719
1.821429	0.601944	0.328919	0.005883
1.868132	0.601944	0.337353	0.006184
1.914835	0.601944	0.345787	0.006334
1.961538	0.601944	0.354221	0.006615
2.008242	0.601944	0.362655	0.006755
2.054945	0.601944	0.371089	0.007019
2.101648	0.601944	0.379523	0.007151
2.148352	0.601944	0.387957	0.007401
2.195055	0.601944	0.396391	0.007525
2.241758	0.601944	0.404825	0.007763
2.288462	0.601944	0.413259	0.007763
2.335165	0.601944	0.421693	0.008060
2.381868	0.601944	0.430127	0.008524
2.428571	0.601944	0.438561	0.009051
2.475275	0.601944	0.446995	0.009593
2.521978	0.601944	0.455429	0.010128
2.568681	0.601944	0.463863	0.010646
2.615385	0.601944	0.472297	0.011145
2.662088	0.601944	0.480731	0.011625
2.708791	0.601944	0.489165	0.012088
2.755495	0.601944	0.497599	0.012534
2.802198	0.601944	0.506033	0.012965
2.848901	0.601944	0.514467	0.013382
2.895604	0.601944	0.522901	0.013786
2.942308	0.601944	0.531335	0.014180
2.989011	0.601944	0.539769	0.014562
3.035714	0.601944	0.548203	0.014936
3.082418	0.601944	0.556637	0.015301
3.129121	0.601944	0.565071	0.015658
3.175824	0.601944	0.573505	0.016009
3.222527	0.601944	0.581939	0.016358
3.250000	0.601944	0.590373	0.026411


```

END FTABLE 2
FTABLE 1
23 5
Depth Area Volume Outflow1 Outflow2 Velocity Travel Time***
(ft) (acres) (acre-ft) (cfs) (cfs) (ft/sec) (Minutes)***
0.000000 0.601944 0.000000 0.000000 0.000000
0.046703 0.601944 0.028113 0.000000 0.026411
0.093407 0.601944 0.056226 0.000000 0.026411
0.140110 0.601944 0.084338 0.000000 0.026411
0.186813 0.601944 0.112451 0.000000 0.026411
0.233516 0.601944 0.140564 0.000000 0.026411
0.280220 0.601944 0.168677 0.000000 0.026411
0.326923 0.601944 0.196789 0.000000 0.026411
0.373626 0.601944 0.224902 0.000000 0.026411
0.420330 0.601944 0.253015 0.000000 0.026411
0.467033 0.601944 0.281128 0.000000 0.026411
0.513736 0.601944 0.309240 0.017087 0.026411
0.560440 0.601944 0.337353 0.157374 0.026411
0.607143 0.601944 0.365466 0.369426 0.026411
0.653846 0.601944 0.393579 0.627270 0.026411
0.700549 0.601944 0.421691 0.911089 0.026411
0.747253 0.601944 0.449804 1.200769 0.026411
0.793956 0.601944 0.477917 1.476083 0.026411
0.840659 0.601944 0.506030 1.718754 0.026411
0.887363 0.601944 0.534143 1.915531 0.026411
0.934066 0.601944 0.562255 2.061968 0.026411
0.980769 0.601944 0.590368 2.166777 0.026411
1.000000 0.601944 0.601944 2.287491 0.026411

```

```

END FTABLE 1
FTABLE 4
64 4
Depth Area Volume Outflow1 Velocity Travel Time***
(ft) (acres) (acre-ft) (cfs) (ft/sec) (Minutes)***
0.000000 0.893566 0.000000 0.000000
0.052198 0.893566 0.013993 0.000000
0.104396 0.893566 0.027985 0.000000
0.156593 0.893566 0.041978 0.000000
0.208791 0.893566 0.055971 0.000000
0.260989 0.893566 0.069963 0.000000
0.313187 0.893566 0.083956 0.000000
0.365385 0.893566 0.097949 0.000000
0.417582 0.893566 0.111941 0.000000
0.469780 0.893566 0.125934 0.000000
0.521978 0.893566 0.139927 0.000000
0.574176 0.893566 0.153919 0.000000
0.626374 0.893566 0.167912 0.000000
0.678571 0.893566 0.181905 0.000000
0.730769 0.893566 0.195897 0.000000
0.782967 0.893566 0.209890 0.000000
0.835165 0.893566 0.223882 0.000000
0.887363 0.893566 0.237875 0.000000
0.939560 0.893566 0.251868 0.000000
0.991758 0.893566 0.265860 0.000000
1.043956 0.893566 0.279853 0.000000
1.096154 0.893566 0.293846 0.000000
1.148352 0.893566 0.307838 0.000000
1.200549 0.893566 0.321831 0.000000
1.252747 0.893566 0.335824 0.000000
1.304945 0.893566 0.349816 0.000000
1.357143 0.893566 0.363809 0.000000
1.409341 0.893566 0.377802 0.001476
1.461538 0.893566 0.391794 0.002214
1.513736 0.893566 0.405787 0.003228
1.565934 0.893566 0.419780 0.003735
1.618132 0.893566 0.433772 0.004479
1.670330 0.893566 0.447765 0.004851
1.722527 0.893566 0.461758 0.005448
1.774725 0.893566 0.481114 0.005746
1.826923 0.893566 0.500471 0.006257
1.879121 0.893566 0.519827 0.006512

```

1.931319	0.893566	0.539184	0.006966
1.983516	0.893566	0.558540	0.007193
2.035714	0.893566	0.577897	0.007606
2.087912	0.893566	0.597253	0.007812
2.140110	0.893566	0.616610	0.008194
2.192308	0.893566	0.635966	0.008385
2.244505	0.893566	0.655323	0.008593
2.296703	0.893566	0.674679	0.009080
2.348901	0.893566	0.694036	0.009784
2.401099	0.893566	0.713392	0.010559
2.453297	0.893566	0.732749	0.011340
2.505495	0.893566	0.752105	0.012100
2.557692	0.893566	0.771462	0.012829
2.609890	0.893566	0.790818	0.013525
2.662088	0.893566	0.810175	0.014190
2.714286	0.893566	0.829531	0.014827
2.766484	0.893566	0.848888	0.015438
2.818681	0.893566	0.868244	0.016027
2.870879	0.893566	0.887601	0.016594
2.923077	0.893566	0.906957	0.017143
2.975275	0.893566	0.926314	0.017675
3.027473	0.893566	0.945670	0.018192
3.079670	0.893566	0.965027	0.018695
3.131868	0.893566	0.984383	0.019187
3.184066	0.893566	1.003740	0.019669
3.236264	0.893566	1.023096	0.020150
3.250000	0.893566	1.030869	0.032411

END FTABLE 4

FTABLE 3

30 5

Depth (ft)	Area (acres)	Volume (acre-ft)	Outflow1 (cfs)	Outflow2 (cfs)	Velocity (ft/sec)	Travel Time*** (Minutes)***
0.000000	0.893566	0.000000	0.000000	0.000000		
0.052198	0.893566	0.046642	0.000000	0.032411		
0.104396	0.893566	0.093284	0.000000	0.032411		
0.156593	0.893566	0.139927	0.000000	0.032411		
0.208791	0.893566	0.186569	0.000000	0.032411		
0.260989	0.893566	0.233211	0.000000	0.032411		
0.313187	0.893566	0.279853	0.000000	0.032411		
0.365385	0.893566	0.326495	0.000000	0.032411		
0.417582	0.893566	0.373137	0.000000	0.032411		
0.469780	0.893566	0.419780	0.000000	0.032411		
0.521978	0.893566	0.466422	0.034569	0.032411		
0.574176	0.893566	0.513064	0.213745	0.032411		
0.626374	0.893566	0.559706	0.471194	0.032411		
0.678571	0.893566	0.606348	0.775552	0.032411		
0.730769	0.893566	0.652991	1.099144	0.032411		
0.782967	0.893566	0.699633	1.413620	0.032411		
0.835165	0.893566	0.746275	1.692395	0.032411		
0.887363	0.893566	0.792917	1.915531	0.032411		
0.939560	0.893566	0.839559	2.076126	0.032411		
0.991758	0.893566	0.886202	2.187838	0.032411		
1.043956	0.893566	0.932844	2.322958	0.032411		
1.096154	0.893566	0.979486	2.431861	0.032411		
1.148352	0.893566	1.026128	2.536091	0.032411		
1.200549	0.893566	1.072770	2.636204	0.032411		
1.252747	0.893566	1.119412	2.732651	0.032411		
1.304945	0.893566	1.166055	2.825808	0.032411		
1.357143	0.893566	1.212697	2.915991	0.032411		
1.409341	0.893566	1.259339	3.003467	0.032411		
1.461538	0.893566	1.305981	3.088466	0.032411		
1.500000	0.893566	1.340349	3.171188	0.032411		

END FTABLE 3

END FTABLES

EXT SOURCES

<-Volume->	<Member>	SsysSgap<--Mult-->	Tran	<-Target vols>	<-Grp>	<-Member->	***
<Name>	#	<Name>	#	tem strg<-factor->	strg	<Name>	# #
WDM	2	PREC	ENGL	1	PERLND	1 999	EXTNL PREC
WDM	2	PREC	ENGL	1	IMPLND	1 999	EXTNL PREC

WDM	1	EVAP	ENGL	1	PERLND	1	999	EXTNL	PETINP
WDM	1	EVAP	ENGL	1	IMPLND	1	999	EXTNL	PETINP
WDM	2	PREC	ENGL	1	RCHRES	1		EXTNL	PREC
WDM	2	PREC	ENGL	1	RCHRES	3		EXTNL	PREC
WDM	1	EVAP	ENGL	0.5	RCHRES	1		EXTNL	POTEV
WDM	1	EVAP	ENGL	0.7	RCHRES	2		EXTNL	POTEV
WDM	1	EVAP	ENGL	0.5	RCHRES	3		EXTNL	POTEV
WDM	1	EVAP	ENGL	0.7	RCHRES	4		EXTNL	POTEV

END EXT SOURCES

EXT TARGETS

<-Volume->	<-Grp>	<-Member->	<--Mult-->	Tran	<-Volume->	<Member>	Tsys	Tgap	Amd	***	
<Name>	#	<Name>	#	#<-factor-->	strg	<Name>	#	<Name>	tem	strg	strg***
RCHRES	2	HYDR	RO	1	1	WDM	1004	FLOW	ENGL		REPL
RCHRES	2	HYDR	STAGE	1	1	WDM	1005	STAG	ENGL		REPL
RCHRES	1	HYDR	STAGE	1	1	WDM	1006	STAG	ENGL		REPL
RCHRES	1	HYDR	O	1	1	WDM	1007	FLOW	ENGL		REPL
COPY	2	OUTPUT	MEAN	1	1	WDM	702	FLOW	ENGL		REPL
COPY	502	OUTPUT	MEAN	1	1	WDM	802	FLOW	ENGL		REPL
RCHRES	4	HYDR	RO	1	1	WDM	1008	FLOW	ENGL		REPL
RCHRES	4	HYDR	STAGE	1	1	WDM	1009	STAG	ENGL		REPL
RCHRES	3	HYDR	STAGE	1	1	WDM	1010	STAG	ENGL		REPL
RCHRES	3	HYDR	O	1	1	WDM	1011	FLOW	ENGL		REPL
COPY	1	OUTPUT	MEAN	1	1	WDM	701	FLOW	ENGL		REPL
COPY	501	OUTPUT	MEAN	1	1	WDM	801	FLOW	ENGL		REPL

END EXT TARGETS

MASS-LINK

<Volume>	<-Grp>	<-Member->	<--Mult-->	<Target>	<-Grp>	<-Member->	***	
<Name>		<Name>	#	#<-factor-->	<Name>		#	#***
MASS-LINK			2					
PERLND	PWATER	SURO		0.083333	RCHRES	INFLOW	IVOL	
END MASS-LINK			2					
MASS-LINK			3					
PERLND	PWATER	IFWO		0.083333	RCHRES	INFLOW	IVOL	
END MASS-LINK			3					
MASS-LINK			5					
IMPLND	IWATER	SURO		0.083333	RCHRES	INFLOW	IVOL	
END MASS-LINK			5					
MASS-LINK			8					
RCHRES	OFLOW	OVOL	2		RCHRES	INFLOW	IVOL	
END MASS-LINK			8					
MASS-LINK			12					
PERLND	PWATER	SURO		0.083333	COPY	INPUT	MEAN	
END MASS-LINK			12					
MASS-LINK			13					
PERLND	PWATER	IFWO		0.083333	COPY	INPUT	MEAN	
END MASS-LINK			13					
MASS-LINK			15					
IMPLND	IWATER	SURO		0.083333	COPY	INPUT	MEAN	
END MASS-LINK			15					
MASS-LINK			16					
RCHRES	ROFLOW				COPY	INPUT	MEAN	
END MASS-LINK			16					
MASS-LINK			17					
RCHRES	OFLOW	OVOL	1		COPY	INPUT	MEAN	
END MASS-LINK			17					

END MASS-LINK

END RUN

DRAFT

DRAFT

Mitigated HSPF Message File

ERROR/WARNING ID: 238 1

The continuity error reported below is greater than 1 part in 1000 and is therefore considered high.

Did you specify any "special actions"? If so, they could account for it.

Relevant data are:

DATE/TIME: 1976/ 7/31 24: 0

RCHRES : 1

RELERR	STORS	STOR	MATIN	MATDIF
-1.0000	0.00000	0.0000E+00	0.00000	8.9960E-12

Where:

RELERR is the relative error (ERROR/REFVAL).

ERROR is (STOR-STORS) - MATDIF.

REFVAL is the reference value (STORS+MATIN).

STOR is the storage of material in the processing unit (land-segment or reach/reservior) at the end of the present interval.

STORS is the storage of material in the pu at the start of the present printout reporting period.

MATIN is the total inflow of material to the pu during the present printout reporting period.

MATDIF is the net inflow (inflow-outflow) of material to the pu during the present printout reporting period.

ERROR/WARNING ID: 238 1

The continuity error reported below is greater than 1 part in 1000 and is therefore considered high.

Did you specify any "special actions"? If so, they could account for it.

Relevant data are:

DATE/TIME: 1976/ 7/31 24: 0

RCHRES : 3

RELERR	STORS	STOR	MATIN	MATDIF
-1.000E+00	0.00000	0.0000E+00	0.00000	8.7314E-12

Where:

RELERR is the relative error (ERROR/REFVAL).

ERROR is (STOR-STORS) - MATDIF.

REFVAL is the reference value (STORS+MATIN).

STOR is the storage of material in the processing unit (land-segment or reach/reservior) at the end of the present interval.

STORS is the storage of material in the pu at the start of the present printout reporting period.

MATIN is the total inflow of material to the pu during the present printout reporting period.

MATDIF is the net inflow (inflow-outflow) of material to the pu during the present printout reporting period.

Disclaimer

Legal Notice

This program and accompanying documentation are provided 'as-is' without warranty of any kind. The entire risk regarding the performance and results of this program is assumed by End User. Clear Creek Solutions Inc. and the governmental licensee or sublicensees disclaim all warranties, either expressed or implied, including but not limited to implied warranties of program and accompanying documentation. In no event shall Clear Creek Solutions Inc. be liable for any damages whatsoever (including without limitation to damages for loss of business profits, loss of business information, business interruption, and the like) arising out of the use of, or inability to use this program even if Clear Creek Solutions Inc. or their authorized representatives have been advised of the possibility of such damages. Software Copyright © by : Clear Creek Solutions, Inc. 2005-2025; All Rights Reserved.

Clear Creek Solutions, Inc.
6200 Capitol Blvd. Ste F
Olympia, WA. 98501
Toll Free 1(866)943-0304
Local (360)943-0304

www.clearcreeksolutions.com

DRAFT

ATTACHMENT 3

Structural BMP Maintenance Information

This is the cover sheet for Attachment 3.

Indicate which Items are Included behind this cover sheet:

Attachment Sequence	Contents	Checklist
Attachment 3a	Structural BMP Maintenance Thresholds and Actions (Required)	<input checked="" type="checkbox"/> Included See Structural BMP Maintenance Information Checklist on the back of this Attachment cover sheet.
Attachment 3b	Draft Maintenance Agreement (when applicable)	<input checked="" type="checkbox"/> Included <input type="checkbox"/> Not Applicable

E.12 BF-1 Biofiltration



Location: 43rd Street and Logan Avenue, San Diego, California

MS4 Permit Category

Biofiltration

Manual Category

Biofiltration

Applicable Performance Standard

Pollutant Control

Flow Control

Primary Benefits

Treatment

Volume Reduction (Incidental)

Peak Flow Attenuation (Optional)

Description


Biofiltration (Bioretention with underdrain) facilities are vegetated surface water systems that filter water through vegetation, and soil or engineered media prior to discharge via underdrain or overflow to the downstream conveyance system. Bioretention with underdrain facilities are commonly incorporated into the site within parking lot landscaping, along roadsides, and in open spaces. Because these types of facilities have limited or no infiltration, they are typically designed to provide enough hydraulic head to move flows through the underdrain connection to the storm drain system. Treatment is achieved through filtration, sedimentation, sorption, biochemical processes and plant uptake.

Typical bioretention with underdrain components include:


- Inflow distribution mechanisms (e.g, perimeter flow spreader or filter strips)
- Energy dissipation mechanism for concentrated inflows (e.g., splash blocks or riprap)
- Shallow surface ponding for captured flows
- Side slope and basin bottom vegetation selected based on expected climate and ponding depth
- Non-floating mulch layer (Optional)
- Media layer (planting mix or engineered media) capable of supporting vegetation growth
- Filter course layer consisting of aggregate to prevent the migration of fines into uncompacted native soils or the aggregate storage layer
- Aggregate storage layer with underdrain(s)

Appendix E: BMP Design Fact Sheets

- Impermeable liner or uncompacted native soils at the bottom of the facility
- Overflow structure



PLAN
NOT TO SCALE



SECTION A-A'
NOT TO SCALE

Typical plan and Section view of a Biofiltration BMP

Design Adaptations for Project Goals

Biofiltration Treatment BMP for storm water pollutant control. The system is lined or un-lined to provide incidental infiltration, and an underdrain is provided at the bottom to carry away filtered runoff. This configuration is considered to provide biofiltration treatment via flow through the media layer. Storage provided above the underdrain within surface ponding, media, and aggregate storage is considered included in the biofiltration treatment volume. Saturated storage within the aggregate storage layer can be added to this design by raising the underdrain above the bottom of the aggregate storage layer or via an internal weir structure designed to maintain a specific water level elevation.

Integrated storm water flow control and pollutant control configuration. The system can be designed to provide flow rate and duration control by primarily providing increased surface ponding and/or having a deeper aggregate storage layer above the underdrain. This will allow for significant detention storage, which can be controlled via inclusion of an outlet structure at the downstream end of the underdrain.

Design Criteria and Considerations

Bioretention with underdrain must meet the following design criteria. Deviations from the below criteria may be approved at the discretion of the City Engineer if it is determined to be appropriate:

<i>Siting and Design</i>	<i>Intent/Rationale</i>
<input type="checkbox"/> Placement observes geotechnical recommendations regarding potential hazards (e.g., slope stability, landslides, liquefaction zones) and setbacks (e.g., slopes, foundations, utilities).	Must not negatively impact existing site geotechnical concerns.
<input type="checkbox"/> An impermeable liner or other hydraulic restriction layer is included if site constraints indicate that infiltration or lateral flows should not be allowed.	Lining prevents storm water from impacting groundwater and/or sensitive environmental or geotechnical features. Incidental infiltration, when allowable, can aid in pollutant removal and groundwater recharge.

<i>Siting and Design</i>	<i>Intent/Rationale</i>
<input type="checkbox"/> Contributing tributary area shall be ≤ 5 acres (≤ 1 acre preferred).	<p>Bigger BMPs may require additional design features for proper performance.</p> <p>Contributing tributary area greater than 5 acres may be allowed at the discretion of the City Engineer if the following conditions are met: 1) incorporate design features (e.g. flow spreaders) to minimizing short circuiting of flows in the BMP and 2) incorporate additional design features requested by the City Engineer for proper performance of the regional BMP.</p>
<input type="checkbox"/> Finish grade of the facility is $\leq 2\%$.	<p>Flatter surfaces reduce erosion and channelization within the facility.</p>
<i>Surface Ponding</i>	
<input type="checkbox"/> Surface ponding is limited to a 24-hour drawdown time.	<p>Surface ponding limited to 24 hour for plant health.</p>
<input type="checkbox"/> Surface ponding depth is ≥ 6 and ≤ 12 inches.	<p>Surface ponding capacity lowers subsurface storage requirements. Deep surface ponding raises safety concerns.</p> <p>Surface ponding depth greater than 12 inches (for additional pollutant control or surface outlet structures or flow-control orifices) may be allowed at the discretion of the City Engineer if the following conditions are met: 1) surface ponding depth drawdown time is less than 24 hours; and 2) safety issues and fencing requirements are considered (typically ponding greater than 18" will require a fence and/or flatter side slopes) and 3) potential for elevated clogging risk is considered.</p>
<input type="checkbox"/> A minimum of 2 inches of freeboard is provided.	<p>Freeboard provides room for head over overflow structures and minimizes risk of uncontrolled surface discharge.</p>

<i>Siting and Design</i>	<i>Intent/Rationale</i>
<input type="checkbox"/> Side slopes are stabilized with vegetation and are = 3H:1V or shallower.	<p>Gentler side slopes are safer, less prone to erosion, able to establish vegetation more quickly and easier to maintain.</p>
<i>Vegetation</i>	
<input type="checkbox"/> Plantings are suitable for the climate and expected ponding depth. A plant list to aid in selection can be found in Appendix E.20.	<p>Plants suited to the climate and ponding depth are more likely to survive.</p>
<input type="checkbox"/> An irrigation system with a connection to water supply should be provided as needed.	<p>Seasonal irrigation might be needed to keep plants healthy.</p>
<i>Mulch (Mandatory)</i>	
<input type="checkbox"/> A minimum of 3 inches of well-aged, shredded hardwood mulch that has been stockpiled or stored for at least 12 months is provided.	<p>Mulch will suppress weeds and maintain moisture for plant growth. Aging mulch kills pathogens and weed seeds and allows the beneficial microbes to multiply.</p>
<i>Media Layer</i>	
<input type="checkbox"/> Media maintains a minimum filtration rate of 5 in/hr over lifetime of facility. An initial filtration rate of 8 to 12 in/hr is recommended to allow for clogging over time; the initial filtration rate should not exceed 12 inches per hour.	<p>A filtration rate of at least 5 inches per hour allows soil to drain between events. The initial rate should be higher than long term target rate to account for clogging over time. However an excessively high initial rate can have a negative impact on treatment performance, therefore an upper limit is needed.</p>

<i>Siting and Design</i>	<i>Intent/Rationale</i>
<p>Media is a minimum 18 inches deep, meeting either of these two media specifications:</p> <p>City of San Diego Low Impact Development Design Manual (page B-18) (July 2011, unless superseded by more recent edition) or County of San Diego Low Impact Development Handbook: Appendix G -Bioretention Soil Specification (June 2014, unless superseded by more recent edition).</p> <p>Alternatively, for proprietary designs and custom media mixes not meeting the media specifications contained in the City or County LID Manual, the media meets the pollutant treatment performance criteria in Section F.1.</p>	<p>A deep media layer provides additional filtration and supports plants with deeper roots.</p> <p>Standard specifications shall be followed.</p> <p>For non-standard or proprietary designs, compliance with F.1 ensures that adequate treatment performance will be provided.</p>
<p>Media surface area is 3% of contributing area times adjusted runoff factor or greater.</p>	<p>Greater surface area to tributary area ratios: a) maximizes volume retention as required by the MS4 Permit and b) decrease loading rates per square foot and therefore increase longevity.</p> <p>Adjusted runoff factor is to account for site design BMPs implemented upstream of the BMP (such as rain barrels, impervious area dispersion, etc.). Refer to Appendix B.2 guidance.</p> <p>Use Worksheet B.5-1 Line 26 to estimate the minimum surface area required per this criteria.</p>
<p>Where receiving waters are impaired or have a TMDL for nutrients, the system is designed with nutrient sensitive media design (see fact sheet BF-2).</p>	<p>Potential for pollutant export is partly a function of media composition; media design must minimize potential for export of nutrients, particularly where receiving waters are impaired for nutrients.</p>
<i>Filter Course Layer</i>	
<p>A filter course is used to prevent migration of fines through layers of the facility. Filter fabric is not used.</p>	<p>Migration of media can cause clogging of the aggregate storage layer void spaces or subgrade. Filter fabric is more likely to clog.</p>

<i>Siting and Design</i>		<i>Intent/Rationale</i>
<input type="checkbox"/>	Filter course is washed and free of fines.	Washing aggregate will help eliminate fines that could clog the facility and impede infiltration.
<input type="checkbox"/>	Filter course calculations assessing suitability for particle migration prevention have been completed.	Gradation relationship between layers can evaluate factors (e.g., bridging, permeability, and uniformity) to determine if particle sizing is appropriate or if an intermediate layer is needed.
<i>Aggregate Storage Layer</i>		
<input type="checkbox"/>	Class 2 Permeable per Caltrans specification 68-1.025 is recommended for the storage layer. Washed, open-graded crushed rock may be used, however a 4-6 inch washed pea gravel filter course layer at the top of the crushed rock is required.	Washing aggregate will help eliminate fines that could clog the aggregate storage layer void spaces or subgrade.
<input type="checkbox"/>	The depth of aggregate provided (12-inch typical) and storage layer configuration is adequate for providing conveyance for underdrain flows to the outlet structure.	Proper storage layer configuration and underdrain placement will minimize facility drawdown time.
<i>Inflow, Underdrain, and Outflow Structures</i>		
<input type="checkbox"/>	Inflow, underdrains and outflow structures are accessible for inspection and maintenance.	Maintenance will prevent clogging and ensure proper operation of the flow control structures.
<input type="checkbox"/>	Inflow velocities are limited to 3 ft/s or less or use energy dissipation methods. (e.g., riprap, level spreader) for concentrated inflows.	High inflow velocities can cause erosion, scour and/or channeling.
<input type="checkbox"/>	Curb cut inlets are at least 12 inches wide, have a 4-6 inch reveal (drop) and an apron and energy dissipation as needed.	Inlets must not restrict flow and apron prevents blockage from vegetation as it grows in. Energy dissipation prevents erosion.
<input type="checkbox"/>	Underdrain outlet elevation should be a minimum of 3 inches above the bottom elevation of the aggregate storage layer.	A minimal separation from subgrade or the liner lessens the risk of fines entering the underdrain and can improve hydraulic performance by allowing perforations to remain unblocked.
<input type="checkbox"/>	Minimum underdrain diameter is 6 inches.	Smaller diameter underdrains are prone to clogging.

<i>Siting and Design</i>	<i>Intent/Rationale</i>
<input type="checkbox"/> Underdrains are made of slotted, PVC pipe conforming to ASTM D 3034 or equivalent or corrugated, HDPE pipe conforming to AASHTO 252M or equivalent.	Slotted underdrains provide greater intake capacity, clog resistant drainage, and reduced entrance velocity into the pipe, thereby reducing the chances of solids migration.
<input type="checkbox"/> An underdrain cleanout with a minimum 6-inch diameter and lockable cap is placed every 250 to 300 feet as required based on underdrain length.	Properly spaced cleanouts will facilitate underdrain maintenance.
<input type="checkbox"/> Overflow is safely conveyed to a downstream storm drain system or discharge point. Size overflow structure to pass 100-year peak flow for on-line infiltration basins and water quality peak flow for off-line basins.	Planning for overflow lessens the risk of property damage due to flooding.

Conceptual Design and Sizing Approach for Storm Water Pollutant Control Only

To design bioretention with underdrain for storm water pollutant control only (no flow control required), the following steps should be taken:

1. Verify that siting and design criteria have been met, including placement requirements, contributing tributary area, maximum side and finish grade slopes, and the recommended media surface area tributary ratio.
2. Calculate the DCV per Appendix B based on expected site design runoff for tributary areas.
3. Use the sizing worksheet presented in Appendix B.5 to size biofiltration BMPs.

Conceptual Design and Sizing Approach when Storm Water Flow Control is Applicable

Control of flow rates and/or durations will typically require significant surface ponding and/or aggregate storage volumes, and therefore the following steps should be taken prior to determination of storm water pollutant control design. Pre-development and allowable post-project flow rates and durations should be determined as discussed in Chapter 6 of the manual.

1. Verify that siting and design criteria have been met, including placement requirements, contributing tributary area, maximum side and finish grade slopes, and the recommended media surface area tributary ratio.

Appendix E: BMP Design Fact Sheets

2. Iteratively determine the facility footprint area, surface ponding and/or aggregate storage layer depth required to provide detention storage to reduce flow rates and durations to allowable limits. Flow rates and durations can be controlled from detention storage by altering outlet structure orifice size(s) and/or water control levels. Multi-level orifices can be used within an outlet structure to control the full range of flows.
3. If bioretention with underdrain cannot fully provide the flow rate and duration control required by this manual, an upstream or downstream structure with significant storage volume such as an underground vault can be used to provide remaining controls.
4. After bioretention with underdrain has been designed to meet flow control requirements, calculations must be completed to verify if storm water pollutant control requirements to treat the DCV have been met.

E.13 Nutrient Sensitive Media Design

Some studies of bioretention with underdrains have observed export of nutrients, particularly inorganic nitrogen (nitrate and nitrite) and dissolved phosphorus. This has been observed to be a short-lived phenomenon in some studies or a long term issue in some studies. The composition of the soil media, including the chemistry of individual elements is believed to be an important factor in the potential for nutrient export. Organic amendments, often compost, have been identified as the most likely source of nutrient export. The quality and stability of organic amendments can vary widely.

The biofiltration media specifications contained in the County of San Diego Low Impact Development Handbook: Appendix G -Bioretention Soil Specification (June 2014, unless superseded by more recent edition) and the City of San Diego Low Impact Development Design Manual (page B-18) (July 2011, unless superseded by more recent edition) were developed with consideration of the potential for nutrient export. These specifications include criteria for individual component characteristics and quality in order to control the overall quality of the blended mixes. As of the publication of this manual, the June 2014 County of San Diego specifications provide more detail regarding mix design and quality control.

The City and County specifications noted above were developed for general purposes to meet permeability and treatment goals. In cases where the BMP discharges to receiving waters with nutrient impairments or nutrient TMDLs, the biofiltration media should be designed with the specific goal of minimizing the potential for export of nutrients from the media. Therefore, in addition to adhering to the City or County media specifications, the following guidelines should be followed:

1. Select plant palette to minimize plant nutrient needs

A landscape architect or agronomist should be consulted to select a plant palette that minimizes nutrient needs. Utilizing plants with low nutrient needs results in less need to enrich the biofiltration soil mix. If nutrient quantity is then tailored to plants with lower nutrient needs, these plants will generally have less competition from weeds, which typically need higher nutrient content. The following practices are recommended to minimize nutrient needs of the plant palette:

- **Utilize native, drought-tolerant plants and grasses where possible.** Native plants generally have a broader tolerance for nutrient content, and can be longer lived in leaner/lower nutrient soils.
- **Start plants from smaller starts or seed.** Younger plants are generally more tolerant of lower nutrient levels and tend to help develop soil structure as they grow. Given the lower cost of smaller plants, the project should be able to accept a plant mortality rate that is somewhat higher than starting from larger plants and providing high organic content.

2. Minimize excess nutrients in media mix

Once the low-nutrient plant palette is established (item 1), the landscape architect and/or agronomist should be consulted to assist in the design of a biofiltration media to balance the interests of plant establishment, water retention capacity (irrigation demand), and the potential for nutrient export. The following guidelines should be followed:

- **The mix should not exceed the nutrient needs of plants.** In conventional landscape design, the nutrient needs of plants are often exceeded intentionally in order to provide a factor of safety for plant survival. This practice must be avoided in biofiltration media as excess nutrients will increase the chance of export. The mix designer should keep in mind that nutrients can be added later (through mulching, tilling of amendments into the surface), but it is not possible to remove nutrients, once added.
- **The actual nutrient content and organic content of the selected organic amendment source should be determined when specifying mix proportions.** Nutrient content (i.e., C:N ratio; plant extractable nutrients) and organic content (i.e., % organic material) are relatively inexpensive to measure via standard agronomic methods and can provide important information about mix design. If mix design relies on approximate assumption about nutrient/organic content and this is not confirmed with testing (or the results of prior representative testing), it is possible that the mix could contain much more nutrient than intended.
- **Nutrients are better retained in soils with higher cation exchange capacity.** Cation exchange capacity can be increased through selection of organic material with naturally high cation exchange capacity, such as peat or coconut coir pith, and/or selection of inorganic material with high cation exchange capacity such as some sands or engineered minerals (e.g., low P-index sands, zeolites, rhyolites, etc). Including higher cation exchange capacity materials would tend to reduce the net export of nutrients. Natural silty materials also provide cation exchange capacity; however potential impacts to permeability need to be considered.
- **Focus on soil structure as well as nutrient content.** Soil structure is loosely defined as the ability of the soil to conduct and store water and nutrients as well as the degree of aeration of the soil. Soil structure can be more important than nutrient content in plant survival and biologic health of the system. If a good soil structure can be created with very low amounts of organic amendment, plants survivability should still be provided. While soil structure generally develops with time, biofiltration media can be designed to promote earlier development of soil structure. Soil structure is enhanced by the use of amendments with high humus content (as found in well-aged organic material). In addition, soil structure can be enhanced through the use of organic material with a distribution of particle sizes (i.e., a more heterogeneous mix).

- **Consider alternatives to compost.** Compost, by nature, is a material that is continually evolving and decaying. It can be challenging to determine whether tests previously done on a given compost stock are still representative. It can also be challenging to determine how the properties of the compost will change once placed in the media bed. More stable materials such as aged coco coir pith, peat, biochar, shredded bark, and/or other amendments should be considered.

With these considerations, it is anticipated that less than 10 percent organic amendment by volume could be used, while still balancing plant survivability and water retention. If compost is used, designers should strongly consider utilizing less than 10 percent by volume.

3. Design with partial retention and/or internal water storage

An internal water storage zone, as described in Fact Sheet PR-1 is believed to improve retention of nutrients. For lined systems, an internal water storage zone worked by providing a zone that fluctuates between aerobic and anaerobic conditions, resulting in nitrification/denitrification. In soils that will allow infiltration, a partial retention design (PR-1) allows significant volume reduction and can also promote nitrification/denitrification.

Acknowledgment: This fact sheet has been adapted from the Orange County Technical Guidance Document (May 2011). It was originally developed based on input from: Deborah Deets, City of Los Angeles Bureau of Sanitation, Drew Ready, Center for Watershed Health, Rick Fisher, ASLA, City of Los Angeles Bureau of Engineering, Dr. Garn Wallace, Wallace Laboratories, Glen Dake, GDML, and Jason Schmidt, Tree People. The guidance provided herein does not reflect the individual opinions of any individual listed above and should not be cited or otherwise attributed to those listed.

E.14 BF-3 Proprietary Biofiltration Systems

The purpose of this fact sheet is to help explain the potential role of proprietary BMPs in meeting biofiltration requirements, when full retention of the DCV is not feasible. The fact sheet does not describe design criteria like the other fact sheets in this appendix because this information varies by BMP product model.

Criteria for Use of a Proprietary BMP as a Biofiltration BMP

A proprietary BMP may be acceptable as a “biofiltration BMP” under the following conditions:


- (1) The BMP meets the minimum design criteria listed in Appendix F, including the pollutant treatment performance standard in Appendix F.1;
- (2) The BMP is designed and maintained in a manner consistent with its performance certifications (See explanation in Appendix F.2); and
- (3) The BMP is acceptable at the discretion of the City Engineer. The City Engineer has no obligation to accept any proprietary biofiltration BMP.

Guidance for Sizing a Proprietary BMP as a Biofiltration BMP

Proprietary biofiltration BMPs must meet the same sizing guidance as non-proprietary BMPs. Sizing is typically based on capturing and treating 1.50 times the DCV not reliably retained. Guidance for sizing biofiltration BMPs to comply with requirements of this manual is provided in Appendix F.2.

FLOGARD +PLUS®

Replacement & Repair Instruction Manual



FloGard Plus Replacement and Repair

Parts of the FloGard Plus Inlet Filter-

1. FloGard Stainless Steel Support Frame
2. Fossil Rock Absorbent Pouches
3. Liner
4. GeoGrid Support Basket & Cable


* Grate and Basin NOT INCLUDED

Disassembly:

1. Clear FloGard of any existing debris by hand or vacuum.
2. Unclip and remove the Fossil Rock pouches from the inside Liner.
3. Lift the FloGard from the catch basin.
4. Using a slotted screw driver, carefully pry open the metal tabs holding the GeoGrid and Cable in place. Separate the GeoGrid and Liner from the FloGard frame.
5. Unclip the Liner from the inside of the GeoGrid. If you are reusing the Liner, rinse thoroughly with water and inspect for tears. (If torn, mend with stainless steel wire or replace the Liner).
6. Rinse and inspect the GeoGrid Basket and the reinforcing cable. (If torn, mend with stainless steel wire or replace the GeoGrid).
7. Rinse and inspect the Stainless Steel FloGard frame.

Reassembly:

1. Fully expand the GeoGrid Basket and orient to the FloGard frame. Hook cable and GeoGrid to the FloGard frame metal tabs and close the tabs using slotted screwdriver. Move around the FloGard until all tabs are closed and GeoGrid is secured to the Frame.
2. Expand and orient the Liner, locating the clips at each corner and side. Push the Liner through the center of the FloGard frame and secure the clips to the GeoGrid Basket close to the top support cable. Push the Liner to expand inside of the basket.
3. Clip new Fossil Rock Rubberizer pouches to the inside of the Liner.
4. Lower FloGard back into the basin, replace grate.



FLOGARD +PLUS®

OUR MARKETS



BUILDING
STRUCTURES



COMMUNICATIONS



WATER



ENERGY



TRANSPORTATION

Attachment 3b

RECORDING REQUESTED BY:

City of Santee, CA

AFTER RECORDING MAIL TO:

City Clerk
City of Santee
10601 Magnolia Avenue
Santee, CA 92071-1266

ABOVE SPACE FOR RECORDER'S USE

**AGREEMENT TO PERFORM STORM WATER
FACILITIES MAINTENANCE**

NO RECORDATION FEE REQUIRED; THIS DOCUMENT IS
EXEMPT FROM RECORDING FEES PURSUANT
TO CALIFORNIA GOVERNMENT CODE SECTIONS 27383

DOCUMENTARY TRANSFER TAX DUE \$ 0

Assessor's Parcel No. _____

Project No. _____

This AGREEMENT for the maintenance and repair of certain Storm Water Management Facilities is entered into between _____ (hereinafter referred to as "Owner") and the City of Santee (hereinafter referred to as "City") for the benefit of the City, the successors in interest to the City, and the public generally.

RECITALS

A. Owner is the owner of certain real property located in the City of Santee, California, more particularly described in **Exhibit "A"** hereto (hereinafter referred to as the "Property"), and has proposed that the Property be developed as _____ (insert brief description of type of project, e.g., "a 100 unit residential subdivision") _____ in accordance with applications for Tentative Map No. ____

_____, Development Review No. _____, Conditional Use Permit No. _____, Grading Permit No. _____ which are on file with the City. This Agreement is required as a condition of approval for such development as set forth in Resolution Nos. _____.

B. In accordance with the City of Santee's Storm Water Management and Discharge Control Ordinance, (Santee Municipal Code, Chapter 9.06), the City of Santee Subdivision Ordinance, the City of Santee Zoning Ordinance, the City of Santee Grading Ordinance and/or other ordinances or regulations of the City which regulate land development and urban runoff, Owner has prepared and submitted to the City, a site specific Storm Water Quality Management Plan (hereinafter the SWQMP), prepared by _____ and dated _____ as it currently exists or may hereafter be amended and which is on file with the City's Department of Development Services. The SWQMP proposes that storm water runoff from the Property be treated by the use of various storm water management facilities which are identified in the SWQMP as "Best Management Practices" or "BMP's":

The precise location and extent of the BMP's are described and shown in the SWQMP. The SWQMP specifies the frequency, manner, and standards by which the BMP's must be repaired and maintained in order to retain their effectiveness, as set forth in the Operation and Maintenance Section included in the SWMP.

C. The information contained in the SWQMP and the Owner's representation that the BMP's will be maintained pursuant to the SWQMP have been relied upon by City in approving Owner's development applications. It is the purpose of this Agreement to assure that the BMP's are maintained in perpetuity, by creating obligations which are enforceable against the Owner and the Owner's successors in interest in the Property. It is intended that these obligations be enforceable notwithstanding other provisions related to BMP maintenance which are provided by law.

AGREEMENT

NOW, THEREFORE, for consideration of City's approval of the above development applications and the mutual covenants set forth herein, IT IS HEREBY AGREED AS FOLLOWS:

1. **Maintenance of Storm Water Management Facilities.** Owner agrees, for itself and its successors in interest, to all or any portion of the Property, to comply in all respects with the requirements of the Storm Water Management and Discharge Control Ordinance and the SWQMP with regard to the maintenance

of all BMP's as designated in the SWQMP, and in particular agrees to perform, at its sole cost, expense and liability, the following "Maintenance Activities": all inspections, cleaning, repairs, servicing, maintenance and other actions specified in the SWQMP, with respect to all of the BMP's listed at Recital "B" above, at the times and in the manner specified in the SWQMP as it currently exists or may be amended or modified as provided herein. Owner shall initiate, perform and complete all Maintenance Activities at the required time, without request or demand from City or any other agency. Owner further agrees that "Maintenance Activities" shall include replacement or modification of the BMP's in the event that the BMP fails to provide the necessary water quality treatment, it is found that the BMP was not installed correctly, or in the event that the BMP is not functioning as intended. Replacement shall be with an identical type, size and model of BMP, except that:

(a) The City Engineer may authorize substitution of an alternative BMP if he or she determines that it will function as good or better than the failed BMP. The City requires that proposed modifications be submitted for review and approval prior to making any changes in the field, and that the Storm Water Quality Management Plan be revised or amended and resubmitted for approval; and

(b) Pursuant to Section 9.06.200 of the Storm Water Management and Discharge Control Ordinance, any discharge that would result in or contribute to a violation of the City's NPDES Permit and any amendment, revision or re-issuance thereof, either separately considered or when combined with other discharges, is prohibited. Liability for any such discharge shall be the responsibility of the owner(s) causing or responsible for the discharge. Owner agrees that if the BMP, in the judgment of the Director of Development Services, is inappropriate or inadequate to the circumstances and has or may result in a violation of water quality standards, the BMP must be modified or replaced with an upgraded BMP to prevent any actual or potential violation.

2. Annual Inspection and Certification by Owner

Owner agrees to provide documentation of BMP maintenance as required for the City to ensure that all storm water BMPs are properly maintained and are functioning as intended, in compliance with the site specific Storm Water Quality Management Plan. Owner shall provide annual certification that BMPs have been properly maintained for the time period of *September 1 to August 31, each year. This documentation is due to the City prior to September 15th of each year.* Structural BMPs for which annual certification is required includes, but is not limited to: drainage inserts; detention basins; hydrodynamic separators; swales; filters;

bioretention facilities; and Low Impact Development Integrated Management Practices (LID IMPs).

3. **Notices.** Owner further agrees that it shall, prior to transferring ownership of any land on which any of the above BMP's are located, and also prior to transferring ownership of any such BMP, provide clear written notice of the above maintenance obligations associated with that BMP to the transferee. The Storm Water Quality Management Plan and all associated records must also be provided to all subsequent owners upon transfer of property title.

4. **City's Right to Perform Maintenance.** It is agreed that City shall have the right, but not the obligation, to elect to perform any or all of the Maintenance Activities if, in the City's sole judgment, Owner has failed to perform the same. It is recognized and understood that the City makes no representation that it intends to or will perform any of the Maintenance Activities, and any election by the City to perform any of the Maintenance Activities, shall in no way relieve Owner of its continuing maintenance obligations under this agreement. If the City elects to perform any of the Maintenance Activities, it is understood that the City shall be deemed to be acting as the agent of the Owner and said work shall be without warranty or representation by City as to safety or effectiveness, shall be deemed to be accepted by Owner "as is", and shall be covered by Owner's indemnity provisions below.

If the City performs any of the Maintenance Activities, after City has served written notice to the Owner to perform the same, and the Owner has failed to do so within a reasonable time stated in the City's written notice, then Owner shall pay all of the City's costs incurred in performing the Maintenance Activities within sixty days of receipt of an invoice for those costs.

5. **Right of Entry and Inspection by City.** Owner hereby grants to City a perpetual right of entry over, under and across Owner's Property, for purposes of accessing the BMP's and performing inspection of the BMP's or any of the Maintenance Activities related to maintenance of the BMP's. City shall have the right, at any time and without prior notice to Owner, to enter upon any part of said area as may be necessary or convenient for such purposes. Owner shall at all times maintain the Property so as to make the City's access clear and unobstructed. City is required to perform periodic inspection of Structural BMPs. Owner agrees to pay reasonable fees levied by the City on Owners of BMPs for the costs of managing the BMP inspection and maintenance tracking program.

6. **Administration of Agreement for City.** City hereby designates its Department of Development Services with responsibility and authority to administer this Agreement on behalf of City. Any notice or communication related to the

implementation of this Agreement desired or required to be delivered to City shall be addressed to:

Director of Development Services
City of Santee
10601 Magnolia Avenue
Santee, CA 92071

The City Engineer is also granted authority to enter into appropriate amendments to this Agreement on behalf of City, provided that the amendment is consistent with the purposes of this Agreement as set forth above.

7. **Defense and Indemnity.** City shall not be liable for, and Owner and its successors in interest shall defend and indemnify City and the employees and agents of City, against any and all claims, demands, liability, judgments, awards, fines, mechanic's liens or other liens, labor disputes, losses, damages, expenses, charges or costs of any kind or character, including attorneys' fees and court costs (hereinafter collectively referred to as "CLAIMS"), related to this Agreement and arising either directly or indirectly from any act, error, omission or negligence of Owner, Owner's successors, or their contractors, licensees, agents, servants or employees, including, without limitation, claims caused by the concurrent negligent act, error or omission, whether active or passive of City. Owner shall have no obligation, however, to defend or indemnify City from a claim if it is determined by a court of competent jurisdiction that such claim was caused by the sole negligence or willful misconduct of City. Nothing in this Agreement, in the City's approval of the subdivision or other applications or plans and specifications, or inspection of the work, is intended to acknowledge responsibility for any such matter, and City shall have absolutely no responsibility or liability therefore unless otherwise provided by applicable law.

8. **Common Interest Developments.** If the Property is developed as a "Common Interest Development" as defined in Civil Code section 4100 which will include membership in or ownership of an "Association" as defined in Civil Code section 4080, then the following provisions of this Paragraph 7 shall apply during such time as the Property is encumbered by a "Declaration" as defined in Civil Code section 4135, and the Common Area, as "Common Area" is defined in Civil Code section 4095, of the Property is managed and controlled by the Association:

(a) The Association, through its Board of Directors, shall assume full responsibility to perform the MAINTENANCE ACTIVITIES pursuant to this Agreement, and shall undertake all actions and efforts necessary to accomplish the MAINTENANCE ACTIVITIES, including but not limited to, levying regular or special assessments against each member of the

Association sufficient to provide funding for the MAINTENANCE ACTIVITIES, conducting a vote of the membership related to such assessments if required by law. In the event insufficient votes have been obtained to authorize an assessment, the Association shall seek authority from a court of competent jurisdiction for a reduced percentage of affirmative votes necessary to authorize the assessment, re-conducting the vote of the membership in order to obtain the votes necessary to authorize an assessment, and the Association shall take all action authorized by the Declaration or California law to collect delinquent assessments, including but not limited to, the recording and foreclosure of assessment liens.

(b) No provision of the Declaration, nor any other governing document of the Association or grant of authority to its members, shall grant or recognize a right of any member or other person to alter, improve, maintain or repair any of the Property in any manner which would impair the functioning of the BMP's to manage drainage or storm water runoff as described in the SWQMP. In the event of any conflict between the terms of this Agreement and the Declaration or other Association governing documents, the provisions of this Agreement shall prevail.

9. **Agreement Binds Successors and Runs With the Property.** It is understood and agreed that the terms, covenants and conditions herein contained shall constitute covenants running with the land and shall be binding upon the heirs, executors, administrators, successors and assigns of Owner and City, shall be deemed to be for the benefit of all persons owning any interest in the Property (including the interest of City or its successors in the easement granted herein). It is the intent of the parties hereto that this Agreement shall be recorded and shall be binding upon all persons purchasing or otherwise acquiring all or any lot, unit or other portion of the Property, who shall be deemed to have consented to and become bound by all the provisions hereof.

10. **Owner's Continuing Responsibilities Where Work Commenced or Permit Obtained.** Notwithstanding any other provision of this Agreement, no transfer or conveyance of the Property or any portion thereof shall in any way relieve Owner of or otherwise affect Owner's responsibilities for installation or maintenance of BMP's which may have arisen under the ordinances or regulations of City referred to in Recital B above, or other federal, state or local laws, on account of Owner having obtained a permit which creates such obligations or having commenced grading, construction or other land disturbance work.

11. **Amendment and Release.** The terms of this Agreement may be modified only by a written amendment approved and signed by the Director of Development Services and by the Owner or Owner's successor(s) in interest. This

Agreement may be terminated and Owner and the Property released from the covenants set forth herein, by a Release which City may execute if it determines that another mechanism will assure the ongoing maintenance of the BMP's or that it is no longer necessary to assure such maintenance.

12. **Agreement is Intended to Supplement Not Supersede.** This Agreement is intended to supplement and not supersede the requirements of the Chapter 9.06 of the Santee Municipal Code – Storm Water Management and Discharge Control. The requirements listed herein are in addition to the requirements set forth in the Code including Civil Actions and Enforcement Powers established under the Code.

13. **Governing Law and Severability.** This Agreement shall be governed by the laws of the State of California. Venue in any action related to this Agreement shall be in the Superior Court of the State of California, County of San Diego, East County Division. In the event that any of the provisions of this Agreement are held to be unenforceable or invalid by any court of competent jurisdiction, the validity, and enforceability of the remaining provisions shall not be affected thereby.

IN WITNESS WHEREOF, the parties have executed this Agreement on the _____ day of _____, 201__.

CITY OF SANTEE:

By: _____
Melanie Kush
Director of Development Services

OWNERS: _____

By: _____
(sign here)

(print name here)

(title of signatory)

By: _____
(sign here)

(print name here)

(title of signatory)

(All OWNERS must sign)

(Proper notary acknowledgment of execution by OWNER must be attached.)

(President or vice-president **and** secretary or assistant secretary must sign for corporations. If only one officer signs, the corporation must attach a resolution certified by the secretary or assistant secretary under corporate seal empowering that officer to bind the corporation.)

**CITY OF SANTEE
CERTIFICATE OF ACCEPTANCE
FOR
AGREEMENT TO PERFORM STORM WATER FACILITIES MAINTENANCE**

This AGREEMENT by and between the City of Santee, a municipal corporation, and _____ is accepted for recording by the undersigned officers on behalf of the City of Santee pursuant to authority granted by Resolution No. 148-89 of the Santee City Council adopted on August 9, 1989.

Date: _____

By: _____
Melanie Kush
Director of Development Services

CALIFORNIA ALL-PURPOSE ACKNOWLEDGMENT

A notary public or other officer completing this certificate verifies only the identity of the individual who signed the document to which this certificate is attached, and not the truthfulness, accuracy, or validity of that document.

State of California }
County of San Diego }

On _____
(date), before me, Patsy Bell, Santee City Clerk (name and title of the officer), personally appeared _____

(Name(s) of Signer(s)), who proved to me on the basis of satisfactory evidence to be the person(s) whose name(s) is/are subscribed to the within instrument and acknowledged to me that he/she/they executed the same in his/her/their authorized capacity(ies), and that by his/her/their signature(s) on the instrument the person(s), or the entity upon behalf of which the person(s) acted, executed the instrument.


I certify under PENALTY OF PERJURY under the laws of the State of California that the foregoing paragraph is true and correct.

WITNESS my hand and official seal.

Patsy Bell, City Clerk

[Seal]

EXHIBIT 'A'



ATTACHMENT 4

Copy of Plan Sheets Showing Permanent Storm Water BMPs

This is the cover sheet for Attachment 4.

Use this checklist to ensure the required information has been included on the plans:

The plans must identify:

- ☒ Structural BMP(s) with ID numbers matching Form I-6 Summary of PDP Structural BMPs
- ☒ The grading and drainage design shown on the plans must be consistent with the delineation of DMAs shown on the DMA exhibit
- ☒ Details and specifications for construction of structural BMP(s)
- ☒ Signage indicating the location and boundary of structural BMP(s) as required by the [City Engineer]
- ☒ How to access the structural BMP(s) to inspect and perform maintenance
- ☒ Features that are provided to facilitate inspection (e.g., observation ports, cleanouts, silt posts, or other features that allow the inspector to view necessary components of the structural BMP and compare to maintenance thresholds)
- ☒ Manufacturer and part number for proprietary parts of structural BMP(s) when applicable
- ☒ Maintenance thresholds specific to the structural BMP(s), with a location-specific frame of reference (e.g., level of accumulated materials that triggers removal of the materials, to be identified based on viewing marks on silt posts or measured with a survey rod with respect to a fixed benchmark within the BMP)
- ☒ Recommended equipment to perform maintenance
- ☐ When applicable, necessary special training or certification requirements for inspection and maintenance personnel such as confined space entry or hazardous waste management
- ☒ Include landscaping plan sheets showing vegetation requirements for vegetated structural BMP(s)
- ☒ All BMPs must be fully dimensioned on the plans
- ☐ When proprietary BMPs are used, site-specific cross section with outflow, inflow, and model number shall be provided. Photocopies of general brochures are not acceptable.

GENERAL NOTES

1. AN ENCROACHMENT PERMIT SHALL BE OBTAINED FROM THE DEPARTMENT OF DEVELOPMENT SERVICES PRIOR TO THE START OF ANY CONSTRUCTION WITHIN THE LIMITS OF THE PUBLIC RIGHT-OF-WAY INCLUDING BUT NOT LIMITED TO UTILITY CONNECTIONS OR GRADING.
2. ACCEPTANCE OF THESE IMPROVEMENTS AS SHOWN DOES NOT CONSTITUTE APPROVAL OF ANY CONSTRUCTION OUTSIDE THE PROJECT BOUNDARY.
3. ALL UNDERGROUND UTILITIES WITHIN THE STREET RIGHT-OF-WAY SHALL BE CONSTRUCTED, TESTED AND CONNECTED PRIOR TO CONSTRUCTION OF BERMS, CURBS, CROSS-GUTTERS, SIDEWALKS, RETAINING WALLS OR FINAL PAVING.
4. THE EXISTENCE AND LOCATION OF EXISTING UNDERGROUND FACILITIES SHOWN ON THESE PLANS WERE OBTAINED BY A SEARCH OF AVAILABLE RECORD DATA AND FIELD SURVEYS. TO THE BEST OF OUR KNOWLEDGE, EXISTING FACILITIES ARE SHOWN ON THESE PLANS. THE CONTRACTOR IS REQUIRED TO TAKE PRECAUTIONARY MEASURES TO PROTECT ANY EXISTING FACILITIES SHOWN HEREON AND TO MAKE A REASONABLE AND DILIGENT SEARCH TO DETERMINE ANY OTHER WHICH ARE NOT OF RECORD OR NOT SHOWN ON THESE PLANS AND TO PROTECT THE SAME. ANY FACILITIES SO LOCATED SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER AND INCLUDED ON THE AS-BUILT DRAWINGS FOR THIS PROJECT.

5. LOCATION AND ELEVATION OF IMPROVEMENTS TO BE MET BY WORK TO BE DONE SHALL BE CONFIRMED BY FIELD MEASUREMENTS PRIOR TO CONSTRUCTION OF NEW WORK. CONTRACTOR SHALL BE RESPONSIBLE FOR MAKING EXPLORATORY EXCAVATIONS AND LOCATING EXISTING UNDERGROUND FACILITIES SUFFICIENTLY AHEAD OF CONSTRUCTION TO ALLOW FOR REVISIONS TO PLANS IF REVISIONS ARE NECESSARY BECAUSE OF CHANGES IN LINE OR GRADE DUE TO THE ACTUAL LOCATION OF THE EXISTING FACILITIES.

6. THE CONTRACTOR SHALL NOTIFY THE SAN DIEGO GAS AND ELECTRIC COMPANY PRIOR TO STARTING WORK NEAR S.D.G. & E. FACILITIES AND SHALL COORDINATE HIS WORK WITH COMPANY REPRESENTATIVES.

NOTICE: FOR LOCATION OF ELECTRICAL CABLES AND GAS PIPING AND APPURTENANCES CONTACT THE SAN DIEGO GAS AND ELECTRIC COMPANY. TELEPHONE: 811.

7. THE CONTRACTOR SHALL NOTIFY THE SBC PACIFIC BELL TELEPHONE COMPANY PRIOR TO STARTING WORK NEAR PACIFIC BELL FACILITIES AND SHALL COORDINATE HIS WORK WITH COMPANY REPRESENTATIVES.

NOTICE: FOR LOCATION OF CABLES AND APPURTENANCES CONTACT AT&T.

8. THE CONTRACTOR SHALL NOTIFY PADRE DAM MUNICIPAL WATER DISTRICT 48 HRS. PRIOR TO STARTING WORK NEAR PADRE DAM FACILITIES AND SHALL COORDINATE HIS WORK WITH DISTRICT REPRESENTATIVES.

NOTICE: FOR LOCATION OF WATER AND SEWER FACILITIES AND APPURTENANCES CONTACT PADRE DAM. TELEPHONE: 811.

9. THE CONTRACTOR SHALL NOTIFY COX CABLE TV PRIOR TO STARTING WORK NEAR COX CABLE FACILITIES AND SHALL COORDINATE HIS WORK WITH COMPANY REPRESENTATIVES.

NOTICE: FOR LOCATION OF CABLES AND APPURTENANCES CONTACT COX CABLE. TELEPHONE: 811.

10. IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO CONTACT THE UTILITY AGENCIES, ADVISE THEM OF THE PROPOSED IMPROVEMENTS, AND COORDINATE RELOCATIONS, IF NEEDED.

11. POWER SOURCES AND RUNS SERVING STREET LIGHTS SHALL BE SHOWN ON THE "AS-BUILT" IMPROVEMENT DRAWINGS. ALL SOURCES SHALL BE LOCATED WITHIN THE DEDICATED RIGHT-OF-WAY, OR WITHIN EASEMENTS DEDICATED TO THE CITY OF SANTEE.

12. CITY OF SANTEE - INSPECTION REQUIREMENTS:
A. CONTRACTOR SHALL INFORM THE CITY PROJECT ENGINEER 48 HRS. IN ADVANCE OF COMMENCING WORK. PHONE (619) 258-4100 EXT 168.
B. THE CONTRACTOR SHALL GIVE A MINIMUM OF 24 HRS. NOTICE ON REQUESTS FOR INSPECTION. CONTRACTOR SHALL SCHEDULE ALL INSPECTIONS THROUGH SANTEEPORTAL.ORG.
C. ANY WORK PERFORMED WITHOUT THE BENEFIT OF INSPECTION IS SUBJECT TO REMOVAL AND REPLACEMENT AT THE CONTRACTOR'S EXPENSE.

13. THE CONTRACTOR SHALL RELOCATE STREET SIGNS WHEN CONDITIONS SO DICTATE. CONTRACTOR SHALL PROTECT AND ASSUME RESPONSIBILITY FOR ALL OTHER TRAFFIC CONTROL DEVICES. CONTRACTOR SHALL REPLACE TRAFFIC STRIPING, STREET MARKINGS, AND CURB MARKINGS REMOVED OR DAMAGED BY HIS WORK.

14. SIDEWALK JOINT LOCATIONS SHALL BE INSTALLED IN ACCORDANCE WITH REGIONAL STANDARD DRAWING NO. G-9. CURB OR CURB AND GUTTER JOINT LOCATIONS SHALL INCLUDE EXPANSION JOINTS AT CURB RETURNS, ADJACENT TO WALLS AND STRUCTURES AND AT 45 FOOT INTERVALS. WEAKENED PLANE JOINTS SHALL BE PLACED EVERY 15' AND GROOVED JOINTS PLACED EVERY 5'. ALL CONCRETE JOINTS SHALL CONFORM TO REGIONAL STANDARD DRAWING NO. G-10. SIDEWALKS SHALL BE REMOVED TO THE NEAREST JOINT. REFER TO PROJECT SPECIFICATIONS SECTION 32 13 FOR FURTHER INFORMATION.

15. SIDEWALKS AND BIKEPATHS ARE DESIGNED TO HAVE CLEAR UNOBSTRUCTED ACCESS. THESE FACILITIES SHALL BE KEPT CLEAR OF STREET LIGHTS, FIRE HYDRANTS, METER BOXES, TRANSFORMERS, ELECTRICAL PULL BOXES, BLOWOFFS, AIR VENTS OR OTHER SIMILAR OBSTRUCTIONS AT ALL TIMES AND SHALL MAINTAIN 4' MINIMUM CLEARANCE.

16. THE CONTRACTOR IS RESPONSIBLE FOR ENSURING ADEQUACY OF DESIGN AND CONSTRUCTION IN ACCORDANCE WITH THE SPECIFIED GENERAL STANDARDS OF CONSTRUCTION LISTED HEREON, AND TO PROTECT THE WORK AT ALL TIMES DURING THE COURSE OF CONSTRUCTION. FAILED OR DAMAGED WORK SUCH AS CRACKED SIDEWALKS, CURB AND GUTTER, CROSS GUTTERS, DRIVEWAY APRONS AND SO FORTH, SHALL BE REPLACED TO THE NEAREST JOINT OR SCORE LINE IN EACH DIRECTION PRIOR TO PLACEMENT OF THE FINAL PAVEMENT COURSE.

17. THE CONTRACTOR SHALL ENFORCE SAFETY MEASURES AND REGULATIONS INCLUDING THE DESIGN, CONSTRUCTION AND MAINTENANCE FOR CONFORMING TO ALL LOCAL, STATE, AND FEDERAL SAFETY AND HEALTH STANDARDS, LAWS AND REGULATIONS.

18. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE REMOVAL, DISPOSAL, AND COORDINATION OF ALL PRIVATE FACILITIES, FENCES, WALLS, DEBRIS, LANDSCAPING AND IRRIGATION WITHIN THE RIGHT OF WAY WHICH REQUIRES REMOVAL FOR CONSTRUCTION PURPOSES. EACH INDIVIDUAL OWNER EFFECTED SHALL BE NOTIFIED 5 DAYS IN ADVANCE PRIOR TO DEMOLITION OR REMOVAL OF PRIVATE PROPERTY WITHIN THE RIGHT OF WAY.

19. NO WORK OUTSIDE THE RIGHT OF WAY SHALL BE CONDUCTED WITHOUT THE PRIOR WRITTEN APPROVAL OF THE CITY.

20. SOME UTILITIES MAY BE RELOCATED BY THE UTILITY COMPANIES PRIOR TO CONSTRUCTION. THE CONTRACTOR SHALL VERIFY THAT ALL UTILITIES ARE RELOCATED PRIOR TO START OF WORK BY CONTACTING THE CITY.

21. CONTRACTOR SHALL BE PROPERLY LICENSED BY THE TIME THE CONTRACT IS AWARDED, PURSUANT TO THE PROVISIONS OF PUBLIC CONTRACT CODE 20103.5.

STORMWATER POLLUTION PREVENTION NOTES:

1. APPROPRIATE EROSION PREVENTION AND SEDIMENT CONTROL MEASURES WILL BE IMPLEMENTED AT ALL TIMES.
2. THE TOPS OF ALL SLOPES SHALL HAVE A DIKE OR TRENCH TO PREVENT WATER FROM FLOWING OVER THE CRESTS OF SLOPES.
3. CLEAN GRAVEL ONLY WILL BE USED IN GRAVEL BAGS.

4. CATCH BASINS, DESILTING BASINS, GRAVEL BAGS, CHECK DAMS AND STORM DRAIN SYSTEMS SHALL BE INSTALLED TO THE SATISFACTION OF THE CITY ENGINEER. THESE FACILITIES SHALL BE CLEANED ON A REGULAR BASIS, AND KEPT FREE OF SOIL ACCUMULATION.

5. GRAVEL BAG CHECK DAMS SHALL BE PLACED IN UNPAVED AREAS WITH GRADIENTS IN EXCESS OF 2%, IN OTHER GRADED OR EXCAVATED AREAS AS REQUIRED BY THE DEPARTMENT OF DEVELOPMENT SERVICES, AND AT OR NEAR EVERY POINT WHERE CONCENTRATED FLOWS LEAVE THE DEVELOPMENT.

6. GRAVEL BAGS SHALL BE PLACED ON THE UPSTREAM SIDE OF ALL DRAINAGE INLETS TO MINIMIZE SILT BUILDUP IN THE INLETS AND PIPES.

7. THE CONTRACTOR SHALL IMMEDIATELY REPAIR ANY ERODED SLOPES.

8. ROADWAYS AND ENTRANCES TO AND FROM THE SITE SHALL BE SWEEPED ON A REGULAR BASIS TO KEEP THEM FREE OF SOIL ACCUMULATION.

9. CONTRACTOR SHALL HAVE WATER TRUCKS AND EQUIPMENT ON-SITE TO MINIMIZE AIRBORNE DUST CREATED FROM GRADING AND HAULING OPERATIONS OR EXCESSIVE WIND CONDITIONS. WATERING SHALL BE PERFORMED ON A CONTINUOUS BASIS ANY TIME THESE CONDITIONS ARE PRESENT AND AT ALL OTHER TIMES AS DIRECTED BY THE CITY ENGINEER. ADDITIONAL DUST CONTROL MEASURES SHALL BE IMPLEMENTED AS NEEDED.

10. STOCKPILES SHALL BE COVERED AT THE END OF EACH WORKING DAY AND PRIOR TO PREDICTED RAIN EVENTS. ASPHALT SHALL BE STORED ON A LAYER OF PLASTIC SHEETING, OR EQUIVALENT.

11. ALL PORTABLE TOILETS SHALL HAVE A SECONDARY CONTAINMENT AND NOT BE LOCATED NEAR A STORM DRAIN (I.E. CATCH BASIN OR STREET).

12. INACTIVE SLOPES SHALL BE PROTECTED AND STABILIZED WITHIN 10 CALENDAR DAYS OF LAST BEING WORKED, OR ON THE DIRECTION OF THE CITY. ACTIVE SLOPES SHALL BE STABILIZED DURING RAIN.

13. EROSION CONTROL ON SLOPES SHALL BE MITIGATED BY INSTALLING LANDSCAPING AS PER APPROVED LANDSCAPE PLANS AS REQUIRED BY THE DEVELOPMENT REVIEW CONDITIONS..

14. VEHICLE MAINTENANCE, REPAIR AND STORAGE BMPS WILL BE IMPLEMENTED INCLUDING: USE OF DRIP PANS OR EQUIVALENT UNDER VEHICLE STORED OVERNIGHT; DAILY INSPECTION FOR LEAKS AND SPILLS; PROMPT REMOVAL OF SPILLS; AVAILABILITY OF OIL-ABSORBENT SPILL REMOVAL MATERIALS ON SITE.

15. HEAVY EQUIPMENT WILL NOT BE STORED ON THE PUBLIC RIGHT-OF-WAY.

16. TRASH SHALL BE PLACED IN DUMPSTERS. OFFCUTS FROM FRAMING WILL BE STORED APPROPRIATLY AND NOT ALLOWED TO ACCUMULATE IN STOCKPILES AROUND THE SITE.

17. TRASH DUMPSTERS WILL HAVE LIDS. THE LIDS WILL REMAIN CLOSED AND THE DUMPSTERS WILL NOT BE OVERFILLED. ADDITIONAL TRASH PICK UPS SHALL BE MADE AS NECESSARY.

18. LIQUID MATERIALS WILL BE STORED IN CLOSED CONTAINERS IN SECONDARY CONTAINMENT AND UNDER COVER. SOLID MATERIALS WILL BE STORED ON PALLETS AND BE COVERED DURING RAIN.

19. A MATERIALS WASHOUT WILL BE AVAILABLE ONSITE WHENEVER LIQUID MATERIALS ARE USED. THE WASHOUT WILL FULLY CONTAIN THOSE MATERIALS AND THE SURROUNDING AREA SHALL BE KEPT FREE OF SPILLS.

20. DISCHARGE OF POTABLE WATER (SUCH AS FROM POWERWASHING OR FILLING WATER TRUCKS) WILL BE PREVENTED.

21. 125 PERCENT OF THE MATERIALS REQUIRED TO MAINTAIN STORM WATER BMPS SHALL BE PRESENT ON THE SITE AT ALL TIMES.

22. STORMWATER CONTROL MEASURES SHOWN HEREON ARE BEST MANAGEMENT PRACTICES FOR THIS SITE BASED ON THE ANTICIPATED PROGRESS OF THE WORK. ADDITIONAL MEASURES MAY BE REQUIRED AT ANY TIME AT THE DISCRETION OF THE CITY ENGINEER AS THE WORK PROGRESSES. IT IS THE CONTRACTOR'S RESPONSIBILITY TO ENSURE ADEQUATE PROTECTION IS IN PLACE AT ALL TIMES TO PREVENT ANY DISCHARGE OF POLLUTANTS, INCLUDING SEDIMENT, FROM THE EXPOSED SITE AREAS. BMPS WILL BE MAINTAINED UNTIL REMOVAL.

23. SILT FENCING SHALL BE INSTALLED AROUND THE PERIMETER OF ALL GRADING WORK AND THE PERIMETER OF THE IMPROVEMENT AREA.

ENGINEER OF WORK'S DESIGN CERTIFICATION

I, SARAH CURRAN, HEREBY DECLARE THAT I AM THE ENGINEER OF WORK FOR THIS PROJECT, THAT I HAVE EXERCISED RESPONSIBLE CHARGE OVER THE DESIGN AS DEFINED IN SECTION 6703 OF THE BUSINESS AND PROFESSIONS CODE, AND THAT THE DESIGN IS CONSISTENT WITH CURRENT STANDARDS.

I, UNDERSTAND THAT THE CHECK OF PROJECT DRAWINGS AND SPECIFICATIONS BY THE CITY OF SANTEE IS CONFINED TO A REVIEW ONLY AND DOES NOT RELIEVE ME AS THE ENGINEER OF WORK OF MY RESPONSIBILITIES FOR PROJECT DESIGN.

I FURTHER UNDERSTAND THAT UPON APPROVAL OF THESE PLANS BY THE CITY ENGINEER, THE PLANS BECOME THE PROPERTY OF THE CITY OF SANTEE IN ACCORDANCE WITH THE CITY PUBLIC WORKS STANDARDS. AS SUCH, I HEREBY RELINQUISH RIGHT OF OWNERSHIP TO THE CITY TO USE THESE PLANS AS THEY MAY DEEM NECESSARY

SIGNED: Sarka DATE: 04/04/2025
R.C.E. # C69620, MY REGISTRATION EXPIRES ON 06/30/26.

NONRESIDENTIAL FLOOD STATEMENT


I, SARAH CURRAN, A REGISTERED CIVIL ENGINEER HEREBY CERTIFY THAT:

1. THE PAD ELEVATIONS SHOWN ON THIS AS-BUILT GRADING PLAN HAVE BEEN VERIFIED BY ME AND THAT SAID ELEVATIONS ARE AT A MINIMUM OF ONE FOOT ABOVE THE BASE FLOOD ELEVATION AS ESTABLISHED BY THE BASE FLOOD DISCHARGE RATES SET FORTH IN THE FLOOD DAMAGE PREVENTION ORDINANCE - CHAPTER 11.36 OF THE SANTEE MUNICIPAL CODE, OR

2. THE STRUCTURES ON THIS PROPERTY HAVE BEEN FLOOD PROOFED TO OR ABOVE THE BASE FLOOD ELEVATION AS ESTABLISHED BY THE BASE FLOOD DISCHARGE RATES SET FORTH IN THE FLOOD DAMAGE PREVENTION ORDINANCE - CHAPTER 15.52 OF THE SANTEE MUNICIPAL CODE.

SIGNED: Sarka DATE: 04/04/2025
R.C.E. # C69620, MY REGISTRATION EXPIRES ON 06/30/26.

SANTEE COMMUNITY CENTER
(CIP 2018-31)
CITY OF SANTEE



VICINITY MAP
NO SCALE

STANDARD SPECIFICATIONS:

- STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION ("GREENBOOK") 2021 EDITION.
- CITY OF SANTEE DEVELOPMENT SERVICES STANDARDS, LATEST EDITION.
- CALIFORNIA DEPARTMENT OF TRANSPORTATION, "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES" 2014 REVISION 6 EDITION.
- STANDARD SPECIFICATIONS OF THE PADRE DAM MUNICIPAL WATER DISTRICT, WATER AGENCY STANDARDS, W.A.S.

STANDARD DRAWINGS:

- CITY OF SANTEE STANDARD DRAWINGS.
- SAN DIEGO REGIONAL STANDARD DRAWINGS (R.S.D.) AS RECOMMENDED BY THE REGIONAL STANDARDS COMMITTEE, MAINTAINED AND PUBLISHED BY THE SAN DIEGO COUNTY DEPARTMENT OF PUBLIC WORKS, 2018 EDITION.
- STANDARD DRAWINGS OF THE PADRE DAM MUNICIPAL WATER DISTRICT, WATER AGENCY STANDARDS, W.A.S.
- STANDARD PLANS FOR PUBLIC WORKS CONSTRUCTION 2021 EDITION.

LEGAL DESCRIPTION:

SITE ADDRESS: 10129 RIVERWALK DRIVE
SANTEE, CA 92071

APN: 381-051-14-00

ALL THOSE PORTIONS OF BLOCKS 2 AND 3 OF THE SUBDIVISION OF LOTS "H" AND "O", PER MAP NO. 817, RECORDED APRIL 2, 1896.

SHEET INDEX:

SHEET NO.	DESCRIPTION
C1.0	TITLE SHEET AND GENERAL NOTES
C1.1	EXISTING CONDITIONS PLAN
C1.2	DEMOLITION PLAN
C1.3	GRADING AND PAVING PLAN
C1.4	PARKING LOT GRADING AND PAVING PLAN
C1.5	HORIZONTAL CONTROL PLAN
C1.6	PARKING LOT HORIZONTAL CONTROL PLAN
C1.7	HORIZONTAL CONTROL PLAN TABLES
C1.8	TRAFFIC SIGNAGE AND STRIPING PLAN
C1.9	CIVIL UTILITY PLAN
C1.10	CIVIL DETAILS
C1.11	CIVIL DETAILS
C1.12	EROSION CONTROL PLAN

BENCHMARK:

THE BENCHMARK USED FOR THIS SURVEY IS GPS STATION "FP7" PER RECORD OF SURVEY 20986, BEING A STANDARD STREET SURVEY MONUMENT, M-10, WITH PUNCH ONLY, LOCATED ON A 5.00' OFFSET SOUTH ALONG THE CENTERLINE OF COTTONWOOD AVENUE FROM THE CENTERLINE INTERSECTION OF PALM GLEN DRIVE AND COTTONWOOD AVENUE AS DERIVED FROM MAP NO. 7349.

ELEVATION: 355.96 FEET FROM SAID RECORD OF SURVEY 20986. FOR THE PURPOSE OF THIS SURVEY IT IS 356.05 FEET.

DATUM: NAVD88

CITY RESUBMITTAL
03/05/2025


ABBREVIATIONS:

AC	ASPHALT CONCRETE
C&G	CURB AND GUTTER
CB	CATCH BASIN
CBM	CONSTRUCTION BENCH MARK
EX	EXISTING
FG	FINISH GRADE
FL	FLOW LINE
LT	LEFT
MH	MANHOLE
OHE	OVER HEAD ELECTRIC
PCC	PORTLAND CEMENT CONCRETE
PP	POWER POLE
RCB	REINFORCED CONCRETE BOX
RCP	REINFORCED CONCRETE PIPE
RT	RIGHT
ROW	RIGHT OF WAY
RW	RECYCLED WATER
SDRSD	SAN DIEGO COUNTY REGIONAL STANDARD DRAWINGS
SDMH	STORM DRAIN MANHOLE
SL	STREET LIGHT
TC	TOP OF CURB
TF	TOP OF FOOTING
X-ING	CROSSING

LEGEND


ITEM (RSD)	SYMBOL
RIGHT-OF-WAY	ROW
EXIST TELEPHONE	T
EXIST CABLE TV	CATV
EXIST ELECTRIC.....	E
EXIST SANITARY SEWER.....	SS
EXIST WATER.....	W
EXIST GAS.....	G
EXIST RECYCLED WATER.....	RW
EXIST CHAIN LINK FENCE.....	X X X
EXIST SIDEWALK	4" 4" 4"
EXIST CATCH BASIN.....	CB
EXIST POWER POLE.....	Opp
EXIST CURB AND GUTTER	SD SD
EXIST STORM DRAIN.....	SD
EXIST SEWER SERVICE	S
EXIST WATER SERVICE	W
EXIST BLOWOFF	B
EXIST RECYCLED WATER SERVICE	RW
CURB AND GUTTER (G-2).....	G-2
LODGE POLE FENCE (2 RAIL).....	● ● ●
CHAIN LINK FENCE (M-6).....	X X X
REMOVABLE BOLLARD.....	●
DG SURFACE.....	DG
6" CONCRETE MOW CURB.....	6" C
CONSTRUCTION NOTE.....	①

* ALL DIMENSIONS IN FEET UNLESS OTHERWISE SHOWN



CONSTRUCTION RECORD	REFERENCES	DATE	BY	REVISIONS	ACPTD	BENCH MARK	SCALE	DESIGNED BY	DRAWN BY	CHECKED BY	REVIEWED	CITY OF SANTEE	DEPARTMENT OF DEVELOPMENT SERVICES	CITY W.O. NO.	DRAWING NO.
CONTRACTOR						THE BENCHMARK USED FOR THIS SURVEY IS GPS STATION "FP7" PER RECORD OF SURVEY 20986, BEING A STANDARD STREET SURVEY MONUMENT, M-10 WITH PUNCH ONLY. ELEVATION: 355.96 FEET FROM RDS 20986, FOR THE PURPOSES OF THIS SURVEY IT IS 356.05 FEET.	HORIZ: AS SHOW	SKC	GPY	EH		IMPROVEMENT PLANS FOR:	SANTEE COMMUNITY CENTER	CIP 2018-31	C1.0
INSPECTOR						DATUM: NAVD88	VERT: AS SHOW	PLANS PREPARED UNDER THE SUPERVISION OF SARAH CURRAN		DATE 04/04/2025	BY		TITLE SHEET AND GENERAL NOTES		SHEET X OF X
DATE COMPLETED								RCE NO. C69620		EXPIRES 06/30/2026	PROJECT ENGINEER				

Plotted - 3/4/2025 2:24:57 PM :: Saved - 9/12/2024 8:10:58 AM :: S:\SHMC010100\CADD\Design\Sheets\SHMC010100-EX.DWG :: chase.lawson



CONSTRUCTION RECORD	REFERENCES	DATE	BY	REVISIONS	ACPTD
CONTRACTOR					
INSPECTOR					
DATE COMPLETED					

BENCH MARK
THE BENCHMARK USED FOR THIS SURVEY IS GPS STATION "EP7" PER RECORD OF SURVEY 20986, BEING A STANDARD STREET SURVEY MONUMENT, M-10 WITH PUNCH ONLY. ELEVATION: 355.96 FEET FROM RDS 20986, FOR THE PURPOSES OF THIS SURVEY IT IS 356.05 FEET.
DATUM: NAVD88

SCALE
HORIZ: AS SHOW
VERT: AS SHOW

DESIGNED BY	DRAWN BY	CHECKED BY
SKC	GPY	EH
PLANS PREPARED UNDER THE SUPERVISION OF		
SARAH CURRAN		
RCE NO.	C69620	DATE 04/04/2025
		EXPIRES 06/30/2026

REVIEWED _____
BY _____ PROJECT ENGINEER

CITY OF SANTEE
IMPROVEMENT PLANS FOR:

DEPARTMENT OF DEVELOPMENT SERVICES
SANTEE COMMUNITY CENTER
EXISTING CONDITIONS PLAN

CITY W.O. NO.
CIP 2018-31


DRAWING NO.
C1.1
SHEET X OF X

LEGEND AND ABBREVIATIONS

AC	ASPHALTIC CONCRETE
AD	AREA DRAIN
BFP	BACKFLOW PREVENTION ASSEMBLY
BW	BOTTOM OF WALL
CATV	CABLE TELEVISION
CMU	CONCRETE MASONRY UNIT
C/O	SANITARY SEWER CLEANOUT
CONC	CONCRETE/CONCRETE SPOT EL.
CP	CONCRETE PEDESTAL
CPAD	CONCRETE PAD
CR	COMMUNICATION RISER
DI	DROP INLET
DIA	DIAMETER
DECID	DECIDUOUS
ECCB	ELECTRIC CABINET
EC	EDGE OF CONCRETE
EL	ELEVATION
ELEC	ELECTRIC
EUC	EUCALYPTUS
EVC	ELECTRIC VEHICLE CHARGING STATION
EVT	ELECTRIC VAULT
EP	EDGE OF PAVEMENT
FDC	FIRE DEPARTMENT CONNECTION
FF	FINISHED FLOOR
FHV	FIRE HYDRANT VALVE
FL	FLOWLINE
GB	GRADE BREAK
GRD	GROUND
GR	GROUNDING ROD
HCR	HANDICAP RAMP
HDCP	HANDICAP
IR	IRRIGATION CONTROL VALVE
OHC	OVERHANG
LS	LANDSCAPE
RD	3" PVC ROOF DRAIN
(N)	NORTH
(S)	SOUTH
SW	SIDEWALK
TC	TOP OF CURB
TOP	TOP OF SLOPE
TRW	TREE WELL
TW	TOP OF WALL
UD	SIDEWALK UNDERDRAIN
VG	VALLEY GUTTER
BL	BOLLARD
FH	FIRE HYDRANT
GV	GAS VALVE
ICV	IRRIGATION CONTROL VALVE
LP	LIGHT ON POLE/LANDSCAPE LIGHT
PED	PEDESTAL
SN	ROAD/TRAFFIC SIGN
WTVL	WATER VALVE
CB	CATCH BASIN
SDMH/CO	STORM DRAIN MANHOLE & CLEANOUT
SMH	SEWER MANHOLE
CI	CURB INLET
RIP RAP	RIP RAP
DG WALK	DG WALK
CONCRETE	CONCRETE
RIVER BED	RIVER BED
GRAVEL PARKING LOT	GRAVEL PARKING LOT
WALL	WALL
TOP OF SLOPE	TOP OF SLOPE
TOE OF SLOPE	TOE OF SLOPE
TOP FACE OF CURB OR EDGE OF PAVEMENT	TOP FACE OF CURB OR EDGE OF PAVEMENT
FLOWLINE OF SWALE	FLOWLINE OF SWALE
CHAINLINK FENCE	CHAINLINK FENCE
WOOD FENCE	WOOD FENCE
WROUGHT IRON FENCE	WROUGHT IRON FENCE
UNDERGROUND COMMUNICATION	UNDERGROUND COMMUNICATION
UNDERGROUND ELECTRIC	UNDERGROUND ELECTRIC
UNDERGROUND GAS	UNDERGROUND GAS
UNDERGROUND DOMESTIC WATER	UNDERGROUND DOMESTIC WATER
UNDERGROUND RECLAIM WATER	UNDERGROUND RECLAIM WATER
UNDERGROUND SANITARY SEWER	UNDERGROUND SANITARY SEWER
UNDERGROUND STORM DRAIN	UNDERGROUND STORM DRAIN
EXISTING CONTOUR LINE	EXISTING CONTOUR LINE
TREE	TREE


GENERAL NOTES

- BASE CONDITIONS SHOWN HEREON AS EXISTING CONDITIONS ARE BASED ON A SURVEY DATED MARCH 23, 2022, PREPARED BY PSOMAS, AND PUBLICLY AVAILABLE RECORD AS-BUILT DRAWINGS.
- SEE THE GEOTECHNICAL INVESTIGATION REPORT, SANTEE COMMUNITY CENTER, DATED MARCH 18, 2022, PREPARED BY GROUP DELTA CONSULTANTS, INC.. CONTRACTOR SHALL BE RESPONSIBLE TO REVIEW AND COMPLY WITH RECOMMENDATIONS PROVIDED IN THE GEOTECHNICAL REPORT.



IMPROVEMENT PLANS - SANTEE COMMUNITY CENTER, CIP 2018-31

Plotted - 3/4/2025 2:25:43 PM :: Saved - 9/12/2024 9:49:58 AM :: S:\HMC010100\CADD\Design\Sheets\HMC010100-DM.DWG :: chase.lawson



LEGEND

- REMOVE EXIST ASPHALT PAVEMENT AND AGGREGATE BASE
- REMOVE EXIST CONCRETE PAVEMENT AND PERIMETER CURB/GUTTERS/SIDEWALK (WHERE OCCURS)
- REMOVE EXIST LANDSCAPING AND IRRIGATION
- REMOVE EXIST CONCRETE MOW CURB
- SAWCUT LINE
- REMOVE EXIST FENCE/GATE
- EXISTING NATURAL SWALE
- APPROXIMATE LIMITS OF WORK

DEMOLITION NOTES

- REMOVE AND DISPOSE GATE AND GATE POSTS.
- REMOVE AND DISPOSE CONCRETE CURB OR CURB & GUTTER.
- REMOVE AND DISPOSE AC PAVEMENT AND BASE, FULL DEPTH, WHEEL STOPS, AND ADA PARKING SIGNAGE.
- PROTECT CURB & GUTTER IN PLACE.
- PROTECT DRAINAGE STRUCTURE IN PLACE.
- PROTECT SEWER MANHOLE IN PLACE.
- PROTECT SEWER LINE IN PLACE.
- PROTECT FENCE IN PLACE.
- PROTECT STORM DRAIN PIPE IN PLACE.
- REMOVE CONCRETE PAVEMENT & SIDEWALK.
- NOT USED.
- REFER TO LANDSCAPE SHEETS L2, 10 AND L2.11 FOR IRRIGATION DEMOLITION AND DISPOSE.
- PROTECT IN PLACE BACK FLOW PREVENTER AND FIRE PIPE CONNECTION.
- REMOVE AND DISPOSE TREE AND TRUNKS.
- REMOVE AND DISPOSE OF TRASH ENCLOSURE AND FOOTINGS.
- PROTECT SIGN.
- PROTECT REMOVABLE BOLLARD IN PLACE.
- PROTECT TREE.
- REMOVE & DISPOSE SIGN.
- PROTECT MOW CURB AND DG WALK.
- EXISTING YMCA WATER METERS (2) TO BE REMOVED BY PADRE DAM MUNICIPAL WATER DISTRICT AFTER RELOCATION INSTALL (SEE UTILITIES PLAN). BACKFLOW PREVENTERS (2) TO BE REMOVED BY CONTRACTOR AFTER RELOCATION INSTALL (SEE UTILITIES PLAN).
- REMOVE AND DISPOSE WOOD STAIRS.
- PROTECT IN PLACE PEDESTRIAN BRIDGE.
- REMOVE GRASS FIELD AND AGGREGATE BASE.
- REMOVE LIGHT STANDARD POLE FOOTING AND PULL BOX
- PROTECT FIRE HYDRANT IN PLACE.
- PROTECT UNDERGROUND ELECTRICAL PULL BOX.
- REMOVE AND DISPOSE MOW CURB.
- PROTECT EXIST CURBS, STRIPES, ASPHALT CONCRETE, PLANTERS, IRRIGATION, LANDSCAPING, ELECTRICAL AND LIGHTING IN PLACE.
- REMOVE AND DISPOSE EXISTING CATCH BASIN.
- PROTECT IN PLACE EXISTING MAIL BOX.
- REMOVE AND DISPOSE EXISTING TREES AND ROOT BARRIERS IN ISLAND PLANTERS.
- REMOVE AND DISPOSE PVC STORM DRAIN.

GENERAL DEMOLITION NOTES

- PRIOR TO ANY DEMOLITION OR EXCAVATION FOR THIS CONTRACT CONTRACTOR SHALL VERIFY LOCATION OF ALL UNDERGROUND UTILITIES. THE EXISTENCE AND LOCATION OF ANY UNDERGROUND UTILITY PIPES OR STRUCTURES SHOWN ON THESE PLANS HAS BEEN OBTAINED FROM AVAILABLE RECORDS ONLY AND MAY NOT REFLECT ALL EXISTING UTILITIES.
- LOCATION OF ALL EXISTING UTILITIES SHALL BE CONFIRMED BY THE CONTRACTOR PRIOR TO CONSTRUCTION OF WORK. ACCURATE VERIFICATION AS TO SIZE, LOCATION AND DEPTH OF EXISTING UNDERGROUND SERVICES SHALL BE THE CONTRACTORS RESPONSIBILITY.
- CONTRACTOR IS REQUIRED TO TAKE PRECAUTIONARY MEASURES TO PROTECT THE UTILITY LINES SHOWN HEREON AND ANY OTHER EXISTING LINES NOT OF RECORD OR NOT SHOWN ON THESE PLANS.
- THE CONTRACTOR SHALL NOTIFY ALL AFFECTED UTILITY AGENCIES PRIOR TO STARTING HIS WORK WITH UTILITY REPRESENTATIVES. FOR LOCATION OF UNDERGROUND UTILITIES AND APPURTENANCES, CONTACT "UNDERGROUND SERVICE ALERT" AT 811.
- EXIST ABANDONED UNDERGROUND UTILITIES TO BE REMOVED AND DISPOSED.
- WITHIN DEMOLITION AREA, REMOVE ALL TREES, ROOTS, SHRUBS, STRUCTURES, FENCING, STRUCTURAL FOUNDATIONS, PAVED PATHS AND STAIRS, CONCRETE PAVEMENT, ASPHALT PAVEMENT, CURBS, GUTTERS, GROUND COVER, AND ANY EXISTING IMPROVEMENTS NOT SPECIFICALLY NOTED TO REMAIN. REMOVE ALL MISCELLANEOUS TRASH FROM SITE.
- UNLESS OTHERWISE NOTED, ALL EXISTING UNDERGROUND UTILITIES AND ASSOCIATED STRUCTURES SHALL BE PROTECTED IN PLACE.
- REFERENCE MECHANICAL, ELECTRICAL AND TELECOMMUNICATION PLANS FOR DEMOLITION AND INSTALLATION OF M, E, & T UTILITIES AND STRUCTURES.
- REFERENCE LANDSCAPE PLANS FOR TREE PROTECTION AND REMOVALS.
- REFERENCE LANDSCAPE PLANS FOR DEMOLITION AND INSTALLATION OF IRRIGATION LINES.
- SHOULD ANY EXISTING UTILITY NOT SHOWN HEREON BE ENCOUNTERED, THE CONTRACTOR SHALL NOTIFY THE OWNER AND ENGINEER PRIOR TO DEMOLITION OF SUCH UTILITY.
- CONTRACTOR SHALL USE A 3RD PARTY UNDERGROUND LOCATION SERVICE TO DETERMINE THE LOCATION OF ALL ELECTRICAL, WATER, SEWER, AND IRRIGATION LINES.

811
Call 2 Full Working Days in Advance

DIGALERT

GRAPHIC SCALE
1 INCH = 40 FEET

40' 0' 40' 80' 120'


PROFESSIONAL SEAL
SARAH K. CURRAN
CIVIL
STATE OF CALIFORNIA
No. 006670

CONSTRUCTION RECORD	REFERENCES	DATE	BY	REVISIONS	ACPTD
CONTRACTOR					
INSPECTOR					
DATE COMPLETED					

SCALE	DESIGNED BY	DRAWN BY	CHECKED BY	REVIEWED
HORIZ: AS SHOW VERT: AS SHOW	SKC	GPY	EH	
	PLANS PREPARED UNDER THE SUPERVISION OF SARAH CURRAN RCE NO. C69620			
		DATE 04/04/2025 EXPIRES 06/30/2026		BY PROJECT ENGINEER

CITY OF SANTEE	DEPARTMENT OF DEVELOPMENT SERVICES	CITY W.O. NO.	DRAWING NO.
IMPROVEMENT PLANS FOR:	SANTEE COMMUNITY CENTER	CIP 2018-31	C1.2
	DEMOLITION PLAN		SHEET X OF X

IMPROVEMENT PLANS - SANTEE COMMUNITY CENTER, CIP 2018-31





- LEGEND**
- CURB RAMP
 - CONCRETE CROSS GUTTER/RIBBON GUTTER
 - CATCH BASIN
 - CLEANOUT
 - SLOPE ARROW
 - 500 NEW CONTOUR
 - x 505.50 NEW SPOT ELEVATION
 - 500 EXISTING CONTOUR (PER AERIAL SURVEY, ACCURACY OF ± 0.5')
 - 000.00 EXISTING ELEVATION (PER FIELD SURVEY, ACCURACY OF ± 0.1')
 - x 500.0 EXISTING SPOT ELEVATION (PER AERIAL SURVEY, ACCURACY OF ± 0.5')
 - 740 NEW CONTOUR LINE
 - DAYLIGHT LINE
 - SAWCUT LINE
 - RIDGE
 - GRADE BREAK
 - CONCRETE CURB
 - CONCRETE CURB AND GUTTER
 - LIMITS OF WORK
 - CONCRETE VEHICULAR PAVEMENT
 - AC PAVEMENT
 - CONCRETE SIDEWALK

- GRADING NOTES**
1. CONSTRUCT CONCRETE CURB PER SDRSD G-01 6" CURB FACE UNLESS NOTED OTHERWISE.
 2. CONSTRUCT CONCRETE CURB AND GUTTER PER SDRSD G-02 8" CURB FACE TYPE H.
 3. CONSTRUCT TYPE A CURB RAMP PER SDRSD G-27.
 4. CONSTRUCT CROSS GUTTER PER SDRSD G-12 WIDTH PER PLANS.
 5. CONSTRUCT CONCRETE SIDEWALK PER DETAIL 4 SHEET C1.10.
 6. CONSTRUCT CONCRETE VEHICULAR PAVEMENT PER DETAIL 3 SHEET C1.10.
 7. CONSTRUCT ASPHALT CONCRETE PAVEMENT PER DETAIL 2 SHEET C1.10.
 8. CONSTRUCT FENCE PER LANDSCAPE PLAN.
 9. CONSTRUCT CURB CUT WITH RIP RAP APRON PER DETAIL 2 SHEET C1.11.
 10. NOT USED.
 11. CONSTRUCT CURBSIDE GRATED CATCH BASIN PER SPPWC STD 303. SINGLE GRATE V=5.77' (FSD) WITH CASE F LOCAL DEPRESSION AT CATCH BASIN PER SPPWC STD 313.4.
 12. CONSTRUCT TRASH ENCLOSURE PER ARCHITECT PLAN.
 13. CONSTRUCT SEAT WALL PER LANDSCAPE PLAN.
 14. CONSTRUCT BIOFILTRATION BASIN PER DETAIL 1 SHEET C1.11.
 15. EXISTING PEDESTRIAN BRIDGE TO REMAIN.
 16. CONSTRUCT CONCRETE DRIVEWAY (ALLEY TYPE) PER SDRSD G-14E.
 17. CONSTRUCT 8" CURB WITH SIDEWALK UNDERDRAIN PER SDRSD D-27.
 18. CONSTRUCT 12" CURB CUT PER DETAIL 2 ON SHEET 1 SHEET C1.11.
 19. CONSTRUCT TYPE A 6" ROLLED CURB ALONG CONCRETE PAVEMENT ACCESS PER SDRSD G-4A WITH 8" LONG CURB TRANSITION ON EACH END PER SDRSD G-4AB.
 20. INSTALL DEMOUNTABLE POST PER SDRSD M-16.
 21. CONSTRUCT TYPE D-3 CURB RAMP PER SDRSD G-31.
 22. CONSTRUCT TYPE D-2 CURB PAMP PER SDRSD G-31.
 23. CONSTRUCT COBBLE ENERGY DISSIPATION PER DETAIL 4 ON SHEET C1.11.
 24. CONSTRUCT SIDEWALK UNDERDRAIN PER DETAIL 5 ON SHEET C1.11.
 25. ELECTRICAL EQUIPMENT. SEE MEP PLANS FOR EQUIPMENT AND PAD CONSTRUCTION DETAILS.

- GENERAL GRADING NOTES**
1. CONTRACTOR SHALL PROTECT IN PLACE OR ADJUST WHERE NECESSARY ALL EXISTING UTILITY LINES, WHETHER SHOWN OR NOT SHOWN ON THESE PLANS, THAT LAY WITHIN THE LIMITS OF THE NEW CONSTRUCTION, AND ARE NOT SPECIFICALLY MARKED TO BE REMOVED OR ABANDONED.
 2. FINAL MANHOLE, VALVE BOXES AND VAULTS RIM ELEVATIONS SHALL BE ADJUSTED TO MEET FINAL GRADES.
 3. CONTRACTOR TO VERIFY ALL EXISTING UTILITIES THAT ARE IN CONFLICT WITH THE PROJECT PRIOR TO THE START OF CONSTRUCTION AND NOTIFY THE ENGINEER OF RECORD OF ANY FOUND CONFLICTS. CONTRACTOR SHALL USE A 3RD PARTY UNDERGROUND UTILITY SERVICE TO DETERMINE THE LOCATION OF ALL ELECTRICAL, WATER, SEWER, AND IRRIGATION LINES.
 4. THE LOCATION AND PROTECTION OF ALL UTILITIES IS THE RESPONSIBILITY OF THE CONTRACTOR.
 5. JOIN ELEVATIONS SHOW APPROXIMATE. NEW CONCRETE JOINS SHALL MATCH EXISTING ELEVATIONS.
 6. BUILDING PAD PREPARATION REFERENCE SHEET S0.01 FOR SOIL (GROUND) IMPROVEMENTS AND SHEET S3.02 FOR ADDITIONAL REQUIRED EXCAVATION AND CERTIFIED FILL BENEATH BUILDING.

- SPECIAL GEOTECHNICAL NOTES**
1. GROUND IMPROVEMENT SPECIALTY CONTRACTOR SHALL SUBMIT PLANS AND DESIGN CALCULATIONS PRIOR TO CONSTRUCTION FOR APPROVAL. THE PLANS SHALL BE REVIEWED BY THE GEOTECHNICAL ENGINEER OR RECORD FOR CONCURRENCE THAT THEY MEET THE DESIGN INTENT NOTED IN THE PROJECT GEOTECHNICAL REPORT. THE GROUND IMPROVEMENT DESIGN PACKAGE SHALL INCLUDE QUALITY CONTROL PROCEDURES TO CONFIRM THE DESIGN BEARING CAPACITY AND LIQUEFACTION POTENTIAL MEET THE DESIGN INTENT. THE QUALITY CONTROL PROCEDURES SHALL INCLUDE AN INDICATOR MODULUS TEST (MT) PROGRAM AND A GROUND IMPROVEMENT TEST SECTION TO INDICATE PRE- AND POST- IMPROVEMENT BORINGS AND/OR CPTS ALONG WITH LIQUEFACTION ANALYSIS TO INDICATE THAT THE POST-GROUND IMPROVEMENT MEETS THE DESIGN INTENT.
 2. ALL GRADING WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE REQUIREMENTS AND RECOMMENDATIONS CONTAINED IN THE PROJECT SPECIFIC GEOTECHNICAL REPORT, PROJECT NUMBER IR786, BY GROUP DELTA, DATED JUNE 15, 2022.




Plotted - 3/4/2025 2:27:00 PM :: Saved - 2/24/2025 4:54:02 PM :: S:\HMC\01000\CADD\Design\Sheets\HMC010100-0P.DWG :: chasae.lawson

IMPROVEMENT PLANS - SANTEE COMMUNITY CENTER, CIP 2018-31

CONSTRUCTION RECORD					REFERENCES	DATE	BY	REVISIONS	ACPTD	BENCH MARK	SCALE	DESIGNED BY	DRAWN BY	CHECKED BY	REVIEWED	CITY OF SANTEE	DEPARTMENT OF DEVELOPMENT SERVICES	CITY W.O. NO.	DRAWING NO.
CONTRACTOR	INSPECTOR	DATE COMPLETED																	
										THE BENCHMARK USED FOR THIS SURVEY IS GPS STATION "EP7" PER RECORD OF SURVEY 20086, BEING A STANDARD STREET SURVEY MONUMENT, M-10 WITH PUNCH ONLY. ELEVATION: 355.96 FEET FROM ROS 20086. FOR THE PURPOSES OF THIS SURVEY IT IS 356.05 FEET. DATUM: NAVD83	HORIZ: AS SHOW VERT: AS SHOW	SKC	GPY	EH		IMPROVEMENT PLANS FOR:	SANTEE COMMUNITY CENTER	CIP 2018-31	C1.3
												PLANS PREPARED UNDER THE SUPERVISION OF SARAH CURRAN		DATE 04/04/2025	BY PROJECT ENGINEER				SHEET X OF X
												RCE NO. C69620		EXPIRES 06/30/2026					

Plotted - 3/4/2025 2:28:14 PM :: Saved - 2/24/2025 5:00:20 PM :: S:\HMC010100\CADD\Design\Sheets\HMC010100-CP PARKING LOT.DWG :: chase.lawson



CONSTRUCTION RECORD	REFERENCES	DATE	BY	REVISIONS	ACPTD
CONTRACTOR					
INSPECTOR					
DATE COMPLETED					


BENCH MARK THE BENCHMARK USED FOR THIS SURVEY IS GPS STATION "EP7" PER RECORD OF SURVEY 20986, BEING A STANDARD STREET SURVEY MONUMENT, M-10 WITH PUNCH ONLY. ELEVATION: 355.96 FEET FROM ROS 20986. FOR THE PURPOSES OF THIS SURVEY IT IS 356.05 FEET. DATUM: NAVD83

SCALE
HORIZ: AS SHOW
VERT: AS SHOW

DESIGNED BY SKC	DRAWN BY GPY	CHECKED BY EH
PLANS PREPARED UNDER THE SUPERVISION OF SARAH CURRAN		
RCE NO. C69620	DATE 04/04/2025	EXPIRES 06/30/2026

REVIEWED	BY
	PROJECT ENGINEER

CITY OF SANTEE	DEPARTMENT OF DEVELOPMENT SERVICES	CITY W.O. NO.	DRAWING NO.
IMPROVEMENT PLANS FOR:	SANTEE COMMUNITY CENTER	CIP 2018-31	C1.4
	PARKING LOT GRADING AND PAVING PLAN		SHEET X OF X




LEGEND	
	CURB RAMP
	CONCRETE CROSS GUTTER/RIBBON GUTTER
	CATCH BASIN
	CLEANOUT
	SLOPE ARROW
	NEW CONTOUR
	NEW SPOT ELEVATION
	EXISTING CONTOUR (PER AERIAL SURVEY, ACCURACY OF ± 0.5')
	EXISTING ELEVATION (PER FIELD SURVEY, ACCURACY OF ± 0.1')
	EXISTING SPOT ELEVATION (PER AERIAL SURVEY, ACCURACY OF ± 0.5')
	NEW CONTOUR LINE
	DAYLIGHT LINE
	SAWCUT LINE
	RIDGE LINE
	GRADE BREAK
	CONCRETE CURB
	CONCRETE CURB AND GUTTER
	LIMITS OF WORK
	CONCRETE VEHICULAR PAVEMENT
	AC PAVEMENT
	CONCRETE SIDEWALK

- GRADING NOTES**
- CONSTRUCT CONCRETE CURB PER SDRSD G-01 6" CURB FACE UNLESS NOTED OTHERWISE.
 - CONSTRUCT CONCRETE CURB AND GUTTER PER SDRSD G-02 8" CURB FACE TYPE H.
 - CONSTRUCT TYPE A CURB RAMP PER SDRSD G-27.
 - CONSTRUCT CROSS GUTTER PER SDRSD G-12 WIDTH PER PLANS.
 - CONSTRUCT CONCRETE SIDEWALK PER DETAIL 4 SHEET C1.10.
 - CONSTRUCT CONCRETE VEHICULAR PAVEMENT PER DETAIL 3 SHEET C1.10.
 - CONSTRUCT ASPHALT CONCRETE PAVEMENT PER DETAIL 2 SHEET C1.10.
 - CONSTRUCT FENCE PER LANDSCAPE PLAN.
 - CONSTRUCT CURB CUT WITH RIP RAP APRON PER DETAIL 2 SHEET C1.11.
 - NOT USED
 - CONSTRUCT CURBSIDE GRATED CATCH BASIN PER SPPWC STD 303.4 SINGLE GRATE, V=5.77' (FD) WITH CASE F LOCAL DEPRESSION AT CATCH BASIN PER SPPWC STD 313.4.
 - CONSTRUCT TRASH ENCLOSURE PER ARCHITECT PLAN.
 - CONSTRUCT SEAT WALL PER LANDSCAPE PLAN.
 - CONSTRUCT BIOFILTRATION BASIN PER DETAIL 1 SHEET C1.11.
 - EXISTING PEDESTRIAN BRIDGE TO REMAIN.
 - CONSTRUCT CONCRETE DRIVEWAY (ALLEY TYPE) PER SDRSD G-14E.
 - CONSTRUCT 8" CURB WITH SIDEWALK UNDERDRAIN PER SDRSD D-27.
 - CONSTRUCT 12" CURB CUT PER DETAIL 2 ON SHEET 1 SHEET C1.11.
 - CONSTRUCT TYPE A 6" ROLLED CURB ALONG CONCRETE PAVEMENT ACCESS PER SDRSD G-34A WITH 8" LONG CURB TRANSITION ON EACH END PER SDRSD G-04B.
 - INSTALL DEMOUNTABLE POST PER SDRSD M-16.
 - CONSTRUCT TYPE D-3 CURB RAMP PER SDRSD G-31.
 - CONSTRUCT TYPE D-2 CURB PAMP PER SDRSD G-31.
 - CONSTRUCT COBBLE ENERGY DISSIPATION PER DETAIL 4 ON SHEET C1.11.
 - CONSTRUCT SIDEWALK UNDERDRAIN PER DETAIL 5 ON SHEET C1.11.
 - ELECTRICAL EQUIPMENT. SEE MEP PLANS FOR EQUIPMENT AND PAD CONSTRUCTION DETAILS.


- GENERAL GRADING NOTES**
- CONTRACTOR SHALL PROTECT IN PLACE OR ADJUST WHERE NECESSARY ALL EXISTING UTILITY LINES, WHETHER SHOWN OR NOT SHOWN ON THESE PLANS, THAT LAY WITHIN THE LIMITS OF THE NEW CONSTRUCTION, AND ARE NOT SPECIFICALLY MARKED TO BE REMOVED OR ABANDONED.
 - FINAL MANHOLE, VALVE BOXES AND VAULTS RIM ELEVATIONS SHALL BE ADJUSTED TO MEET FINAL GRADES.
 - CONTRACTOR TO VERIFY ALL EXISTING UTILITIES THAT ARE IN CONFLICT WITH THE PROJECT PRIOR TO THE START OF CONSTRUCTION AND NOTIFY THE ENGINEER OF RECORD OF ANY FOUND CONFLICTS. CONTRACTOR SHALL USE A 3RD PARTY UNDERGROUND UTILITY SERVICE TO DETERMINE THE LOCATION OF ALL ELECTRICAL, WATER, SEWER, AND IRRIGATION LINES.
 - THE LOCATION AND PROTECTION OF ALL UTILITIES IS THE RESPONSIBILITY OF THE CONTRACTOR.
 - JOIN ELEVATIONS SHOW APPROXIMATE. NEW CONCRETE JOINS SHALL MATCH EXISTING ELEVATIONS.
 - BUILDING PAD PREPARATION REFERENCE SHEET S0.01 FOR SOIL (GROUND) IMPROVEMENTS AND SHEET S3.02 FOR ADDITIONAL REQUIRED EXCAVATION AND CERTIFIED FILL BENEATH BUILDING.

SPECIAL GEOTECHNICAL NOTES


- GROUND IMPROVEMENT SPECIALTY CONTRACTOR SHALL SUBMIT PLANS AND DESIGN CALCULATIONS PRIOR TO CONSTRUCTION FOR APPROVAL. THE PLANS SHALL BE REVIEWED BY THE GEOTECHNICAL ENGINEER OF RECORD FOR CONCURRENCE THAT THEY MEET THE DESIGN INTENT NOTED IN THE PROJECT GEOTECHNICAL REPORT. THE GROUND IMPROVEMENT DESIGN PACKAGE SHALL INCLUDE QUALITY CONTROL PROCEDURES TO CONFIRM THE DESIGN BEARING CAPACITY AND LIQUEFACTION POTENTIAL MEET THE DESIGN INTENT. THE QUALITY CONTROL PROCEDURES SHALL INCLUDE AN INDICATOR MODULUS TEST (MT) PROGRAM AND A GROUND IMPROVEMENT TEST SECTION TO INDICATE PRE- AND POST- IMPROVEMENT BORINGS AND/OR CPTS ALONG WITH LIQUEFACTION ANALYSIS TO INDICATE THAT THE POST-GROUND IMPROVEMENT MEETS THE DESIGN INTENT.
- ALL GRADING WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE REQUIREMENTS AND RECOMMENDATIONS CONTAINED IN THE PROJECT SPECIFIC GEOTECHNICAL REPORT, PROJECT NUMBER IR786, BY GROUP DELTA, DATED JUNE 15, 2022.



IMPROVEMENT PLANS - SANTEE COMMUNITY CENTER, CIP 2018-31




- LEGEND**
- CONCRETE CURB
 - CONCRETE CURB AND GUTTER
 - SAWCUT LINE
 - PROPERTY LINE
 - LIMITS OF WORK
 - LANDSCAPE PER LANDSCAPE PLANS
 - CONCRETE VEHICULAR PAVEMENT
 - AC PAVEMENT
 - CONCRETE SIDEWALK



CONSTRUCTION RECORD		REFERENCES	DATE	BY	REVISIONS	ACPTD
CONTRACTOR						
INSPECTOR						
DATE COMPLETED						
BENCH MARK		THE BENCHMARK USED FOR THIS SURVEY IS GPS STATION "EP7" PER RECORD OF SURVEY 20986, BEING A STANDARD STREET SURVEY MONUMENT, M-10 WITH PUNCH ONLY. ELEVATION: 365.96 FEET FROM RDS 20986. FOR THE PURPOSES OF THIS SURVEY IT IS 366.05 FEET. DATUM: NAVD88				
SCALE		DESIGNED BY: SKC DRAWN BY: GPY CHECKED BY: EH PLANS PREPARED UNDER THE SUPERVISION OF SARAH CURRAN RCE NO. C69620 DATE 04/04/2025 EXPIRES 06/30/2026				
HORIZ: AS SHOW		REVIEWED: _____ BY: _____ PROJECT ENGINEER				
VERT: AS SHOW		CITY OF SANTEE IMPROVEMENT PLANS FOR: DEPARTMENT OF DEVELOPMENT SERVICES Santee Community Center HORIZONTAL CONTROL PLAN				
CITY OF SANTEE		CITY W.O. NO. CIP 2018-31		DRAWING NO. C1.5 SHEET X OF X		

Plotted - 3/4/2025 2:29:27 PM :: Saved - 2/14/2025 3:35:44 PM :: S:\HMC010100\CADD\Design\Sheets\HMC010100-HC.DWG :: chloee.lawson



Plotted - 3/4/2025 2:30:32 PM :: Saved - 1/18/2024 1:52:13 PM :: S:\5HMC010100\CADD\Design\Sheets\5HMC010100-HC PARKING LOT DWG :: chase lawson

CONSTRUCTION RECORD	REFERENCES	DATE	BY	REVISIONS	A
CONTRACTOR _____					
INSPECTOR _____					
DATE COMPLETED _____					


CPTD	BENCH MARK		SCALE	DESIGNED BY	DRAWN BY	CHECKED BY	REVIEWED _____ BY _____ PROJECT ENGINEER	CITY OF SANTEE		DEPARTMENT OF DEVELOPMENT SERVICES	CITY W.O. NO.	DRAWING NO.	IMPROV	
	THE BENCHMARK USED FOR THIS SURVEY IS GPS STATION "FP7" PER RECORD OF SURVEY 20986, BEING A STANDARD STREET SURVEY MONUMENT, M.L. 10 WITH PUNCH ONLY.		HORIZ: AS SHOW	SKC		GPY		PLANS PREPARED UNDER THE SUPERVISION OF SARAH CURRAN RCE NO. _____ C69620	IMPROVEMENT PLANS FOR:		SANTEE COMMUNITY CENTER PARKING LOT HORIZONTAL CONTROL PLAN	CIP 2018-31		C1.6
	ELEVATION: 355.96 FEET FROM ROS 20986, FOR THE PURPOSES OF THIS SURVEY IT IS 356.05 FEET.			DATE 04/04/2025		EXPIRES 06/30/2026								
	DATUM: NAVD88			VERT: AS SHOW										
SHEET X OF X														

SHEET C1.5 POINT TABLES

CURB/EP COORDINATES			CURB/EP COORDINATES			CURB/EP COORDINATES			CURB/EP COORDINATES			BLDG/WALL COORDINATES			BLDG/WALL COORDINATES			BLDG/WALL COORDINATES		
POINT #	NORTHING	EASTING	POINT #	NORTHING	EASTING	POINT #	NORTHING	EASTING	POINT #	NORTHING	EASTING	POINT #	NORTHING	EASTING	POINT #	NORTHING	EASTING	POINT #	NORTHING	EASTING
100	1890106.64	6338566.13	120	1890134.86	6338606.11	140	1890132.70	6338419.03	160	1890215.07	6338400.10	400	1890128.11	6338354.89	427	1890099.52	6338523.80	458	1889977.15	6338443.75
101	1890115.91	6338563.64	121	1890158.86	6338606.26	141	1890140.84	6338400.52	161	1890214.23	6338400.48	401	1890121.11	6338354.89	435	1890024.66	6338351.48	459	1890052.40	6338536.43
102	1890119.79	6338556.91	122	1890223.00	6338607.02	142	1890142.10	6338401.08	162	1890194.25	6338268.38	402	1890115.77	6338354.89	440	1890009.98	6338337.56	460	1890070.73	6338604.91
103	1890104.27	6338499.03	123	1890160.23	6338562.08	143	1890215.03	6338562.01	163	1890187.39	6338260.36	403	1890105.77	6338354.89	441	1890003.98	6338337.56	463	1890095.50	6338524.88
104	1890104.27	6338396.38	124	1890157.84	6338562.08	144	1890214.23	6338561.62	164	1890182.95	6338227.77	404	1890092.52	6338337.40	442	1890001.73	6338339.81	464	1889973.43	6338326.48
105	1890139.27	6338361.38	125	1890148.18	6338554.67	145	1890214.23	6338526.08	165	1890208.94	6338201.95	405	1890092.52	6338349.40	443	1890001.73	6338353.81	465	1889965.43	6338326.48
106	1890142.10	6338361.38	126	1890142.20	6338532.38	146	1890219.88	6338526.08	281	1890145.34	6338544.08	406	1890092.52	6338356.15	444	1890001.73	6338359.81	466	1889965.43	6338314.40
107	1890142.11	6338343.40	127	1890147.03	6338526.08	147	1890224.88	6338531.08	CENTER OF CURB RAMP COORDINATES			407	1890092.52	6338372.15	445	1890001.73	6338374.03	467	1890006.93	6338314.40
108	1890214.23	6338343.38	128	1890151.23	6338526.08	148	1890224.88	6338542.14				408	1890092.52	6338379.06	446	1890001.73	6338380.03	468	1890019.43	6338317.40
109	1890214.23	6338360.05	129	1890151.23	6338542.08	149	1890214.23	6338501.08				409	1890092.52	6338391.06	447	1890001.73	6338392.15	469	1890045.43	6338320.40
110	1890215.42	6338361.30	130	1890160.23	6338544.08	150	1890219.79	6338501.08				410	1890087.48	6338415.14	448	1890003.98	6338394.40	470	1890045.43	6338322.90
111	1890222.58	6338358.11	131	1890142.11	6338501.08	151	1890224.79	6338496.08				411	1890092.25	6338432.93	449	1890009.98	6338394.40	471	1890097.27	6338322.90
112	1890224.57	6338352.54	132	1890137.83	6338501.08	152	1890224.79	6338469.97	500	1890153.35	6338343.40	412	1890086.35	6338441.41	450	1890030.64	6338424.69	472	1890097.27	6338315.41
113	1890224.71	6338302.82	133	1890132.83	6338496.09	153	1890219.79	6338464.97	501	1890176.60	6338343.40	413	1890088.92	6338451.02	451	1890020.98	6338427.28	473	1890126.18	6338315.41
114	1890206.06	6338275.08	134	1890132.78	6338469.98	154	1890214.23	6338464.97	502	1890199.73	6338343.39	414	1890089.44	6338452.95	452	1890011.58	6338429.80	474	1890126.18	6338322.90
115	1890113.68	6338592.74	135	1890137.78	6338464.97	155	1890214.23	6338439.97	503	1890224.54	6338334.13	415	1890092.54	6338464.54	453	1890001.93	6338432.38	475	1890167.03	6338322.90
116	1890123.67	6338590.06	136	1890142.11	6338464.97	156	1890219.70	6338439.97	CENTER OF CURB RAMP COORDINATES			416	1890093.06	6338466.47	454	1890000.88	6338429.56	476	1890175.03	6338322.90
117	1890128.53	6338592.74	137	1890142.10	6338439.97	157	1890224.70	6338434.97				417	1890094.10	6338470.34	455	1889998.16	6338419.39	477	1890224.02	6338322.90
118	1890131.03	6338600.78	138	1890137.72	6338439.97	158	1890224.70	6338419.88				418	1890094.61	6338472.27	456	1889987.58	6338422.23			
119	1890131.04	6338606.08	139	1890132.72	6338434.98	159	1890216.27	6338401.17				419	1890095.94	6338477.21	457	1889992.26	6338439.70			

SHEET C1.6 POINT TABLES

CURB/EP COORDINATES			CURB/EP COORDINATES			CURB/EP COORDINATES			CURB/EP COORDINATES			CURB/EP COORDINATES			CURB/EP COORDINATES		
POINT #	NORTHING	EASTING	POINT #	NORTHING	EASTING	POINT #	NORTHING	EASTING	POINT #	NORTHING	EASTING	POINT #	NORTHING	EASTING	POINT #	NORTHING	EASTING
166	1890220.21	6338200.78	188	1890276.99	6337972.18	210	1890243.96	6338157.09	232	1890321.09	6338058.13	254	1890381.21	6338181.10	276	1890211.33	6337941.68
167	1890269.07	6338201.04	189	1890249.75	6337972.74	211	1890277.71	6338157.09	233	1890323.73	6338055.49	255	1890381.21	6337992.61	277	1890211.33	6337948.68
168	1890279.12	6338191.04	190	1890260.84	6338007.84	212	1890278.96	6338155.84	234	1890321.09	6338052.84	256	1890364.84	6337992.61	278	1890141.15	6337948.68
169	1890279.12	6338184.10	191	1890263.48	6338010.49	213	1890278.96	6338155.61	235	1890318.44	6338055.49	257	1890363.84	6337991.61	279	1890141.13	6337974.91
170	1890276.12	6338181.10	192	1890260.84	6338013.13	214	1890277.71	6338154.36	236	1890321.09	6338013.13	258	1890363.84	6337955.04	280	1890166.22	6337974.91
171	1890218.71	6338181.10	193	1890258.19	6338010.49	215	1890319.09	6338181.10	237	1890323.73	6338010.49	259	1890364.19	6337953.21	CENTER OF CURB RAMP COORDINATES		
172	1890218.71	6338157.45	194	1890260.84	6338052.84	216	1890302.96	6338184.10	238	1890321.09	6338007.84	260	1890366.86	6337950.45			
173	1890217.21	6338155.95	195	1890263.48	6338055.49	217	1890302.96	6338191.44	239	1890318.44	6338010.49	261	1890377.49	6337945.61			
174	1890200.72	6338155.95	196	1890260.84	6338058.13	218	1890312.96	6338201.44	240	1890319.09	6337992.49	262	1890395.04	6337941.74			
175	1890200.71	6337992.49	197	1890258.19	6338055.49	219	1890329.15	6338201.44	241	1890305.02	6337992.49	263	1890400.05	6337942.15			
176	1890217.57	6337992.49	198	1890260.84	6338097.84	220	1890339.15	6338191.44	242	1890303.02	6337990.49	264	1890405.04	6337943.21	504	1890279.12	6338189.19
177	1890219.07	6337990.99	199	1890263.48	6338100.49	221	1890339.15	6338184.10	243	1890303.02	6337969.99	265	1890410.02	6337945.64	505	1890302.96	6338189.19
178	1890219.07	6337976.41	200	1890260.84	6338103.13	222	1890336.15	6338181.10	244	1890303.86	6337969.01	266	1890413.45	6337953.22	506	1890339.15	6338189.19
179	1890217.57	6337974.91	201	1890258.19	6338100.49	223	1890305.96	6338181.10	245	1890337.86	6337961.05	267	1890414.93	6337909.28	507	1890362.87	6338189.19
180	1890190.22	6337974.91	202	1890260.84	6338142.84	224	1890321.09	6338148.13	246	1890339.15	6337962.00	268	1890411.05	6337916.34	508	1890200.72	6338144.45
181	1890242.71	6337979.74	203	1890263.48	6338145.49	225	1890323.73	6338145.49	247	1890339.15	6337991.49	269	1890405.92	6337918.35	509	1890200.72	6338121.20
182	1890242.71	6337990.99	204	1890260.84	6338148.13	226	1890321.09	6338142.84	248	1890338.15	6337992.49	270	1890400.93	6337917.97	510	1890200.71	6338094.95
183	1890244.21	6337992.49	205	1890258.19	6338145.49	227	1890318.44	6338145.49	249	1890382.27	6338201.65	271	1890395.82	6337917.65	511	1890213.83	6337974.91
184	1890258.84	6337992.49	206	1890258.84	6338154.36	228	1890321.09	6338103.13	250	1890372.81	6338201.60	272	1890367.08	6337923.88	512	1890213.82	6337948.68
185	1890277.12	6337992.49	207	1890243.96	6338154.36	229	1890323.73	6338100.49	251	1890362.86	6338191.55	273	1890258.53	6337948.68			
186	1890279.12	6337990.49	208	1890242.71	6338155.61	230	1890321.09	6338097.84	252	1890362.87	6338183.60	274	1890216.32	6337948.68			
187	1890279.12	6337974.17	209	1890242.71	6338155.84	231	1890318.44	6338100.49	253	1890365.37	6338181.10	275	1890216.32	6337941.68			




CONSTRUCTION RECORD		REFERENCES	DATE	BY	REVISIONS	ACPTD	BENCH MARK THE BENCHMARK USED FOR THIS SURVEY IS GPS STATION "EP7" PER RECORD OF SURVEY 20986, BEING A STANDARD STREET SURVEY MONUMENT, M-10 WITH PUNCH ONLY. ELEVATION: 365.96 FEET FROM RDS 20986, FOR THE PURPOSES OF THIS SURVEY IT IS 366.05 FEET. DATUM: NAVD88	SCALE	DESIGNED BY SKC	DRAWN BY GPY	CHECKED BY EH	REVIEWED _____ BY _____ PROJECT ENGINEER	CITY OF SANTEE		DEPARTMENT OF DEVELOPMENT SERVICES	CITY W.O. NO.	DRAWING NO.
CONTRACTOR						HORIZ: AS SHOW		PLANS PREPARED UNDER THE SUPERVISION OF SARAH CURRAN DATE 04/04/2025			IMPROVEMENT PLANS FOR: SANTÉE COMMUNITY CENTER HORIZONTAL CONTROL PLAN		CIP 2018-31	C1.7			
INSPECTOR						VERT: AS SHOW		RCE NO. C69620 EXPIRES 06/30/2026									
DATE COMPLETED													SHEET X OF X				



Plotted -- 3/4/2025 2:30:47 PM -- S: \\HMC010100\CADD\Design\Sheets\HMC010100-HC TABLES.DWG -- chases.tawson

IMPROVEMENT PLANS - SANTEE COMMUNITY CENTER, CIP 2018-31

Plotted - 3/4/2025 2:31:30 PM :: Saved - 9/12/2024 12:04:01 PM :: S:\SHM\010100\CADD\Design\Sheets\SHM\010100--SS.DWG :: chase.lawson



CONSTRUCTION RECORD	REFERENCES	DATE	BY	REVISIONS	ACPTD
CONTRACTOR					
INSPECTOR					
DATE COMPLETED					

BENCH MARK
THE BENCHMARK USED FOR THIS SURVEY IS GPS STATION "FP7" PER RECORD OF SURVEY 20986, BEING A STANDARD STREET SURVEY MONUMENT, M-10 WITH PUNCH ONLY. ELEVATION: 365.96 FEET FROM RDS 20986, FOR THE PURPOSES OF THIS SURVEY IT IS 386.05 FEET. DATUM: NAVD88

SCALE
HORIZ: AS SHOW
VERT: AS SHOW

DESIGNED BY SKC	DRAWN BY GPY	CHECKED BY EH
PLANS PREPARED UNDER THE SUPERVISION OF SARAH CURRAN		
RCE NO. C69620	DATE 04/04/2025	EXPIRES 06/30/2026


REVIEWED _____
BY _____ PROJECT ENGINEER

CITY OF SANTEE
IMPROVEMENT PLANS FOR:
SANTEE COMMUNITY CENTER
TRAFFIC SIGNAGE AND STRIPING PLAN

DEPARTMENT OF DEVELOPMENT SERVICES

CITY W.O. NO.
CIP 2018-31

DRAWING NO.
C1.8
SHEET X OF X



LEGEND

CONCRETE CURB

CONCRETE CURB AND GUTTER

25 FT FIRE ACCESS

PROPERTY LINE

LIMITS OF WORK

LANDSCAPE PER LANDSCAPE PLANS

CONCRETE VEHICULAR PAVEMENT

AC PAVEMENT

CONCRETE SIDEWALK

SAWCUT LINE

PAINTED STRIPE PER CONSTRUCTION NOTE

SIGN PER CONSTRUCTION NOTE

PEDESTRIAN CROSSWALK

- STRIPING NOTES**
- 1

PAINT TYPE 1 PAVEMENT ARROW PER CALTRANS STD PLAN A24A.
- 2

PAINT 12" WHITE STOP LINE PER 2018 CALTRANS STD PLAN A24E.
- 3

PAINT 10' WIDE YELLOW CROSS WALK CENTER ON RAMPS PER 2018 CALTRANS STD PLAN A24F.
- 4

PAINT 4" WHITE STRIPE.
- 5

INSTALL STOP SIGN & POST.
- 6

PAINT 8" TALL "STOP" PAVEMENT MARKING PER CALTRANS STD PLAN A24E.
- 7

INSTALL TOW AWAY SIGN, REFER TO DETAIL 5/A10.01
- 8

INSTALL FIRE LANE NO PARKING SIGN, REFER TO DETAIL 15/A10.01
- 9

INSTALL "ONE WAY" SIGN & POST. CALIFORNIA MUTCD R6-1.
- 10

PAINT TYPE 4 PAVEMENT ARROW PER CALTRANS STD PLAN A24A.
- 11

PAINT TYPE 7 PAVEMENT ARROW PER CALTRANS STD PLAN A24A.
- 12

PAINT 12" WHITE "NO PARKING" PER CALTRANS STD PLAN A24E
- 13

PAINT TOP AND FACE OF CURB RED FOR NO PARKING.

- SIGNING AND STRIPING NOTES**
1.


ALL STRIPING, MARKINGS AND LEGENDS SHALL BE REFLECTORIZED THERMOPLASTIC UNLESS OTHERWISE NOTED.
2.

REFER TO ARCHITECTURAL SHEET A1.22 FOR ACCESSIBLE PARKING STRIPING, SIGNAGE, TRUNCATED DOMES, AND WHEEL STOPS
- 1

= PAINT TOP & FACE OF CURB RED FOR NO PARKING.
- 2


= PAINT TOP & FACE OF CURB BLUE AT ADA STALLS.
3.

SIGNS TO BE INSTALLED ON BREAK-AWAY SIGN POSTS PER SDRSD M-45.



IMPROVEMENT PLANS - SANTEE COMMUNITY CENTER, CIP 2018-31

Plotted = 3/5/2025 9:17:58 AM :: Saved = 3/5/2025 9:16:40 AM :: S:\BHW\010100\CADD\Design Sheets\SHM\010100-UT.DWG :: chris.lawson




- LEGEND**
- S— S— SIDEWALK UNDERDRAIN
 - FW — FW — FIRE WATER SERVICE & BACKFLOW
 - W — W — DOMESTIC WATER SERVICE, BACKFLOW, & METER
 - SS — SS — SEWER LINE
 - SS — SS — SEWER MANHOLE
 - SD — SD — STORM DRAIN
 - UD — UD — UNDERDRAIN PIPE
 - CB — CB — CATCH BASIN
 - FH — FH — FIRE HYDRANT
 - X — X — CHAIN LINK FENCE/GATE
 - — — — — LIMITS OF WORK
 - — — — — PROPERTY LINE

- CONSTRUCTION NOTES**
1. CONSTRUCT 4" PVC (SDR 35) SEWER LINE. SLOPE PER PLAN. PIPE BEDDING AND TRENCH PER WAS SP-02.
 2. CONSTRUCT 6" PVC (SDR 35) SEWER LINE. SLOPE PER PLAN. PIPE BEDDING AND TRENCH PER WAS SP-02.
 3. CONSTRUCT SANITARY SEWER CLEANOUT PER WAS SC-01, TYPE A WITH SCREW CAP.
 4. CONSTRUCT 2" COPPER WATER LINE, PIPE BEDDING AND TRENCH PER WAS WP-02.
 5. CONSTRUCT HDPE STORM DRAIN LINE. SIZE, LENGTH, AND SLOPE PER PLAN. PIPE BEDDING AND TRENCH PER DETAIL SDRSD D-80.
 6. CONNECT TO EXISTING UTILITY. CONTRACTOR TO FIELD VERIFY LOCATION, DEPTH, SIZE AND CONDITION PRIOR TO CONSTRUCTION.
 7. CONSTRUCT 4" PVC STORM DRAIN LINE. LENGTH AND SLOPE PER PLAN. STUB OUT FOR CONNECTION TO BUILD DRAIN PER DETAIL. SEE STRUCTURAL/PLUMBING PLANS. PIPE BEDDING AND TRENCH PER DETAIL SDRSD D-80.
 8. CONSTRUCT GATE VALVE PER WAS WV-02.
 9. CONSTRUCT 24"x24" CATCH BASIN. PER DETAIL 5 SHEET C1.10. INCLUDE FLOGARD CATCH BASIN INSERT FILTER BY OLD CASTLE (MODEL NO. FGP-24F8) FOR TRASH CAPTURE OR EQUAL. SEE DETAIL 6, SHEET C1.11. INCLUDE STORM DRAIN SIGNAGE PER CASQA SD-13. SEE EXAMPLE DETAIL 7, SHEET C1.11.
 10. REFER TO PLUMBING SITE PLAN FOR CONNECTION, LOCATION AND ELEVATION.
 11. REFER TO FIRE PLANS FOR CONNECTION, LOCATION AND ELEVATION.
 12. INSTALL AND FURNISH (AS NOTED).
 13. CONSTRUCT THRUST BLOCK. CLASS 350 RATED WORKING PRESSURE. PER AWWA C110 WITH RESTRAINED JOINTS (U.N.O.). SIZE PER ADJOINING PIPE, ANGLE PER PLAN. SEE DETAIL 3, SHEET C1.11.
 14. CONSTRUCT BIOFILTRATION BASIN PER DETAIL 1 SHEET C1.11.
 15. CONSTRUCT 12" PVC STORM DRAIN. PIPE BEDDING AND TRENCH PER DETAIL SDRSD D-80.
 16. CONSTRUCT SANITARY SEWER MANHOLE PER WAS SM-01, TYPE A WITH SCREW CAP.
 17. CONSTRUCT STORM DRAIN CLEANOUT PER WAS SC-01, TYPE A WITH SCREW CAP.
 18. CONSTRUCT 6" FIRE WATER SERVICE PER WAS WF-05.
 19. CONSTRUCT NEW FIRE HYDRANT PER WAS WF-02.
 20. INSTALL FIRE DEPARTMENT CONNECTION SEE DETAIL 7 ON SHEET C1.10.
 21. CONSTRUCT POST INDICATOR VALVE SEE DETAIL 7 ON SHEET C1.10.
 22. CONNECTION TO PADRE DAM MAIN TO BE PERFORMED BY THE DISTRICT AT THE OWNERS EXPENSE.
 23. CONSTRUCT 2-INCH DOMESTIC WATER BACKFLOW PREVENTOR ASSEMBLY PER WAS WR-01, WITH STAINLESS STEEL PROTECTION CAGE AND FOUNDATION.
 24. PDMMO TO INSTALL. INSTALL 2" DOMESTIC WATER SERVICE PER WAS WS-02.
 25. CONSTRUCT UNDERDRAIN AS REQUIRED BY BIO RETENTION BASIN DETAIL 1 SHEET C1.11.
 26. CONSTRUCT BROOKS 24"x24" CATCH BASIN WITH GALVANIZED STEEL GRATE. OR APPROVED EQUAL. INSTALL 3" ORIFICE AT AN ELEVATION 3" ABOVE THE BASIN FINISH FLOOR. INCLUDE FLOGARD CATCH BASIN INSERT FILTER BY OLD CASTLE (MODEL NO. FGP-24F8) FOR TRASH CAPTURE OR EQUAL. SEE DETAIL 6, SHEET C1.11. INCLUDE STORM DRAIN SIGNAGE PER CASQA SD-13. SEE EXAMPLE DETAIL 7, SHEET C1.11.
 27. CONSTRUCT 6" PVC STORM DRAIN LINE.
 28. CONSTRUCT 8" PVC STORM DRAIN LINE.
 29. CONSTRUCT C900 PVC FIRE WATER LINE. PIPE BEDDING AND TRENCH PER WAS WP-02.
 30. CONSTRUCT 6-INCH REDUCED PRESSURE PRINCIPLE DETECTOR ASSEMBLY PER WAS WR-02, PRIMED AND PAINTED RED WITH 1/2" STAINLESS STEEL CHAIN FOR LOCKING HANDLES.
 31. CONSTRUCT CURBSIDE GRATING CATCH BASIN. SEE GRADING PLAN. INCLUDE FLOGARD CATCH BASIN INSERT FILTER BY OLD CASTLE (MODEL NO. FGP-24F8) FOR TRASH CAPTURE OR EQUAL. SEE DETAIL 6, SHEET C1.11. INCLUDE STORM DRAIN SIGNAGE PER CASQA SD-13. SEE EXAMPLE DETAIL 7, SHEET C1.11.
 32. HEADWALL PER DETAIL 6 SHEET C1.10.
 33. DEEPEN STRUCTURE TO CONFORM INVERT PER PLAN.
 34. CONSTRUCT STORM DRAIN MANHOLE PER SPPWC STD PLAN 321-2. SEE DETAIL 8, SHEET C1.10.


- NOTES**
1. MAINTAIN 10' CLEARANCE BETWEEN DOMESTIC AND SANITARY SEWER PIPES OUTSIDE DIAMETERS.
 2. DEPTH OF COVER BASED ON FINISHED SURFACE.
 3. EXISTING UTILITY LOCATIONS, SIZES, AND DEPTHS SHALL BE FIELD VERIFIED BY CONTRACTOR PRIOR TO CONSTRUCTION.
 4. PROVIDE PEDESTRIAN AND TRAFFIC RATED RIMS AND COVERS FOR RELOCATED OR ADJUSTED UTILITY STRUCTURES.
 5. NEW UTILITY STRUCTURES AND MANHOLES SHALL HOUSE TRAFFIC AND PEDESTRIAN RATED COVERS.
 6. REFERENCE MECHANICAL, ELECTRICAL AND TELECOMMUNICATION PLANS FOR DEMOLITION AND INSTALLATION OF M, E, & T UTILITIES AND STRUCTURE.
 7. REFERENCE LANDSCAPE PLANS FOR DEMOLITION AND INSTALLATION OF IRRIGATION LINES.

CONTRACTOR SHALL VERIFY LOCATION OF ALL UNDERGROUND UTILITIES AS DESCRIBED IN GENERAL NOTE 4 ON SHEET C1.0. CONTRACTOR TO USE 3RD PARTY PRIVATE UNDERGROUND UTILITY LOCATION SERVICE.




CONSTRUCTION RECORD					REFERENCES	DATE	BY	REVISIONS	ACPTD	BENCH MARK	SCALE	DESIGNED BY	DRAWN BY	CHECKED BY	REVIEWED	CITY OF SANTEE	DEPARTMENT OF DEVELOPMENT SERVICES	CITY W.O. NO.	DRAWING NO.
CONTRACTOR	INSPECTOR	DATE COMPLETED																	
										THE BENCHMARK USED FOR THIS SURVEY IS GPS STATION "FP7" PER RECORD OF SURVEY 20986, BEING A STANDARD STREET SURVEY MONUMENT, M-10 WITH PUNCH ONLY. ELEVATION: 365.96 FEET FROM RDS 20986. FOR THE PURPOSES OF THIS SURVEY IT IS 366.05 FEET. DATUM: NAVD83	HORIZ: AS SHOW VERT: AS SHOW	SKC	GPY	EH		IMPROVEMENT PLANS FOR:	SANTEE COMMUNITY CENTER CIVIL UTILITY PLAN	CIP 2018-31	C1.9 SHEET X OF X

IMPROVEMENT PLANS - SANTEE COMMUNITY CENTER, CIP 2018-31




CATCH BASIN DETAIL 5
N.T.S. C1.10




- NOTE:**
1. AC STRUCTURAL SECTIONS ARE FOR ESTIMATING PURPOSES ONLY AND SHALL BE BASED ON SUBGRADE TESTS BY THE GEOTECHNICAL ENGINEER PRIOR TO PLACEMENT OF BASE MATERIAL.
 2. OVER EXCAVATE AND RECOMPACT 1-FT BELOW PAVEMENT SECTION PER GEOTECHNICAL REPORT.

ASPHALT PAVEMENT DETAIL 2
N.T.S. C1.10




- NOTE:**
1. OVER EXCAVATE AND RECOMPACT 1-FT BELOW PAVEMENT SECTION PER GEOTECHNICAL REPORT.

CONCRETE VEHICULAR PAVEMENT DETAIL 3
N.T.S. C1.10





- NOTE:**
1. OVER EXCAVATE AND RECOMPACT 1-FT BELOW PAVEMENT SECTION PER GEOTECHNICAL REPORT.

CONCRETE WALK DETAIL 4
N.T.S. C1.10



8" HEADWALL 6
N.T.S. C1.10



FIRE DEPARTMENT CONNECTION AND POST INDICATOR VALVE DETAIL 7
N.T.S. C1.10

N.T.S.

NOTES:

1. FIRE MARSHAL SHALL SPECIFY LOCATION OF FIRE DEPARTMENT CONNECTION (FDC). CLEARANCE AROUND FDC SHALL BE 3 FEET RIGHT, LEFT, REAR, AND 20 FEET IN FRONT.
2. A METAL SIGN WITH RAISED LETTERS AT LEAST 1 INCH IN SIZE SHALL BE MOUNTED ON ALL FIRE DEPARTMENT CONNECTIONS SERVICING AUTO SPRINKLERS, STANDPIPES OR FIRE PUMPS. SUCH SIGNS SHALL READ "AUTO SPRINKLER", "STANDPIPE", OR "TEST CONNECTION" AS APPLICABLE. WHERE THE FDC DOES NOT SERVE THE ENTIRE BUILDING A SIGN SHALL BE PROVIDED INDICATING THE PORTIONS OF THE BUILDING TO BE SERVED.
3. FIRE PROTECTION FACILITIES ARE OWNED AND MAINTAINED BY THE CUSTOMER.
4. ASSEMBLIES AND PIPING ON FIRE LINES SHALL BE FM/UL AND CONFORM TO THE APPLICABLE NFPA. THRUST BLOCKING AND/OR MECHANICAL RESTRAINTS SHALL BE PROVIDED AS NECESSARY.
5. STANDPIPE MATERIALS AND DEVICES MUST BE OF SUFFICIENT STRENGTH TO WITHSTAND A MINIMUM OF 200 PSI.
6. ALL FERROUS MATERIAL PRODUCTS THAT WILL INTERACT WITH THE SOIL WHEN INSTALLED SHALL BE PROPERLY COATED FOR CORROSION PROTECTION PER GEOTECH REPORT.

Plotted - 3/4/2025 2:33:14 PM :: Saved - 2/24/2025 5:36:21 PM :: S:\SHWC010100\CADD\Design\Sheets\SHWC010100-DTDWG :: chase.lawson

CONSTRUCTION RECORD	REFERENCES	DATE	BY	REVISIONS	ACPTD
CONTRACTOR					
INSPECTOR					
DATE COMPLETED					

BENCH MARK
THE BENCHMARK USED FOR THIS SURVEY IS GPS STATION "FP7" PER RECORD OF SURVEY 20986, BEING A STANDARD STREET SURVEY MONUMENT, M-10 WITH PUNCH ONLY. ELEVATION: 365.96 FEET FROM ROS 20986, FOR THE PURPOSES OF THIS SURVEY IT IS 366.05 FEET. DATUM: NAVD88

SCALE	DESIGNED BY	DRAWN BY	CHECKED BY
HORIZ: AS SHOW	SKC	GPY	EH
VERT: AS SHOW	PLANS PREPARED UNDER THE SUPERVISION OF SARAH CURRAN	DATE 04/04/2025	DATE 06/30/2026
	RCE NO. C69620		



REVIEWED	BY
	PROJECT ENGINEER

CITY OF SANTEE	DEPARTMENT OF DEVELOPMENT SERVICES	CITY W.O. NO.	DRAWING NO.
IMPROVEMENT PLANS FOR:	SANTEE COMMUNITY CENTER CIVIL DETAILS	CIP 2018-31	C1.10
			SHEET X OF X



IMPROVEMENT PLANS - SANTEE COMMUNITY CENTER, CIP 2018-31


Printed = 3/5/2025 9:18:36 AM : : Saved = 3/5/2025 8:58:36 AM : : S:\HW\010100\CADD\Design\Sheet\SHWC010100-D1.DWG : : chsae.lawson





SECTION A-A

- BIOFILTRATION PROTECTION DURING CONSTRUCTION:
1. PREVENT OVER-COMPACTION OF NATIVE SOILS IN AREAS OF THE BASIN WHERE INFILTRATION WILL OCCUR. DELINEATE THE BIOFILTRATION AREA AND KEEP CONSTRUCTION TRAFFIC OFF. PROTECT SOILS WITH FENCING, PLYWOOD, ETC.
 2. PROVIDE EROSION CONTROL IN THE CONTRIBUTING DRAINAGE AREAS OF THE DESIGNATED BIOFILTRATION AREA. STABILIZE UPSLOPE AREAS.
 3. DRAINAGE SHOULD BE DIRECTED AWAY FROM BIORETENTION FACILITIES UNTIL UPSLOPE AREAS ARE STABILIZED. THE CONCENTRATION OF FINES COULD PREVENT POST-CONSTRUCTION INFILTRATION AND CAUSE DESIGN FAILURE.
 4. IF DRAINAGE IS TO BE ALLOWED THROUGH THE FACILITY DURING CONSTRUCTION LEAVE OR BACKFILL AT LEAST 6 INCHES ABOVE THE FINAL GRADE. TEMPORARILY COVER THE UNDERDRAIN WITH PLASTIC OR FABRIC. LINE OR MULCH THE BIOFILTRATION AREA.
 5. BIORETENTION FACILITIES SHOULD REMAIN OUTSIDE THE LIMIT OF DISTURBANCE TO PREVENT SOIL COMPACTION BY HEAVY EQUIPMENT. PROTECT BIORETENTION AREAS WITH SILT FENCE AND CONSTRUCTION FENCING.
 6. VERIFY INSTALLATION OF UNDERDRAIN IS CORRECT PRIOR TO PLACING SOIL.

BIOFILTRATION BASIN DETAIL 1
N.T.S. C1.11




COBBLE ENERGY DISSIPATION AT STORM PIPE OUTLETS 4
N.T.S. C1.11




CURB CUT INLET DETAIL 2
N.T.S. C1.11

- BIORETENTION DESIGN NOTES
1. FOR USE WITH STORMWATER FACILITIES WITH SIDE SLOPES.
 2. PROVIDE SPOT ELEVATIONS ON PLANS (F.E., O.E., G.I.E., I.E.) REFER TO GRADING SHEETS FOR SPOT ELEVATIONS.
 3. CURB AND WALL DETAILS MAY BE MODIFIED BY CIVIL AND GEOTECHNICAL ENGINEERS SUBJECT TO APPROVAL BY CITY ENGINEER.
 4. WHERE INLET FLOW VELOCITY IS HIGH, EXTEND COBBLE INTO FACILITY, BUT AVOID EXCESSIVE USE.
- CONSTRUCTION NOTES
1. AFTER CONSTRUCTION PLACE SAND BAGS AT GUTTER OPENINGS TO KEEP STORM FLOWS FROM ENTERING FACILITY UNTIL VEGETATION IS ESTABLISHED.




SIDEWALK UNDERDRAIN 5
N.T.S. C1.11

- NOTES:
1. CONCRETE SHALL BE 500-C-3250.
 2. SLOPE OF DRAINAGE CHANNEL TO BE SLOPED TOWARDS BIORETENTION BASIN. SLOPES OF FINISHED SIDEWALK PER PLAN.
 3. SIDEWALK FINISH TO MATCH ADJACENT SIDEWALK.
 4. PROVIDE 3\"/>
 5. THIS DETAIL IS A MODIFICATION OF SDRSD D-25A.



CONCRETE THRUST AND ANCHOR BLOCK INSTALLATIONS 3
N.T.S. C1.11



U.S. PATENT # 6,000,023 & 6,877,029

FloGard®
Stormwater Solutions
Catch Basin Insert Filter
Grated Inlet Style

Oldcastle®
Stormwater Solutions
7921 Southpark Plaza, Suite 200 | Littleton, CO 80120 | PH: 800.579.8819 | oldcastlestormwater.com
THIS DOCUMENT IS THE PROPERTY OF OLDCASTLE STORMWATER SOLUTIONS. IT IS TO BE USED FOR THE PROJECT AND NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM. WITHOUT PERMISSION IN WRITING FROM OLDCASTLE STORMWATER SOLUTIONS, NO PART OF THIS DOCUMENT MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM.

FGP-0001 G ECD-0142 JPR 7/13/16 JPR 11/3/06 SHEET 1 OF 2

U.S. PATENT # 6,000,023 & 6,877,029

FGP-0001

“ULTIMATE” BYPASS FEATURE
(LOUVERS & OPENINGS)
SEE DETAIL C

DEPTH
STANDARD SHALLOW = 12 INCHES
CUSTOM

DETAIL B
SECTION VIEW
Flogard® FILTER
-INSTALLED-

DETAIL C
“ULTIMATE”
BYPASS FEATURES

* MANY OTHER STANDARD & CUSTOM SIZES & DEPTHS AVAILABLE UPON REQUEST.

SPECIFIER CHART											
STANDARD & SHALLOW DEPTH (Data in these columns is the same for both STANDARD & SHALLOW versions)		STANDARD DEPTH -20 inches-				SHALLOW DEPTH -12 inches-					
MODEL NO.	STANDARD DEPTH	INLET ID Inside Dimension (inch x inch)	GRATE OD Outside Dimension (inch x inch)	TOTAL BYPASS CAPACITY (cu. ft. / sec.)	SOLIDS STORAGE CAPACITY (cu. ft.)	MODEL NO.	SHALLOW DEPTH	INLET ID Inside Dimension (inch x inch)	GRATE OD Outside Dimension (inch x inch)	TOTAL BYPASS CAPACITY (cu. ft. / sec.)	SOLIDS STORAGE CAPACITY (cu. ft.)
FGP-12F	12 X 12	12 X 14	2.8	0.3	0.4	FGP-12FB	12 X 12	12 X 14	2.8	0.3	0.4
FGP-16F	16 X 16	16 X 18	4.7	0.8	0.7	FGP-16FB	16 X 16	16 X 18	4.7	0.8	0.7
FGP-18F	18 X 18	18 X 20	4.7	0.8	0.7	FGP-18FB	18 X 18	18 X 20	4.7	0.8	0.7
FGP-1824F	18 X 22	18 X 24	5.0	1.5	1.2	FGP-1824FB	18 X 22	18 X 24	5.0	1.5	1.2
FGP-1836F	18 X 36	18 X 40	6.9	2.3	1.6	FGP-1836FB	18 X 36	18 X 40	6.9	2.3	1.6
FGP-2024F	18 X 22	20 X 24	5.9	1.2	1.0	FGP-2024FB	18 X 22	20 X 24	5.9	1.2	1.0
FGP-21F	22 X 22	22 X 24	6.1	2.2	1.5	FGP-21FB	22 X 22	22 X 24	6.1	2.2	1.5
FGP-24F	24 X 24	24 X 27	6.1	2.2	1.5	FGP-24FB	24 X 24	24 X 27	6.1	2.2	1.5
FGP-2436F	24 X 30	26 X 30	7.0	2.8	1.8	FGP-2436FB	24 X 30	26 X 30	7.0	2.8	1.8
FGP-2436F	24 X 36	24 X 40	8.0	3.4	2.0	FGP-2436FB	24 X 36	24 X 40	8.0	3.4	2.0
FGP-2448F	24 X 48	26 X 48	9.5	4.4	2.4	FGP-2448FB	24 X 48	26 X 48	9.5	4.4	2.4
FGP-28F	28 X 28	32 X 32	6.3	2.2	1.5	FGP-28FB	28 X 28	32 X 32	6.3	2.2	1.5
FGP-30F	30 X 30	30 X 34	8.1	3.6	2.0	FGP-30FB	30 X 30	30 X 34	8.1	3.6	2.0
FGP-36F	36 X 36	36 X 40	9.1	4.6	2.4	FGP-36FB	36 X 36	36 X 40	9.1	4.6	2.4
FGP-3648F	36 X 48	40 X 48	11.5	6.8	3.2	FGP-3648FB	36 X 48	40 X 48	11.5	6.8	3.2
FGP-48F	48 X 48	48 X 54	13.2	9.5	3.9	FGP-48FB	48 X 48	48 X 54	13.2	9.5	3.9
FGP-SD24F	24 X 24	28 X 28	6.1	2.2	1.5	FGP-SD24FB	24 X 24	28 X 28	6.1	2.2	1.5

Flogard®

Catch Basin Insert Filter

Grated Inlet Style

Oldcastle®
Stormwater Solutions

7701 Southpark Plaza, Suite 200 | Littleton, CO 80120 | Tel: 800.579.8819 | oldcastlestormwater.com
 THIS DOCUMENT IS THE PROPERTY OF OLDCASTLE STORMWATER SOLUTIONS. IT IS TO BE USED FOR THE PROJECT AND SITE SPECIFICALLY IDENTIFIED. IT IS NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN PERMISSION OF OLDCASTLE STORMWATER SOLUTIONS.

FGP-0001

G

JPR 7/13/16

JPR 11/3/06


SHEET 2 OF 2

FLOGARD CATCH BASIN INSERT FILTER 6
N.T.S. C1.11

CONSTRUCTION RECORD	REFERENCES	DATE	BY	REVISIONS	ACPTD	SCALE	DESIGNED BY	DRAWN BY	CHECKED BY	REVIEWED	CITY OF SANTEE	DEPARTMENT OF DEVELOPMENT SERVICES	CITY W.O. NO.	DRAWING NO.
CONTRACTOR						HORIZ: AS SHOW	SKC	GPY	EH		IMPROVEMENT PLANS FOR:	SANTEE COMMUNITY CENTER	CIP 2018-31	C1.11
INSPECTOR						VERT: AS SHOW	PLANS PREPARED UNDER THE SUPERVISION OF	SARAH CURRAN	DATE 04/04/2025	BY	PROJECT ENGINEER	CIVIL DETAILS		SHEET X OF X
DATE COMPLETED							RCE NO. C69620		EXPIRES 06/30/2026					

THE BENCHMARK USED FOR THIS SURVEY IS GPS STATION "FP7" PER RECORD OF SURVEY 20986, BEING A STANDARD STREET SURVEY MONUMENT, M-10 WITH PUNCH ONLY. ELEVATION: 365.96 FEET FROM ROS 200986. FOR THE PURPOSES OF THIS SURVEY IT IS 386.05 FEET. DATUM: NAVD88

Plotted - 3/4/2025 2:34:24 PM :: Saved - 2/25/2025 3:10:55 PM :: S:\HMC010100\CADD\Design\Sheets\HMC010100-EC.DWG :: chosel.lawson




LEGEND

- INSTALL CONTINUOUS SILT FENCE PER CALTRANS CONSTRUCTION SITE BMP MANUAL (2017) SC-1
- INSTALL CONTINUOUS GRAVEL BAG CHECK DAM ON TOP OF EXISTING PAVEMENT (NO GAPS) (SE-6)
- INSTALL GRAVEL BAG INLET PROTECTION AT ALL INLETS EXPOSED TO CONSTRUCTION RUNOFF PER DETAIL THIS SHEET. (SE-10)
- LIMITS OF WORK
- INSTALL TEMPORARY CONSTRUCTION FENCING. MAINTAIN 4' MINIMUM WALKWAY CLEARANCE WHERE FENCE IS INSTALLED ON SIDEWALK. AREAS OF SOIL DISTURBANCE TO BE LIMITED TO WITHIN THE PROPOSED FENCE LINE.
- PROPOSED CONTOUR
- PROPOSED SPOT ELEVATION
- EXISTING CONTOUR
- EXISTING SPOT ELEVATION
- EXISTING TREE
- FLOW ARROW
- CONSTRUCTION ENTRANCE PER CALTRANS C9ONSTRUCTION SITE BMP MANUAL (2017) (TC-1)
- PROPOSED DRAINAGE MANAGEMENT AREA (DMA). SEE PROPOSED DMA EXHIBIT FOR MORE DETAIL.

GENERAL NOTES

- REFER TO THE LATEST EDITION OF THE CALIFORNIA STORMWATER BEST MANAGEMENT PRACTICE HANDBOOK FOR THE BMP OUTLINED ON THIS PLAN.
- INSTALL INLET PROTECTION ON ALL EXISTING INLETS PRIOR TO DEMOLITION.
- SAMPLING LOCATIONS SHOWN MAY BE MODIFIED IN THE FIELD DURING STORM EVENTS AT THE DISCRETION OF THE QSP.
- THE LOCATION AND PROTECTION OF ALL UTILITIES IS THE RESPONSIBILITY OF THE CONTRACTOR.



SC-10
GRAVEL BAG INLET PROTECTION
N.T.S.

BEST MANAGEMENT PRACTICES:

- EVERY EFFORT SHOULD BE MADE TO ELIMINATE THE DISCHARGE OF NON-STORMWATER FROM THE PROJECT SITE AT ALL TIMES.
- ERODED SEDIMENTS AND OTHER POLLUTANTS MUST BE RETAINED ON-SITE AND MAY NOT BE TRANSPORTED FROM THE SITE VIA SHEET FLOW, SWALES, AREA DRAINS, NATURAL DRAINAGE COURSES OR WIND.
- STOCKPILES OF EARTH AND OTHER CONSTRUCTION RELATED MATERIALS MUST BE PROTECTED FROM BEING TRANSPORTED FROM THE SITE BY THE FORCES OF WIND OR WATER.
- FUELS, OILS, SOLVENTS, AND OTHER TOXIC MATERIALS MUST BE STORED IN ACCORDANCE WITH THEIR LISTING AND ARE NOT TO CONTAMINATE THE SOIL AND SURFACE WATERS. ALL APPROVED STORAGE CONTAINERS ARE TO BE PROTECTED FROM THE WEATHER. SPILLS MUST BE CLEANED UP IMMEDIATELY AND DISPOSED OF IN A PROPER MANNER. SPILLS MAY NOT BE WASHED INTO THE DRAINAGE SYSTEM.
- EXCESS OR WASTE CONCRETE MAY NOT BE WASHED INTO THE PUBLIC WAY OR ANY OTHER DRAINAGE SYSTEM. PROVISIONS SHALL BE MADE TO RETAIN CONCRETE WASTES ON-SITE UNTIL THEY CAN BE DISPOSED OF AS SOLID WASTE.
- TRASH AND CONSTRUCTION RELATED SOLID WASTES MUST BE DEPOSITED INTO A COVERED RECEPTACLE TO PREVENT CONTAMINATION OF RAINWATER AND DISPERSAL BY WIND.
- SEDIMENTS AND OTHER MATERIALS MAY NOT BE TRACKED FROM THE SITE BY VEHICLE TRAFFIC. THE CONSTRUCTION ENTRANCE ROADWAYS MUST BE STABILIZED SO AS TO INHIBIT SEDIMENTS FROM BEING DEPOSITED INTO THE PUBLIC WAY. ACCIDENTAL DEPOSITIONS MUST BE SWEEPED UP IMMEDIATELY AND MAY NOT BE WASHED DOWN BY RAIN OR OTHER MEANS.
- THESE FOLLOWING BMPs AS OUTLINED IN, BUT NOT LIMITED TO, THE LATEST EDITION OF THE CASQA CONSTRUCTION BMP ONLINE HANDBOOK OR CALTRANS STORM WATER QUALITY HANDBOOKS (CONSTRUCTION SITE BMP MANUAL) MAY APPLY DURING THE CONSTRUCTION OF THIS PROJECT AND APPLY TO THE ENTIRETY OF THE PROJECT SITE.

EROSION CONTROL

- EC1 SCHEDULING
- EC2 PRESERVATION OF EXISTING VEGETATION

TEMPORARY SEDIMENT CONTROL

- SE6 GRAVEL BAG BERM
- SE7 STREET SWEEPING
- SE8 SANDBAG BARRIER
- SE10 TEMPORARY DRAINAGE INLET PROTECTION

WIND EROSION CONTROL

- WE1 WIND EROSION CONTROL

WASTE MANAGEMENT & MATERIAL POLLUTION CONTROL

- WM1 MATERIAL DELIVERY AND STORAGE
- WM2 MATERIAL USE
- WM3 STOCKPILE MANAGEMENT
- WM4 SPILL PREVENTION AND CONTROL
- WM5 SOLID WASTE MANAGEMENT
- WM9 SANITARY/SEPTIC WASTE MANAGEMENT
- WM10 LIQUID WASTE MANAGEMENT

EQUIPMENT TRACKING CONTROL

- TC1 TEMPORARY CONSTRUCTION ENTRANCE/EXIT

NON-STORMWATER MANAGEMENT

- NS1 WATER CONSERVATION PRACTICES
- NS3 PAVING AND GRINDING OPERATIONS
- NS6 ILLICIT CONNECTION/DISCHARGE
- NS7 POTABLE WATER/IRRIGATION
- NS8 VEHICLE AND EQUIPMENT CLEANING
- NS9 VEHICLE AND EQUIPMENT FUELING
- NS10 VEHICLE AND EQUIPMENT MAINTENANCE
- NS15 DEMOLITION ADJACENT TO WATER

CITY OF SANTEE STORMWATER-SPECIFIC BMP NOTES:

- THIS PROJECT SHALL COMPLY WITH ALL REQUIREMENTS OF THE CITY OF SANTEE AND STATE OF CALIFORNIA WATER QUALITY CONTROL BOARD, SAN DIEGO REGION
- THE CONTRACTOR SHALL IMPLEMENT BEST MANAGEMENT PRACTICES (BMPs) DURING ALL PHASES OF CONSTRUCTION.
 - SUFFICIENT BMPs MUST BE INSTALLED TO PREVENT SILT, MUD, OR OTHER CONSTRUCTION DEBRIS FROM BEING TRACKED INTO THE ADJACENT STREET(S) OR STORM WATER CONVEYANCE SYSTEMS DUE TO CONSTRUCTION VEHICLES OR ANY OTHER CONSTRUCTION ACTIVITY. THE CONTRACTOR SHALL BE RESPONSIBLE FOR CLEANING ANY SUCH DEBRIS THAT MAY BE IN THE STREET OR CONVEYANCE SYSTEM AT THE ENDS OF EACH WORK DAY OR AFTER A STORM EVENT THAT CAUSED A BREACH IN THE INSTALLED CONSTRUCTION BMPs.
 - STORM WATER POLLUTION PREVENTION DEVICES AND OR PRACTICES SHALL BE MODIFIED AS NEEDED AS THE PROJECT PROGRESSES TO ENSURE EFFECTIVENESS. IF AT ANY TIME, BMPs ARE FOUND TO BE INTENTIONALLY DISABLED, RUN-OVER, REMOVED, OR OTHERWISE INEFFECTIVE, THEY SHALL BE MODIFIED AND REPLACED IMMEDIATELY.
 - TRASH AND CONSTRUCTION SOLID WASTES SHALL BE DEPOSITED INTO A COVERED RECEPTACLE TO PREVENT CONTAMINATION OF RAINWATER AND DISPERSAL BY WIND. THE STORAGE OF ALL CONSTRUCTION MATERIALS AND CONSTRUCTION WASTES MUST BE PROTECTED AGAINST THE POTENTIAL RELEASE OF POLLUTANTS INTO THE ENVIRONMENT.
 - A CONCRETE WASHOUT SHALL BE PROVIDED ON ALL PROJECTS WHICH PROPOSE THE CONSTRUCTION OF ANY CONCRETE IMPROVEMENTS THAT ARE TO BE POURED IN PLACE ON THE SITE.
 - ALL BMPs SHALL BE MAINTAINED IN WORKING ORDER AT ALL TIMES. ALL SLOPES THAT ARE CREATED OR DISTURBED BY CONSTRUCTION ACTIVITY MUST BE PROTECTED AGAINST EROSION AND SEDIMENT TRANSPORT AT ALL TIMES.
 - IF TRENCHING/DIGGING ACTIVITIES ARE NOT COMPLETED WITHIN ONE DAY, PROPER BMPs WILL BE IMPLEMENTED.
 - IF DEBRIS OR MATERIALS WILL BE STORED FOR LONGER THAN ONE DAY, PROPER BMPs WILL BE IMPLEMENTED.

GRAVEL BAG CHEVRON
N.T.S.

GRAPHIC SCALE
1 INCH = 40 FEET



CONSTRUCTION RECORD	REFERENCES	DATE	BY	REVISIONS	ACPTD	BENCH MARK	SCALE	DESIGNED BY	DRAWN BY	CHECKED BY	REVIEWED	CITY OF SANTEE	DEPARTMENT OF DEVELOPMENT SERVICES	CITY W.O. NO.	DRAWING NO.
CONTRACTOR						THE BENCHMARK USED FOR THIS SURVEY IS GPS STATION "EP7" PER RECORD OF SURVEY 20986, BEING A STANDARD STREET SURVEY MONUMENT, M-10 WITH PUNCH ONLY. ELEVATION: 355.96 FEET FROM RGS 20986, FOR THE PURPOSES OF THIS SURVEY IT IS 356.05 FEET. DATUM: NAVD83	HORIZ: AS SHOW VERT: AS SHOW	SKC	GPY	EH		IMPROVEMENT PLANS FOR:	SANTEE COMMUNITY CENTER EROSION CONTROL PLAN	CIP 2018-31	C1.12 SHEET X OF X
INSPECTOR								PLANS PREPARED UNDER THE SUPERVISION OF SARAH CURRAN		DATE 04/04/2025	BY PROJECT ENGINEER				
DATE COMPLETED								RCE NO. C69620		EXPIRES 06/30/2026					

IMPROVEMENT PLANS - SANTEE COMMUNITY CENTER, CIP 2018-31